



OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 14 - Plastics Piping System Components and Related Materials

This is the Official Listing recorded on October 5, 2016.

Performance Pipe
A Div. of Chevron Phillips Chem Co., LP
5085 West Park Boulevard
Suite 500
Plano, TX 75093
972-599-6600



Facility: Knoxville, TN

Gas Applications - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe # * S	PE 2406/2708	DriscoPlex® 6500	ASTM D2513
1/2" - 12"			
Pipe * ¢	PE 2406/2708	DriscoPlex® 6500	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			
1/2" - 12" SDR 21			
Pipe # * S	PE 4710	Driscopipe® 8100	ASTM D2513
1/2" - 12"			
Pipe * ¢	PE 4710	Driscopipe® 8100	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			
1/2" - 12" SDR 21			
Pipe # * S	PE 4710	YELLOWSTRIPE® 8300	ASTM D2513
1/2" - 12"			
Pipe * ¢	PE 4710	YELLOWSTRIPE® 8300	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			
1/2" - 12" SDR 21			

All sizes between 1/2" and 12" with a DR of 11 or thinner are Certified.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



% Only those products identified in Listing are Certified.

* Gas pipe and tubing limited to outside underground use only.

¢ Product is authorized to bear the cNSF and/or the cNSFus Mark.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

NOTE: NSF Certified materials and generic ingredients are exempt from bearing an NSF Certification Mark. Certified materials and generic ingredients are identified by the manufacturer name, facility and trade designation as shown in the Official Listing.

Facility: Reno, NV

Gas Applications - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe # % * §	PE 2406/2708	DriscoPlex® 6500	ASTM D2513
1/2" - 12"			
Pipe % * ¢	PE 2406/2708	DriscoPlex® 6500	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			
1/2" - 12" SDR 21			
Pipe % * ¢	PE 4710	Driscopipe® 8100	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			
1/2" - 12" SDR 21			
Pipe # % * §	PE 4710	YELLOWSTRIPE® 8300	ASTM D2513
1/2" - 12"			
Pipe % * ¢	PE 4710	YELLOWSTRIPE® 8300	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			
1/2" - 12" SDR 21			

All sizes between 1/2" and 12" with a DR of 11 or thinner are Certified.

% Only those products identified in Listing are Certified.

* Gas pipe and tubing limited to outside underground use only.

¢ Product is authorized to bear the cNSF and/or the cNSFus Mark.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

NOTE: NSF Certified materials and generic ingredients are exempt from bearing an NSF Certification Mark. Certified materials and generic ingredients are identified by the manufacturer name, facility and trade designation as shown in the Official Listing.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



Facility: Fairfield, IA

Potable Water - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe * + [G]	PE 4710	DriscoPlex PW	ASTM D2239
1/2" - 2" SIDR 5.3			
1/2" - 2" SIDR 7			
1/2" - 2" SIDR 9			
1/2" - 3" SIDR 13.5			
1/2" - 3" SIDR 15			
1/2" - 2" SIDR 19			
Pipe * + [G]	PE 4710	DriscoPlex PW	ASTM D3035
1/2" - 24" DR 7			
1/2" - 24" DR 9			
1/2" - 24" DR 9.3			
1/2" - 24" DR 11			
1/2" - 24" DR 13.5			
1/2" - 24" DR 15.5			
1/2" - 24" DR 17			
1/2" - 24" DR 21			
1/2" - 24" DR 26			
1/2" - 24" DR 32.5			
Pipe * + [G]	PE 4710	DriscoPlex PW	ASTM F714
3" - 18" SDR 7.3DR 11			
3" - 20" SDR 8.3DR 13.5			
3" - 20", 22", 24" SDR 9			
3" - 20", 22" - 30" SDR 9.3			
3" - 20", 22" - 36" SDR 11			
3" - 36" SDR 13.5			
3" - 48" SIDR 15.5			
3" - 54" SDR 17			
3" - 54" SDR 21			
3" - 54" SDR 26			
3" - 54" SDR 32.5			
3" - 54" SDR 41			
Pipe * + [G]	PE 4710	DriscoPlex PW	ASTM D2737
1/2" - 2" SDR 7.3			
1/2" - 2" SDR 9			
1/2" - 2" SDR 11			
Pipe * + [G]	PE 4710	DriscoPlex PW	ANWA C901
1/2" - 3" SIDR 5.3			
1/2" - 3" SIDR 7			
1/2" - 3" SIDR 9			
3/4" - 3" SIDR 11.5			
2" - 3" SIDR 15			
2" - 3" SIDR 19			
1/2" - 3" SDR 7.3			

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



1/2" - 3"	SDR 9			
1/2" - 3"	SDR 11			
3/4" - 3"	SDR 13.5			
2" - 3"	SDR 17			
2" - 3"	SDR 21			
Pipe * + [G]		PE 3408/PE 4710	DriscoPlex PW	AWWA C906
4" - 63"	DR 7.3			
4" - 63"	DR 9			
4" - 63"	DR 9.3			
4" - 63"	DR 11			
4" - 63"	DR 13.5			
4" - 63"	DR 15.5			
4" - 63"	DR 17			
4" - 63"	DR 21			
4" - 63"	DR 26			
4" - 63"	DR 32.5			

§ These products also meet the requirements for PE 3408 per ASTM D3350-02a.
 * Trade name may be followed by 1000, 1100, 1500, 1600, 4000, 4100, or 5100.
 + Material complies with NSF/ANSI 61 health effects requirements when tested at 73° F.
 [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility: Bloomfield, IA

Gas Applications - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Socket Fittings * ^ ¢ §	PE 2406/2708	Driscoplex® 6500	ASTM D2513/CSA B137.4
90 Degree Elbow			
1/2", 1" CTS SDR 7			
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4" IPS DR 7			
Coupling			
1/2", 3/4", 1" CTS SDR 7			
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3" 4" IPS DR 7			
1 1/4" CTS SDR 9			
End Cap			
1/2", 1" CTS SDR 7			
1/2", 3/4", 1", 1 1/2", 2", 3", 4" IPS SDR 7			
1 1/4" CTS SDR 9.3			
1 1/4" IPS SDR 7.3			
Purge Cap (w/ 1/2" CTS outlet)			
1 1/4", 2", 3", 4" IPS DR 7			
Reducer Coupling			
1/2" IPS x 1/2" CTS DR 7		3/4" CTS x 1/2" CTS DR 7	
3/4" IPS x 1/2" CTS DR 7		3/4" IPS x 1/2" IPS DR 7	
1" CTS x 1/2" CTS DR 7		1" CTS x 1/2" IPS DR 7	
1" IPS x 1/2" CTS DR 7		1" IPS x 1/2" IPS DR 7	

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



- 1" IPS x 3/4" CTS DR 7
- 1" CTS x 3/4" IPS DR 7
- 1 1/2" IPS x 1 1/4" IPS DR 7
- 1 1/4" IPS x 1/2" IPS DR 7
- 1 1/4" IPS x 1" IPS DR 7
- 1 1/4" IPS X 3/4" CTS DR 7.3
- 2" IPS x 1" IPS DR 7
- 2" IPS x 1 1/4" IPS DR 7
- 3" IPS x 2" IPS DR 7
- 4" IPS x 3" IPS DR 7
- 1" IPS x 3/4" IPS DR 7
- 1" IPS x 1" CTS DR 7
- 1 1/4" IPS x 1 1/4" CTS DR 7.3
- 1 1/4" IPS x 3/4" IPS DR 7
- 1 1/4" IPS x 1" CTS DR 7
- 2" IPS x 1" CTS DR 7
- 2" IPS x 1 1/4" CTS DR 7
- 2" IPS x 1 1/2" IPS DR 7
- 4" IPS x 2" IPS DR 7

Service (Branch)(Outlet x Base)

- 1/2" CTS DR 7 x 1 1/4" - 12" IPS
- 1/2" IPS DR 7 x 1 1/4" - 12" IPS
- 3/4" IPS DR 7 x 1 1/4" - 12" IPS
- 1" CTS DR 7 x 1 1/4" - 12" IPS
- 1" IPS DR 7 x 1 1/4" - 12" IPS
- 1 1/4" IPS DR 7 x 2" - 12" IPS

Tapping Tee (Outlet x Base)

- 1/2" CTS DR 7 x 1 1/4" - 18" IPS
- 1/2" IPS DR 7 x 1 1/4" - 18" IPS
- 3/4" CTS DR 7 x 1 1/4" - 18" IPS
- 3/4" IPS DR 7 x 1 1/4" - 18" IPS
- 1" CTS DR 7 x 1 1/4" - 18" IPS
- 1" IPS DR 7 x 1 1/4" - 18" IPS
- 1 1/4" CTS DR 7 x 2" - 18" IPS
- 1 1/4" IPS DR 7 x 2" - 18" IPS

Tee

- 1/2" CTS DR 7
- 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 4" IPS DR 7
- 1" CTS DR 7.3
- 3" IPS DR 7.3

Butt Fusion Fittings * ~ ¢ § PE 2406/2708 Driscoplex® 6500 ASTM D2513/CSA B137.4

45 Degree Elbow

- 2" IPS SDR 7 - 11
- 3", 4", 6", 8" IPS SDR 7 - 17
- 90 Degree Elbow

- 1/2" CTS x .090" WALL
- 3/4" IPS SDR 11
- 1", 1 1/4" IPS SDR 9 - 11
- 1 1/2" IPS SDR 11
- 2" IPS SDR 7 - 11
- 3", 4", 6", 8" IPS SDR 7 - 17

Branch Saddle (Outlet x Base)

- 1/2" CTS (.090" Wall) x 1 1/4" - 24" IPS
- 1/2" IPS DR 9.3 x 1 1/4" - 24" IPS
- 3/4" IPS DR 9, 11 x 1 1/4" - 24" IPS
- 1" IPS DR 9, 11 x 2" - 24" IPS
- 1 1/4" IPS DR 11 x 2" - 24" IPS
- 1 1/2" IPS DR 11 x 2" - 24" IPS
- 2" IPS DR 9, 11 x 3" - 24" IPS
- 3" IPS DR 7 - 11 x 3" - 24" IPS
- 4" IPS DR 7 - 11 x 3" - 24" IPS
- 6" IPS DR 11 x 8" - 24" IPS

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



End Cap

1/2" CTS (.090" Wall)	1/2" IPS DR 9.3
3/4" IPS SDR 11	1" CTS x (.102" Wall)
1" IPS SDR 11	1 1/4" IPS SDR 10
1 1/2" IPS SDR 11	2" IPS SDR 11
3" IPS SDR 11/11.5	4" IPS DR 11/11.5, 13.5
6" IPS DR 11/11.5, 13.5	8" IPS DR 11, 13.5

Purge Cap (Outlet x Main)

1/2" CTS x 2", 3", 4", 6", 8" IPS DR 11
 3/4" IPS x 2", 3", 4", 6", 8" IPS DR 11
 1" CTS x 2", 3", 4", 6", 8" IPS DR 11

Purge Point

1 1/4" DR 10 2" DR 11

Reducer Coupling

1/2" IPS DR 9.3 x 1/2" CTS (.090" Wall)
 3/4" IPS DR 11 x 1/2" CTS (.090" Wall)
 1" x 3/4" IPS DR 11
 1" CTS (.102" Wall) x 1/2" CTS (.090" Wall)
 1" IPS DR 11 x 1/2" CTS (.090" Wall)
 1" IPS DR 11 x 1/2" IPS DR 9.3
 1" IPS DR 11 x 3/4" CTS (.077" Wall, .090" Wall)
 1" IPS DR 11 x 1" CTS (.102" Wall)
 1 1/4" CTS (.121" Wall) x 1" IPS DR 11
 1 1/2" x 3/4" IPS DR 11
 1 1/2" x 1" IPS DR 11
 2" x 1" IPS DR 11
 2" IPS DR 11 x 1 1/4" IPS
 2" x 1 1/2" IPS DR 11
 3" x 2" IPS DR 11
 4" IPS DR 13.5 x 2" DR 11
 4" IPS DR 13.5 x 3" DR 11
 4" x 2" IPS DR 11
 4" x 3" IPS DR 11
 6" x 4" IPS DR 11, 13.5
 8" x 6" IPS DR 11, 13.5

Tapping Tee (Outlet x Base)

1/2" CTS (.090" Wall) x 1 1/4" - 24" IPS
 1/2" IPS DR 9.3 x 1 1/4" - 24" IPS
 3/4" IPS DR 11 x 1 1/4" - 24" IPS
 1" CTS (.090" Wall) x 1 1/4" - 24" IPS
 1" IPS DR 11 x 1 1/4" - 24" IPS
 1" CTS (0.090, 0.102" Wall) x 1 1/4" - 24" IPS
 1 1/4" IPS DR 11 x 2" - 24" IPS
 2" IPS DR 11 x 3" - 24" IPS

Tee

1/2" CTS (.090" Wall)	3/4" IPS DR 11
1" CTS (.102" Wall)	1" IPS DR 11
1 1/4" IPS DR 10	1 1/2" IPS DR 11
2" IPS DR 11	3" IPS DR 11/11.5
4" IPS DR 11 - 13.5	6" IPS DR 11 - 13.5

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



8" IPS DR 11 - 13.5
Socket Fittings * ^ ¢ § PE 4710 Driscoplex® 8100 ASTM D2513/CSA B137.4

90 Degree Elbow

1/2", 1" CTS SDR 7
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4" IPS DR 7

Coupling

1/2", 3/4", 1" CTS SDR 7
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4" IPS DR 7

End Cap

1/2", 1" CTS SDR 7
1/2", 3/4", 1", 1 1/2", 2", 3", 4" IPS SDR 7
1 1/4" IPS SDR 7.3

Purge Cap (w/ 1/2" CTS outlet)

1 1/4", 2", 3", 4" IPS DR 7

Reducer Coupling

1/2" IPS x 1/2" CTS DR 7 3/4" CTS x 1/2" CTS DR 7
3/4" IPS x 1/2" CTS DR 7 3/4" IPS x 1/2" IPS DR 7
1" CTS x 1/2" CTS DR 7 1" CTS x 1/2" IPS DR 7
1" IPS x 1/2" CTS DR 7 1" IPS x 1/2" IPS DR 7
1" IPS x 3/4" CTS DR 7 1" IPS x 3/4" IPS DR 7
1" CTS x 3/4" IPS DR 7 1" IPS x 1" CTS DR 7
1 1/2" IPS x 1 1/4" IPS DR 7 1 1/4" IPS x 1 1/4" CTS DR 7.3
1 1/4" IPS x 1/2" IPS DR 7 1 1/4" IPS x 3/4" IPS DR 7
1 1/4" IPS x 3/4" CTS DR 7.3 1 1/4" IPS x 1" IPS DR 7
1 1/4" IPS x 1" CTS DR 7 2" IPS x 1" CTS DR 7
2" IPS x 1" IPS DR 7 2" IPS x 1 1/4" CTS DR 7.3
2" IPS x 1 1/4" IPS DR 7 2" IPS x 1 1/2" IPS DR 7
3" IPS x 2" IPS DR 7 4" IPS x 2" IPS DR 7
4" IPS x 3" IPS DR 7

Service(Branch) Saddle (Outlet x Base)

1/2" CTS DR 7 x 1 1/4" - 24" IPS
1/2" IPS DR 7 x 1 1/4" - 24" IPS
3/4" IPS DR 7 x 1 1/4" - 24" IPS
1" CTS DR 7 x 1 1/4" - 24" IPS
1" IPS DR 7 x 1 1/4" - 24" IPS
1 1/4" IPS DR 7 x 2" - 24" IPS

Tapping Tee (Outlet x Base)

1/2" CTS DR 7 x 1 1/4" - 24" IPS
1/2" IPS DR 7 x 1 1/4" - 24" IPS
3/4" CTS DR 7 x 1 1/4" - 24" IPS
3/4" IPS DR 7 x 1 1/4" - 24" IPS
1" CTS DR 7 x 1 1/4" - 24" IPS
1" IPS DR 7 x 1 1/4" - 24" IPS
1 1/4" CTS DR 7 x 2" - 24" IPS
1 1/4" IPS DR 7 x 2" - 24" IPS

Tee

1/2" CTS DR 7
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 4" IPS DR 7
1" CTS DR 7.3

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



3" IPS DR 7.3
 Butt Fusion Fittings * ~ ¢ § PE 4710 Driscoplex® 8100 ASTM D2513/CSA B137.4

45 Degree Elbow
 2", 3" IPS SDR 7 - 11 4", 6", 8" IPS SDR 7 - 17
 90 Degree Elbow
 1/2" CTS x .090" WALL 3/4" IPS SDR 11
 1", 1 1/4" IPS SDR 9, 11 1 1/2" IPS SDR 11
 2", 3" IPS SDR 7 - 11 4", 6", 8" IPS SDR 7 - 17
 Branch Saddle (Outlet x Base)
 1/2" CTS (.090" Wall) x 1 1/4" - 24" IPS
 1/2" IPS DR 9.3 x 1 1/4" - 24" IPS
 3/4" IPS DR 9 - 11 x 1 1/4" - 24" IPS
 1" IPS DR 9 - 11 x 2" - 24" IPS
 1 1/4" IPS DR 11 x 2" - 24" IPS
 1 1/2" IPS DR 11 x 2" - 24" IPS
 2" IPS DR 9 - 11 x 3" - 24" IPS
 3" IPS DR 7 - 11 x 3" - 24" IPS
 4" IPS DR 7 - 11 x 3" - 24" IPS
 6" IPS DR 11 x 8" - 24" IPS
 End Cap
 1/2" CTS (.090" WALL) 1/2" IPS DR 9.3
 3/4" CTS (.090" WALL) 3/4" IPS SDR 11
 1" CTS (.102", .125" WALL) 1" IPS SDR 9, 11
 1 1/4" IPS SDR 9, 11 1 1/2" IPS SDR 11
 2" IPS SDR 7 - 11 3" IPS SDR 7 - 17
 4", 6", 8" IPS SDR 7 - 17
 Purge Cap/Purge Point
 1/2" CTS x 2" - 8" IPS DR 11 3/4" IPS x 2" - 8" IPS DR 11
 1" CTS x 2" - 8" IPS DR 11 1 1/4" DR 10
 2" DR 11
 Reducer Coupling
 3/4" IPS DR 11 x 1/2" CTS (.090" Wall)
 3/4" IPS DR 11 x 3/4" CTS (.090" Wall)
 1" x 1/2" IPS DR 11
 1" x 3/4" IPS DR 11
 1" CTS (.102" Wall) x 1/2" CTS (.090" Wall)
 1" IPS DR 9 x 1" CTS (.125" Wall)
 1" IPS DR 11 x 1/2" CTS (.090" Wall)
 1" IPS DR 11 x 1" CTS (.102" Wall)
 1 1/4" x 1" IPS DR 11
 1 1/4" CTS (.121" Wall) X 1" IPS DR 11
 1 1/4" IPS DR 11 x 1" CTS (.102" Wall)
 1 1/4" IPS DR 11 x 1 1/4" CTS (.090" Wall)
 1 1/2" x 3/4" IPS DR 11
 1 1/2" x 1" IPS DR 11
 2" x 1" IPS DR 11
 2" x 1 1/2" IPS DR 9 - 11
 2" IPS DR 11 x 1 1/4" IPS DR 9 - 11
 3" x 2" IPS DR 7 - 11

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



4" IPS DR 11 - 13.5 x 2" DR 7 - 17
 6" x 4" IPS DR 7 - 17
 8" x 6" IPS DR 7 - 17
 Tapping Tee for Gas Applications (Outlet x Base)
 1/2" CTS (.090" Wall) x 1 1/4" - 24"
 1/2" IPS DR 9.3 x 1 1/4" - 24"
 3/4" IPS DR 11 x 1 1/4" - 24"
 1" CTS (.090" Wall) X 1 1/4" - 24"
 1" CTS (0.090, 0.102" Wall) x 1 1/4" - 24" IPS
 1" IPS DR 11 x 1 1/4" - 24"
 1 1/4" IPS DR 11 x 2" - 24"
 2" IPS DR 11 x 3" - 24" IPS
 Tee
 3/4" IPS DR 11
 1 1/4" IPS DR 11
 2", 3" IPS SDR 7 - 11
 1" IPS DR 9 - 11
 1 1/2" IPS DR 11
 4", 6", 8" IPS SDR 7 - 17

- * Gas pipe and tubing limited to outside underground use only.
- ^ Meets the requirements of ASTM D2683.
- ~ Meets the requirements of ASTM D3261.
- ¢ Product is authorized to bear the cNSF and/or the cNSFus Mark.
- § Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

Potable Water - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Socket Fittings ⁺ § [G]	PE 4710	Driscoplex® 8100	ASTM D2683
90 Degree Elbow			
1/2", 1" CTS SDR 7			
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4" IPS DR 7			
Coupling			
1/2", 3/4", 1" CTS SDR 7			
1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 3", 4" IPS DR 7			
End Cap			
1/2", 1" CTS SDR 7			
1/2", 3/4", 1", 1 1/2", 2", 3", 4" IPS SDR 7			
Purge Cap (w/ 1/2" CTS outlet)			
1 1/4", 2", 3", 4" IPS DR 7			
Reducer Coupling			
1/2" IPS x 1/2" CTS DR 7	3/4" CTS x 1/2" CTS DR 7		
3/4" IPS x 1/2" CTS DR 7	3/4" IPS x 1/2" IPS DR 7		
1" CTS x 1/2" CTS DR 7	1" CTS x 1/2" IPS DR 7		
1" IPS x 1/2" CTS DR 7	1" IPS x 1/2" IPS DR 7		
1" IPS x 3/4" CTS DR 7	1" IPS x 3/4" IPS DR 7		
1" CTS x 3/4" IPS DR 7	1" IPS x 1" CTS DR 7		
1 1/2" IPS x 1 1/4" IPS DR 7	1 1/4" IPS x 1 1/4" CTS DR 7.3		
1 1/4" IPS x 1/2" IPS DR 7	1 1/4" IPS x 3/4" IPS DR 7		
1 1/4" IPS x 1" IPS DR 7	1 1/4" IPS x 1" CTS DR 7		
1 1/4" IPS x 3/4" CTS DR 7.3	2" x 1 1/4" IPS DR 7		

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



2" IPS x 1" CTS DR 7	2" IPS x 1" IPS DR 7
2" IPS x 1 1/4" CTS DR 7.3	2" IPS x 1 1/2" IPS DR 7
3" IPS x 2" IPS DR 7	4" IPS x 2" IPS DR 7
4" IPS x 3" IPS DR 7	

Service (Branch) Saddle (Outlet x Base)

1/2" CTS DR 7 x 1 1/4" - 24" IPS
 1/2" IPS DR 7 x 1 1/4" - 24" IPS
 3/4" IPS DR 7 x 1 1/4" - 24" IPS
 1" CTS DR 7 x 1 1/4" - 24" IPS
 1" IPS DR 7 x 1 1/4" - 24" IPS
 1 1/4" IPS DR 7 x 2" - 24" IPS

Tapping Tee (Outlet x Base)

1/2" CTS DR 7 x 1 1/4" - 24" IPS
 1/2" IPS DR 7 x 1 1/4" - 24" IPS
 3/4" CTS DR 7 x 1 1/4" - 24" IPS
 3/4" IPS DR 7 x 1 1/4" - 24" IPS
 1" CTS DR 7 x 1 1/4" - 24" IPS
 1" IPS DR 7 x 1 1/4" - 24" IPS
 1 1/4" CTS DR 7 x 2" - 24" IPS
 1 1/4" IPS DR 7 x 2" - 24" IPS

Tee

1/2" CTS DR 7
 1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 4" IPS DR 7
 1" CTS DR 7.3
 3" IPS DR 7.3

Butt Fusion Fittings + § [G]

PE 4710

Driscoplex® 8100

ASTM D3261

45 Degree Elbow

2", 3" IPS SDR 7 - 11
 90 Degree Elbow

4", 6", 8" IPS SDR 7 - 17

2", 3" IPS SDR 7 - 11

4", 6", 8" IPS SDR 7 - 17

Branch Saddle (Outlet x Base)

2" IPS DR 9 x 3" - 24" IPS
 3" IPS DR 7 - 9 x 3" - 24" IPS
 4" IPS DR 7 - 11 x 3" - 24" IPS
 6" IPS DR 11 x 8" - 24" IPS

End Cap

2", 3" IPS SDR 7 - 11

4", 6", 8" IPS SDR 7 - 17

Flange Adapter

1 1/2" IPS DR 9
 2", 3" IPS DR 7 - 9
 4", 6", 8", 10", 12", 14" IPS DR 7 - 17
 16" IPS DR 9 - 17
 18" DR IPS 11 - 17

Reducer Coupling

2" x 1 1/2" IPS DR 9
 4" x 2" IPS DR 7 - 17
 6" x 4" IPS DR 7 - 17

3" x 2" IPS DR 7 - 9
 4" x 3" IPS DR 7 - 17
 8" x 6" IPS DR 7 - 17

Tee

1" IPS DR 9

2", 3" IPS DR 7 - 9

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



4", 6", 8" IPS DR 7 - 17 Butt Fusion Fittings ⁺ ^ § [G]	PE4710	Driscoplex® 1500	ASTM D3261
45 Degree Elbow			
2", 3" IPS SDR 7 - 11 90 Degree Elbow		4", 6", 8" IPS SDR 7 - 11	
2", 3" IPS SDR 7 - 11 Branch Saddle (Outlet x Base)		4", 6", 8" IPS SDR 7 - 11	
2" IPS DR 9 x 3" - 24" IPS			
3" IPS DR 7 - 9 x 3" - 24" IPS			
4" IPS DR 7 - 11 x 3" - 24" IPS			
6" IPS DR 11 x 8" - 24" IPS			
End Cap			
2", 3" IPS SDR 7 - 11 Flange Adapter		4", 6", 8" IPS SDR 7 - 11	
1 1/2" IPS DR 9			
2", 3" IPS DR 7 - 9			
4", 6", 8", 10", 12", 14" IPS DR 7 - 11			
16" IPS DR 9 - 11			
18" DR IPS 11 - 11			
Reducer Coupling			
2" x 1 1/2" IPS DR 9		3" x 2" IPS DR 7 - 9	
4" x 2" IPS DR 7 - 11		4" x 3" IPS DR 7 - 11	
6" x 4" IPS DR 7 - 11		8" x 6" IPS DR 7 - 11	
Tee			
1" IPS DR 9		2", 3" IPS DR 7 - 9	
4", 6", 8" IPS DR 7 - 11			

+ Material complies with NSF/ANSI 61 health effects requirements when tested at 73° F.

^ Applies to DR 9 and 11 only.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

NOTE: NSF Certified materials and generic ingredients are exempt from bearing an NSF Certification Mark. Certified materials and generic ingredients are identified by the manufacturer name, facility and trade designation as shown in the Official Listing.

Facility: Pryor, OK

Gas Applications - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe # § * §	PE 2406/2708	DriscoPlex® 6500	ASTM D2513
1/2" - 12"			
Pipe § * ¢	PE 2406/2708	DriscoPlex® 6500	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SIDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



1/2" - 12"	SDR 21			
Pipe # % * §		PE 4710	Driscopipe® 8100	ASTM D2513
1/2" - 12"				
Pipe % * ‡		PE 4710	Driscopipe® 8100	CSA B137.4
1/2" - 10"	SDR 8.8			
1/2" - 10"	SDR 10			
1/2" - 12"	SDR 11			
1/2" - 12"	SDR 13.5			
1/2" - 12"	SDR 17			
1/2" - 12"	SDR 21			
Pipe # % * §		PE 4710	YELLOWSTRIPE® 8300	ASTM D2513
1/2" - 12"				
Pipe % * ‡		PE 4710	YELLOWSTRIPE® 8300	CSA B137.4
1/2" - 10"	SDR 8.8			
1/2" - 10"	SDR 10			
1/2" - 12"	SDR 11			
1/2" - 12"	SDR 13.5			
1/2" - 12"	SDR 17			
1/2" - 12"	SDR 21			

All sizes between 1/2" and 12" with a DR of 11 or thinner are Certified.
 % Only those products identified in Listing are Certified.
 * Gas pipe and tubing limited to outside underground use only.
 ‡ Product is authorized to bear the cNSF and/or the cNSFus Mark.
 § Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

Potable Water - Pipe and Fittings

Product Type		Material Type	Trade Name	Product Standard
Pipe * + [G]		PE 4710	DriscoPlex PW	ASTM D2239
1/2" - 2"	SIDR 5.3			
1/2" - 2"	SIDR 7			
1/2" - 2"	SIDR 19			
1/2" - 2"	SIDR 9			
1/2" - 3"	SIDR 15			
1/2" - 3"	SIDR 11.5			
Pipe * + [G]		PE 4710	DriscoPlex PW	ASTM D3035
1/2" - 24"	DR 7			
1/2" - 24"	DR 9			
1/2" - 24"	DR 9.3			
1/2" - 24"	DR 11			
1/2" - 24"	DR 32.5			
1/2" - 24"	DR 15.5			
1/2" - 24"	DR 17			
1/2" - 24"	DR 21			
1/2" - 24"	DR 26			
1/2" - 24"	DR 13.5			

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



<i>Pipe</i> [*] + [G]	<i>PE 4710</i>	<i>DriscoPlex PW</i>	<i>ASTM F714</i>
3" - 18"	SDR 7.3		
3" - 20"	SDR 8.3		
3" - 20", 22" - 30"	SDR 9.3		
3" - 20", 22" - 36"	SDR 11		
3" - 20", 22", 24"	SDR 9		
3" - 36"	SDR 13.5		
3" - 48"	SDR 15.5		
3" - 54"	SDR 17		
3" - 54"	SDR 21		
3" - 54"	SDR 26		
3" - 54"	SDR 32.5		
3" - 54"	SDR 41		

<i>Pipe</i> [*] + [G]	<i>PE 4710</i>	<i>DriscoPlex PW</i>	<i>ASTM D2737</i>
1/2" - 2"	SDR 7.3		
1/2" - 2"	SDR 11		
1/2" - 2"	SDR 9		

<i>Pipe</i> [*] + [G]	<i>PE 4710</i>	<i>DriscoPlex PW</i>	<i>AWWA C901</i>
1/2" - 3"	SDR 9		
1/2" - 3"	SDR 7.3		
1/2" - 3"	SIDR 9		
1/2" - 3"	SDR 11		
1/2" - 3"	SIDR 5.3		
1/2" - 3"	SIDR 7		
2" - 3"	SDR 21		
2" - 3"	SIDR 15		
2" - 3"	SIDR 19		
2" - 3"	SDR 17		
3/4" - 3"	SDR 13.5		
3/4" - 3"	SIDR 11.5		

<i>Pipe</i> [§] * + [G]	<i>PE 3408/PE 4710</i>	<i>DriscoPlex PW</i>	<i>AWWA C906</i>
4" - 63"	DR 7.3		
4" - 63"	DR 9		
4" - 63"	DR 9.3		
4" - 63"	DR 11		
4" - 63"	DR 32.5		
4" - 63"	DR 15.5		
4" - 63"	DR 17		
4" - 63"	DR 21		
4" - 63"	DR 26		
4" - 63"	DR 13.5		

§ These products also meet the requirements for PE 3408 per ASTM D3350-02a.

* Trade name may be followed by 1000, 1100, 1500, 1600, 4000, 4100 or 5100.

+ Material complies with NSF/ANSI 61 health effects requirements when tested at 73° F.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



Drinking Water Act.

Facility: Hagerstown, MD

Gas Applications - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe # % * §	PE 4710	YELLOWSTRIPE® 8300	ASTM D2513
1/2" - 12"			
Pipe % * †	PE 4710	YELLOWSTRIPE® 8300	CSA B137.4
1/2" - 10" SDR 8.8			
1/2" - 10" SDR 10			
1/2" - 12" SDR 11			
1/2" - 12" SDR 13.5			
1/2" - 12" SDR 17			
1/2" - 12" SDR 21			

All sizes between 1/2" and 12" with a DR of 11 or thinner are Certified.

% Only those products identified in Listing are Certified.

* Gas pipe and tubing limited to outside underground use only.

† Product is authorized to bear the cNSF and/or the cNSFus Mark.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

Potable Water - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe * + [G]	PE 4710	DriscoPlex PW	ASTM D2239
1/2" - 2" SIDR 5.3			
1/2" - 2" SIDR 7			
1/2" - 2" SIDR 9			
1/2" - 3" SIDR 11.5			
1/2" - 3" SIDR 15			
1/2" - 2" SIDR 19			
Pipe * + [G]	PE 4710	DriscoPlex PW	ASTM D3035
1/2" - 24" DR 7			
1/2" - 24" DR 9			
1/2" - 24" DR 9.3			
1/2" - 24" DR 11			
1/2" - 24" DR 13.5			
1/2" - 24" DR 15.5			
1/2" - 24" DR 17			
1/2" - 24" DR 21			
1/2" - 24" DR 26			
1/2" - 24" DR 32.5			
Pipe * + [G]	PE 4710	DriscoPlex PW	ASTM F714
3" - 18" SDR 7.3			
3" - 20" SDR 8.3			

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



3" - 20", 22", 24" SDR 9
 3" - 20", 22" - 30" SDR 9.3
 3" - 20", 22" - 36" SDR 11
 3" - 36" SDR 13.5
 3" - 48" SDR 15.5
 3" - 54" SDR 17
 3" - 54" SDR 21
 3" - 54" SDR 26
 3" - 54" SDR 32.5
 3" - 54" SDR 41

Pipe^{* + [G]} PE 4710 DriscoPlex PW ASTM D2737

1/2" - 2" SDR 7.3
 1/2" - 2" SDR 9
 1/2" - 2" SDR 11

Pipe^{* + [G]} PE 4710 DriscoPlex PW AWWA C901

1/2" - 3" SIDR 5.3
 1/2" - 3" SIDR 7
 1/2" - 3" SIDR 9
 3/4" - 3" SIDR 11.5
 2" - 3" SIDR 15
 2" - 3" SIDR 19
 1/2" - 3" SDR 7.3
 1/2" - 3" SDR 9
 1/2" - 3" SDR 11
 3/4" - 3" SDR 13.5

2" - 3" SDR 17
 2" - 3" SDR 21

Pipe^{§ * + [G]} PE 3408/PE 4710 DriscoPlex PW AWWA C906

4" - 63" DR 7.3
 4" - 63" DR 9
 4" - 63" DR 9.3
 4" - 63" DR 11
 4" - 63" DR 13.5
 4" - 63" DR 15.5
 4" - 63" DR 17
 4" - 63" DR 21
 4" - 63" DR 26
 4" - 63" DR 32.5

§ These products also meet the requirements for PE 3408 per ASTM D3350-02a.

* Trade name may be followed by 1000, 1100, 1500, 1600, 4000, 4100 or 5100.

+ Material complies with NSF/ANSI 61 health effects requirements when tested at 73° F.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.