



Chevron Phillips Chemical Company Issued Sales Specification

Name of Product

RACING FUEL 100 ULE

Revision Date

8/23/2010

Chevron Phillips Chemical Company LP
10001 Six Pines Drive
The Woodlands, TX 77380
800-858-4327
Technical Service: 832-813-4862

Chevron Phillips Chemicals International N.V.
Brusselsesteenweg 355
B-3090 Overijse, Belgium
+32 (0) 2 689 12 11

Chevron Phillips Chemicals Asia PTE Ltd.
5 Temasek Boulevard
05-01 Suntec Tower Five
Singapore 038985
+65 6337 9700

Test	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
Anti-Knock Index	---	Calculated	---	100	---	---	---
API Gravity	---	ASTM D-4052	---	---	---	---	REPORT
Aromatics	LV%	ASTM D5769	---	---	35	---	---
Aromatics (Corrected)	LV%	ASTM D-1319	---	---	---	---	REPORT
Aromatics, LV%	LV%	ASTM D-5580	---	---	35	---	---
Benzene	LV%	ASTM D3606 MO	---	---	0.1	---	---
CARB Status	---	NONE	---	---	---	---	REPORT
Corrosion (3 hrs @ 50C)	---	ASTM D-130	---	---	---	---	1B Max
Dielectric Constant	---	Kavlico FT-K01	---	---	---	---	REPORT
Distillation - 10%	FAH	ASTM D-86	---	---	158	---	---
Distillation - 30%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 50%	FAH	ASTM D-86	---	170	235	---	---
Distillation - 70%	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - 90%	FAH	ASTM D-86	---	---	365	---	---
Distillation - EP	FAH	ASTM D-86	---	---	437	---	---
Distillation - IBP	FAH	ASTM D-86	---	---	---	---	REPORT
Distillation - Loss	ML	ASTM D-86	---	---	---	---	REPORT
Distillation - Residue	ML	ASTM D-86	---	---	---	---	REPORT
E200, LV%	LV%	ASTM D-86	---	---	---	---	REPORT
E300, LV%	LV%	ASTM D-86	---	---	---	---	REPORT
Ethanol	LV%	ASTM D-4815	---	5.5	10.0	---	---
Ethanol	LV%	ASTM D-5599	---	5.5	10.0	---	---
Existent Gums, Washed	mg/Hml	ASTM D-381	---	---	5	---	---
Lead	g/gal	ICP/OES	---	---	0.005	---	---
Motor Octane Number	---	ASTM D-2700	---	---	---	---	REPORT
Olefins (Corrected)	LV%	ASTM D-1319	---	---	1	---	---
Olefins, LV%	LV%	ASTM D-6550	---	---	1	---	---

Test	Units	Method	Typical	Minimum	Maximum	Qualitative	Note
Oxidation Stability	min	ASTM D-525	---	1200	---	---	---
Oxygen	WT%	Calculated	---	---	3.7	---	---
Phosphorus	g/gal	ICP/OES	---	---	---	---	REPORT
Research Octane Number	---	ASTM D-2699	---	---	---	---	REPORT
Saturates (Corrected)	LV%	ASTM D-1319	---	---	---	---	REPORT
Specific Gravity 60/60F	---	ASTM D-4052	---	---	---	---	REPORT
Sulfur	ppm	ASTM D-2622	---	---	10	---	---
Vapor Pressure, CARB RVPE calc	PSI	ASTM D-5191	---	6.4	7.0	---	---
Vapor Pressure, EPA DVPE calc.	PSI	ASTM D-5191	---	6.4	7.0	---	---
VOC Status	---	NONE	---	---	---	---	REPORT

Printed Versions of this document are uncontrolled

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.