

Chevron Phillips Chemical Company LP
10001 Six Pines Drive
The Woodlands, TX 77380
800-858-4327
Technical Service: 832-813-4862

Chevron Phillips Chemicals International N.V.
Brusselsesteenweg 355
B-3090 Overijse, Belgium
+32 (0) 2 689 12 11

Chevron Phillips Chemicals Asia PTE Ltd.
5 Temasek Boulevard
05-01 Suntec Tower Five
Singapore 038985
+65 6337 9700

TT105™ UL Racing Fuel

Property	Typical Value	Specification	Test Method
Specific Gravity at 60/60 °F	0.7250	0.7150 – 0.7315	ASTM D 4052
API Gravity		Report	ASTM D 1250
Copper Corrosion, 3 h at 50 °C	1	1 max	ASTM D 130
Existent Gum (washed), mg/100 mL	2	5 max	ASTM D 381
Sulfur, ppm	< 15	15 max	ASTM D 5453
Reid Vapor Pressure, psia	7.0	6.5 – 7.5	ASTM D 5191
Lead, g/gal	< 0.0050	0.0050 max	ICP/OES
Phosphorus, g/gal	0.001	Report	ICP/OES
Oxygen, wt %	< 2.70	2.70 max	Calculated
Distillation Range at 760 mmHg, °F			ASTM D 86
Initial Boiling Point	102	90 – 115	
10%	175	160 – 185	
50%	208	195 – 215	
90%	246	230 – 260	
End Point	300	340 max	
Residue, mL	< 2.0	2.0 max	
Oxidation Stability, min	> 1440	1440 min	ASTM D 525
Dielectric Constant		Report	Kavilco FT-K01
Composition, vol %			ASTM D 1319
Aromatics		Report	
Olefins		Report	
Saturates		Report	
Research Octane Number	110.0	108.0 min	ASTM D 2699
Motor Octane Number	100.0	99.0 min	ASTM D 2700
Anti-Knock Index, (R+M)/2	105.0	104.0 min	Calculated
ETBE, vol %	< 17.5	17.5 max	Chromatography

Other Properties

Color	Gold	Visual
-------	------	--------

Chevron Phillips' Racing Fuels are 100% petroleum derived hydrocarbons and are designed to meet the fuel regulations of most sanctioning bodies. They contain detergent additives, corrosion inhibitors, and antioxidant additives that are added in concentrations similar to those found in commercial fuels.

Please note: This fuel is for off-road use only.

Product Number: 1021631

Revised: 10/26/06

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.