

Chevron Phillips Chemical Company LP
10001 Six Pines Drive
The Woodlands, TX 77380
800-858-4327
Technical Service: 832-813-4862

Chevron Phillips Chemicals International N.V.
Brusselsesteenweg 355
B-3090 Overijse, Belgium
+32 (0) 2 689 12 11

Chevron Phillips Chemicals Asia PTE Ltd.
5 Temasek Boulevard
05-01 Suntec Tower Five
Singapore 038985
+65 6337 9700

UTG-93

Property	Typical Value	Specification	Test Method
Copper Corrosion, 3 h at 50 °C	1	1 max	ASTM D 130
Specific Gravity at 60/60 °F	0.743	0.734 – 0.744	ASTM D 1250
API Gravity at 60 °F	59	58.7 – 61.3	ASTM D 4052
Oxidation Stability	1440+	1440 min	ASTM D 525
Existent Gum, mg/100 mL	1	5 max	ASTM D 381
Lead Content, g/gal	0.001	0.005 max	ASTM D 3237 Modified
Sulfur Content, wt %	0.002	0.1 max	ASTM D 3120
Phosphorus, g/gal	0.001	0.005 max	ASTM D 3231
Total Alcohol Content, vol %	0.00	0.00 max	EPA Procedure 10
Reid Vapor Pressure at 100 °F, psia	9.1	8.8 – 9.2	ASTM D 323
Research Octane Number	93.5	90.3 min	ASTM D 2699
Motor Octane Number	85.1		ASTM D 2700
Sensitivity	8.4	7.5 min	ASTM D 2700
Distillation Range at 760 mmHg, °F			ASTM D 86
Initial Boiling Point	91	75 – 95	
10%	122	120 – 135	
50%	220	200 – 230	
90%	314	300 – 325	
End Point	393	415 max	
Composition, vol %			ASTM D 1319
Olefins	6	10 max	
Aromatics	27	35 max	
Saturates	67		
Heat of Combustion, Net, Btu/lb	18300		ASTM D 240
Carbon Content, wt %	86.5		
Hydrogen Content, wt %	13.5		
Anti-Knock Index, (R+M)/2	86.8	87.0 max	Calculated

This product meets the requirements outlined in Code of Federal Regulation CFR-40, Part 86.113 for use in CAFE and Emission Certification Testing.

Product Number: 1021666

Revised: 07/01/04

Notice: Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.