

**Tertiary Butyl Mercaptan**

Version 1.6

Revision Date 2017-07-06

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Tertiary Butyl Mercaptan
Material : 1069500, 1086416, 1086415, 1070007, 1064730, 1021473,
1021470, 1017940, 1036143, 1024807, 1021472, 1021471,
1024806, 1021469, 1028495, 1021474, 1027458, 1029711,
1017329, 1021468

Use : Chemical intermediate, Odorant

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Local : See Company Address

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture****GHS Classification and labelling according to JIS Z7252-2014 and JIS Z7253-2012 (GHS 2011)****Classification**

: Flammable liquids, Category 2
Skin sensitization, Category 1
Acute aquatic toxicity, Category 2
Chronic aquatic toxicity, Category 2

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Labeling

Symbol(s)

:



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.
 H317: May cause an allergic skin reaction.
 H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**

P210: Keep away from heat/sparks/open flames/hot surfaces.
 No smoking.
 P233: Keep container tightly closed.
 P240: Ground/bond container and receiving equipment.
 P241: Use explosion-proof electrical/ ventilating/ lighting/
 equipment.
 P242: Use only non-sparking tools.
 P243: Take precautionary measures against static discharge.
 P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264: Wash skin thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.
 P272: Contaminated work clothing must not be allowed out of
 the workplace.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/ protective clothing/ eye
 protection/ face protection.

Response:

P303 + P361 + P353: IF ON SKIN (or hair): Remove/ Take
 off immediately all contaminated clothing. Rinse skin with
 water/ shower.
 P304 + P340: IF INHALED: Remove victim to fresh air and
 keep at rest in a position comfortable for breathing.
 P305 + P351 + P338: IF IN EYES: Rinse cautiously with
 water for several minutes. Remove contact lenses, if present
 and easy to do. Continue rinsing.
 P312: Call a POISON CENTER/doctor if you feel unwell.
 P321: Specific treatment (see supplemental first aid
 instructions on this label).
 P333 + P313: If skin irritation or rash occurs: Get medical
 advice/ attention.
 P337 + P313: If eye irritation persists: Get medical advice/
 attention.
 P363: Wash contaminated clothing before reuse.
 P370 + P378: In case of fire: Use dry sand, dry chemical or
 alcohol-resistant foam for extinction.
 P391: Collect spillage.

Storage:

P403 + P233: Store in a well-ventilated place. Keep container
 tightly closed.
 P403 + P235: Store in a well-ventilated place. Keep cool.
 P405: Store locked up.

Disposal:

P501: Dispose of contents/ container to an approved waste
 disposal plant.

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

SECTION 3: Composition/information on ingredients

Synonyms : t-Butyl Mercaptan
tert-Butanethiol
2-Methyl Propane-2-Thiol
TBM
TC4SH
tert-Butyl Mercaptan

Molecular formula : C₄H₁₀S

Chemical name	CAS-No.	Concentration	ENCS/ISHL number
t-Butyl Mercaptan	75-66-1	100%	2-464

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : -26 °C (-15 °F)
estimated

Autoignition temperature : No data available

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire : Do not allow run-off from fire fighting to enter drains or water

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

- | | |
|--|--|
| fighting | courses. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary. |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. |
| Fire and explosion protection | : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. |
| Hazardous decomposition products | : Carbon oxides. Sulfur oxides. |

SECTION 6: Accidental release measures

- | | |
|---------------------------|---|
| Personal precautions | : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods for cleaning up | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

SECTION 7: Handling and storage**Handling**

- | | |
|---|--|
| Advice on safe handling | : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. |
| Advice on protection against fire and explosion | : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity |

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
t-Butyl Mercaptan	Manufacturer	TWA	0.5 ppm,	

JP

Ingredients	Basis	Value	Control parameters	Note
-------------	-------	-------	--------------------	------

Personal protective equipment

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Form : Liquid

Physical state : Liquid

Color : clear

Odor : Repulsive

Safety data

Flash point : -26 °C (-15 °F) estimated

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : no

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Autoignition temperature	: No data available
Molecular formula	: C ₄ H ₁₀ S
Molecular weight	: 90.2 g/mol
pH	: Not applicable
Pour point	: No data available
Boiling point/boiling range	: 63 - 65 °C (145 - 149 °F)
Vapor pressure	: 5.90 PSI at 38 °C (100 °F)
Relative density	: 0.81 at 16 °C (61 °F)
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Relative vapor density	: 3 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity**Possibility of hazardous reactions**

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Oxidizing solids. Oxidizing liquids.
Hazardous decomposition products	: Carbon oxides Sulfur oxides
Other data	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

t-Butyl Mercaptan	: LD ₅₀ : 4,729 mg/kg Species: Rat
-------------------	--

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Sex: male

Acute inhalation toxicity

t-Butyl Mercaptan : LC50: 26643 ppm
Exposure time: 4 h
Species: Rat
Sex: male and female
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50: 22200 ppm
Exposure time: 4 h
Species: Rat
Sex: male
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50: 16500 ppm
Exposure time: 4 h
Species: Mouse
Sex: male
Test atmosphere: vapor
Method: OECD Test Guideline 403

**Tertiary Butyl Mercaptan
Skin irritation**

: No skin irritation.

**Tertiary Butyl Mercaptan
Eye irritation**

: Vapors may cause irritation to the eyes, respiratory system and the skin.

**Tertiary Butyl Mercaptan
Sensitization**

: Causes sensitization.

Repeated dose toxicity

t-Butyl Mercaptan : Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 9, 97, 196 ppm
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: > 196 ppm

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Species: Rat, Male and female
Sex: Male and female
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/day
Exposure time: 42-53 days
Number of exposures: Daily
NOEL: 50 mg/kg bw/day
Lowest observable effect level: 200 mg/kg bw/day
Method: OECD Guideline 422

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 25.1, 99.6, 403.4 ppm
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: 99.6 ppm
Lowest observable effect level: 403.4 ppm
Method: OECD Guideline 413
Target Organs: Liver, Kidney, Blood, Upper respiratory tract
Information given is based on data obtained from similar substances.

Reproductive toxicity

t-Butyl Mercaptan

: Species: Rat
Sex: male and female
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/day
Number of exposures: Daily
Test period: 42 -53 days
Method: OECD Guideline 422
NOAEL Parent: 200 mg/kg bw/day
NOAEL F1: 50 mg/kg bw/day
No adverse effects expected

Developmental Toxicity

t-Butyl Mercaptan

: Species: Mouse
Application Route: Inhalation
Dose: 11, 99, 195 ppm
Exposure time: GD 6-16
Number of exposures: 6 hrs/d
NOAEL Teratogenicity: > = 195 ppm
NOAEL Maternal: > = 195 ppm

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Species: Rat
 Application Route: Inhalation
 Dose: 11, 99, 195 ppm
 Exposure time: GD6-19
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: > =195 ppm
 NOAEL Maternal: > = 195 ppm

Species: Rat
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Exposure time: 42-53 days
 Number of exposures: Daily
 NOAEL Teratogenicity: 50 mg/kg bw /day
 NOAEL Maternal: 200 mg/kg bw /day

**Tertiary Butyl Mercaptan
Aspiration toxicity**

: May be harmful if swallowed and enters airways.

CMR effects

t-Butyl Mercaptan

: Carcinogenicity: Not available
 Mutagenicity: Did not show mutagenic effects in animal experiments.
 Teratogenicity: Did not show teratogenic effects in animal experiments.
 Reproductive toxicity: No toxicity to reproduction

**Tertiary Butyl Mercaptan
Further information**

: Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

t-Butyl Mercaptan

: LC50: 34 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 semi-static test Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

t-Butyl Mercaptan

: EC50: 6.7 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Method: OECD Test Guideline 202

Toxicity to algae

t-Butyl Mercaptan

: EC50: 24 mg/l
 Exposure time: 72 h
 Species: Pseudokirchneriella subcapitata (green algae)
 Method: OECD Test Guideline 201

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Bioaccumulation

t-Butyl Mercaptan : Bioconcentration factor (BCF): 12
Bioaccumulation is unlikely.

Biodegradability

t-Butyl Mercaptan : aerobic
Result: Not readily biodegradable.
6 %
Testing period: 63 d
Method: OECD Test Guideline 301

Ecotoxicology Assessment

Acute aquatic toxicity
t-Butyl Mercaptan : Toxic to aquatic life.

Chronic aquatic toxicity
t-Butyl Mercaptan : Toxic to aquatic life with long lasting effects.

Results of PBT assessment
t-Butyl Mercaptan : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological
information : An environmental hazard cannot be excluded in the event of
unprofessional handling or disposal., Toxic to aquatic life with
long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water
courses or the soil. Do not contaminate ponds, waterways or
ditches with chemical or used container. Send to a licensed
waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.
Do not re-use empty containers. Do not burn, or use a cutting
torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN2347, BUTYL MERCAPTANS, 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2347, BUTYL MERCAPTANS, 3, II, (-26 °C), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2347, BUTYL MERCAPTAN, 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2347, BUTYL MERCAPTAN, 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation****Poisonous and Deleterious Substances Control Law**

: Not relevant

Industrial Safety and Health Law

Substances Subject to be : Not relevant

Notified Names

Enforcement Order of the : Inflammable Substance

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Industrial Safety and Health
Law - Attached table 1
(Dangerous Substances)

Hazardous Substances : Not relevant
Subject to Labeling
Requirements
Ordinance on Prevention of : Not relevant
Organic Solvent Poisoning

Chemical Substance Control Law

: Not relevant

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

: Not relevant

Other regulations

Fire Service Law : Flammable liquids
Type 1 petroleums
Hazardous rank II

Explosive Control Law : Not relevant

Vessel Safety Law : Flammable liquids (Article 2 and 3 of rules on shipping and storage of dangerous goods and its Attached Table 1), Marine pollutants

Aviation Law : Flammable liquid (Article 194 of The Enforcement Rules of Aviation Law and its Attached Table 1)

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
United States of America (USA) : On the inventory, or in compliance with the inventory
TSCA
Canada DSL : On the inventory, or in compliance with the inventory
Australia AICS : On the inventory, or in compliance with the inventory
New Zealand NZIoC : On the inventory, or in compliance with the inventory
Japan ENCS : On the inventory, or in compliance with the inventory
Korea KECI : On the inventory, or in compliance with the inventory
Philippines PICCS : On the inventory, or in compliance with the inventory
China IECSC : On the inventory, or in compliance with the inventory

SECTION 16: Other information**Further information**

Legacy SDS Number : 95900

Tertiary Butyl Mercaptan

Version 1.6

Revision Date 2017-07-06

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		