



Styrene

Version 1.7

Revision Date 2018-03-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : Styrene
 Material : 1037612, 1037607, 1037608, 1037609

Company : Chevron Phillips Chemical Company LP
 10001 Six Pines Drive
 The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America)
 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
 Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Mexico CHEMTREC 01-800-681-9531 (24 hours)
 South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
 Argentina: +(54)-1159839431

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 3
 Acute toxicity, Category 4, Inhalation
 Skin irritation, Category 2
 Eye irritation, Category 2A
 Specific target organ systemic toxicity - single exposure,
 Category 3, Respiratory system
 Specific target organ systemic toxicity - repeated exposure,
 Category 1, Inhalation, Auditory organs
 Aspiration hazard, Category 1

Styrene

Version 1.7

Revision Date 2018-03-05

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H226: Flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H332: Harmful if inhaled.
 H335: May cause respiratory irritation.
 H372: Causes damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/fume/gas/mist/vapor/spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P314 Get medical advice/ attention if you feel unwell.
 P321 Specific treatment (see supplemental first aid instructions on this label).
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Styrene

Version 1.7

Revision Date 2018-03-05

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

Group 2B: Possibly carcinogenic to humans

Styrene 100-42-5

NTP

Reasonably anticipated to be a human carcinogen

Styrene 100-42-5

ACGIH

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

SECTION 3: Composition/information on ingredients

Synonyms : Inhibited Styrene
 Phenylethylene
 Benzene, Ethenyl
 Styrol
 Cinnamene
 Vinylbenzene
 Styrolene
 Styrene Monomer

Molecular formula : C₈H₈

Component	CAS-No.	Weight %
Styrene	100-42-5	100

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

If inhaled : Move to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. Protect unharmed eye. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a

Styrene

Version 1.7

Revision Date 2018-03-05

physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point	:	31 °C (88 °F) Method: closed cup
Autoignition temperature	:	490 °C (914 °F)
Suitable extinguishing media	:	Dry chemical. Carbon dioxide (CO ₂). Alcohol-resistant foam.
Unsuitable extinguishing media	:	High volume water jet.
Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire and explosion protection	:	Normal measures for preventive fire protection. Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	:	No data available.

SECTION 6: Accidental release measures

Personal precautions	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

SDS Number:100000068536

4/14

Styrene

Version 1.7

Revision Date 2018-03-05

Advice on safe handling : Inspect tank vents periodically. Styrene vapors may polymerize in vents or flame arrestors of storage tanks. Check temperature, inhibitor and polymer content at least once a week during warm weather. Increase monitoring frequency if stored at greater than 70 F for longer than 30 days. Minimize storage time.

Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. Review all operations, which have the potential to generating and accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106 "Flammable and Combustible Liquids"; National Fire Protection Association (NFPA 77), "Recommended Practice on Static Electricity"; and/or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising Out of Static, Lightning, and stray Currents". For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Normal measures for preventive fire protection. Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Take precautionary measures against static discharges.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Ingredients	Basis	Value	Control parameters	Note
Styrene	OSHA Z-2	TWA	100 ppm,	
	OSHA Z-2	CEIL	200 ppm,	
	OSHA Z-2	Peak	600 ppm,	
	OSHA Z-1-A	TWA	50 ppm, 215 mg/m ³	
	OSHA Z-1-A	STEL	100 ppm, 425 mg/m ³	
	ACGIH	TWA	20 ppm,	CNS impair, URT irr, peripheral neuropathy, BEI, A4,
	ACGIH	STEL	40 ppm,	CNS impair, URT irr, peripheral neuropathy, BEI, A4,

A4 Not classifiable as a human carcinogen

BEI Substances for which there is a Biological Exposure Index or Indices (see BEI® section)

Styrene

Version 1.7

Revision Date 2018-03-05

CNS impair Central Nervous System impairment
 peripheral Peripheral neuropathy
 neuropathy
 URT irr Upper Respiratory Tract irritation

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Styrene	100-42-5	Immediately Dangerous to Life or Health Concentration Value 700 parts per million	1995-03-01

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Tightly fitting safety goggles. Eye wash bottle with pure water.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Styrene

Version 1.7

Revision Date 2018-03-05

Physical state : Liquid
 Color : Colorless
 Odor : Sweet

Safety data

Flash point : 31 °C (88 °F)
 Method: closed cup

Lower explosion limit : 0.9 %(V)

Upper explosion limit : 6.8 %(V)

Oxidizing properties : no

Autoignition temperature : 490 °C (914 °F)

Molecular formula : C₈H₈

Molecular weight : 104.16 g/mol

pH : Not applicable

Freezing point : -30.63 °C (-23.13 °F)

Pour point : No data available

Boiling point/boiling range : 145.15 °C (293.27 °F)

Vapor pressure : 4.50 MMHG
 at 20 °C (68 °F)

Relative density : 0.91
 at 20 °C (68 °F)

Water solubility : 0.029 wt.% styrene in water @ 20 °C (68°F)

Partition coefficient: n-octanol/water : log Pow: 2.96
 at 25 °C (77 °F)

Viscosity, dynamic : 0.763 cP

Relative vapor density : 3.6
 (Air = 1.0)

Evaporation rate : No data available

Percent volatile : > 99 %

Other information

Conductivity : < 50 pSm

SECTION 10: Stability and reactivity

Styrene

Version 1.7

Revision Date 2018-03-05

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution.
No decomposition if stored and applied as directed.

Possibility of hazardous reactions

- Conditions to avoid : heat, light, catalysts, halogens or any other chemicals.
Heat, flames and sparks.
- Materials to avoid : Corrosive to copper and copper bearing alloys.
- Hazardous decomposition products : No data available
- Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

- Styrene : LD50: > 5,000 mg/kg
Species: Rat
Sex: male and female

Acute inhalation toxicity

- Styrene : LD50: 11.8 mg/l
Exposure time: 4 h
Species: Rat
Test atmosphere: vapor

Acute dermal toxicity

- Styrene : LD50: > 2,000 mg/kg
Species: Rat
Sex: male and female

Styrene

- Skin irritation** : May cause skin irritation in susceptible persons.

Styrene

- Eye irritation** : Irritating to eyes.

Sensitization

- Styrene : Classification: Does not cause skin sensitization.
largely based on human evidence.

Repeated dose toxicity

Styrene

Version 1.7

Revision Date 2018-03-05

Styrene : Species: Mouse, Male and female
 Sex: Male and female
 Application Route: Oral
 Dose: 0. 150, 300 mg/kg
 Exposure time: 78 wk
 Number of exposures: 5 d/wk
 NOEL: 150 mg/kg
 Lowest observable effect level: 300 mg/kg

Species: Rat, male
 Sex: male
 Application Route: Inhalation
 Dose: 0. 500, 650, 850, 1000 ppm
 Exposure time: 4 wk
 Number of exposures: 6 h/d, 5 d/wk
 NOEL: 500 ppm
 Target Organs: Ototoxicity

Styrene
Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

Styrene : Carcinogenicity: This substance has been reported to cause tumors in certain animal species.
 Mutagenicity: In vitro tests showed mutagenic effects which were not observed with in vivo test.
 Teratogenicity: Did not show teratogenic effects in animal experiments.
 Reproductive toxicity: No toxicity to reproduction

Styrene
Further information : Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

Styrene : LC50: 4.02 mg/l
 Exposure time: 96 h
 Species: Pimephales promelas (fathead minnow)
 flow-through test Test substance: yes
 Toxic to fish.

Toxicity to daphnia and other aquatic invertebrates

Styrene : EC50: 4.7 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 flow-through test

Toxicity to algae

Styrene : EC50: 4.9 mg/l
 Exposure time: 72 h
 Species: Selenastrum capricornutum (algae)

Styrene

Version 1.7

Revision Date 2018-03-05

Toxicity to bacteria

Styrene : EC10: 0.28 mg/l
 Exposure time: 96 h
 Growth rate
 Species: Skeletonema costatum (Marine Algae)
 Test substance: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Styrene : NOEC: 1.01 mg/l
 Exposure time: 21 d
 Species: Daphnia magna (Water flea)
 semi-static test
 Test substance: yes
 Method: OECD Test Guideline 211

Elimination information (persistence and degradability)

Bioaccumulation

Styrene : Does not significantly accumulate in organisms.

Biodegradability : According to the results of tests of biodegradability this product is considered as being readily biodegradable.

Ecotoxicology Assessment

Acute aquatic toxicity

Styrene : Toxic to aquatic life.

Chronic aquatic toxicity

Styrene : Harmful to aquatic life with long lasting effects.

Results of PBT assessment

Styrene : This substance is not considered to be very persistent and very bioaccumulating (vPvB)., This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Styrene

Version 1.7

Revision Date 2018-03-05

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN2055, STYRENE MONOMER, STABILIZED, 3, III, RQ (STYRENE)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN2055, STYRENE MONOMER, STABILIZED, 3, III, (31 °C)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2055, STYRENE MONOMER, STABILIZED, 3, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2055, STYRENE MONOMER, STABILIZED, 3, III, (D/E)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN2055, STYRENE MONOMER, STABILIZED, 3, III

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2055, STYRENE MONOMER, STABILIZED, 3, III

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Styrene

Version 1.7

Revision Date 2018-03-05

Other information	: Styrene Monomer, S.T.3, Cat. Y
--------------------------	---

SECTION 15: Regulatory information**National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Acute toxicity (any route of exposure)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Aspiration hazard
 Specific target organ toxicity (single or repeated exposure)

EPCRA - EMERGENCY PLANNING COMMUNITY RIGHT - TO - KNOW

CERCLA Reportable Quantity : 1000 lbs
 Styrene

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients : The following components are subject to reporting levels established by SARA Title III, Section 313:
 : Styrene - 100-42-5

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):
 : Styrene - 100-42-5

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Styrene

Version 1.7

Revision Date 2018-03-05

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

: Styrene - 100-42-5

US State Regulations

Pennsylvania Right To Know

: Styrene - 100-42-5

New Jersey Right To Know

: Styrene - 100-42-5

California Prop. 65
Ingredients


: WARNING! This product contains a chemical known in the
State of California to cause cancer.
Styrene 100-42-5

Notification status

Europe REACH	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On the inventory, or in compliance with the inventory
Canada DSL	:	On the inventory, or in compliance with the inventory
Australia AICS	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 2

**Further information**

Legacy SDS Number : CPC00089

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

Styrene

Version 1.7

Revision Date 2018-03-05

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		