



TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product information

Trade name : TrackTek® 100 ULE
 Material : 1108537, 1108536, 1108535, 1062622, 1062256, 1062507, 1062508, 1062509

Company : Chevron Phillips Chemical Company LP
 Specialty Chemicals
 10001 Six Pines Drive
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals (Shanghai) Corporation
 2299 West Yan an Road, Shanghai

MSDS Requests: 852-29784899
 Technical Information: 86-21-62362199
 Responsible Party: Product Safety Group
 Email:msds@cpchem.com

 ConocoPhillips China Inc.
 Shekou
 Shenzhen, 518067
 China

MSDS Requests: 852-29784899
 Technical Information: 86-755-26812393
 Responsible Party: Product Safety Group
 Email:msds@cpchem.com

Emergency telephone:

Health:
 866.442.9628 (North America)
 1.832.813.4984 (International)

Transport:
 North America: CHEMTREC 800.424.9300 or 703.527.3887
 Asia: +800 CHEMCALL (+800 2436 2255) China: 0532.8388.9090
 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Chemcare Asia: Tel: +65 6848 9048 - Mob: +65 8382 9188 - Fax: +65 6848
 South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
 E-mail address : MSDS@CPChem.com
 Website : www.CPChem.com

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

2. HAZARDS IDENTIFICATION**GHS-Classification**

: Flammable liquids, Category 2
 Acute toxicity, Category 5, Dermal
 Acute toxicity, Category 3, Inhalation
 Eye irritation, Category 2A
 Skin irritation, Category 2
 Aspiration hazard, Category 1
 Acute aquatic toxicity, Category 1

GHS-Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H400: Very toxic to aquatic life.

Precautionary Statements

: **Prevention:**
 P210: Keep away from heat/sparks/open flames/hot surfaces.
 - No smoking.
 P243: Take precautionary measures against static discharge.
 P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 P331: Do NOT induce vomiting.
 P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
 P391: Collect spillage.
Storage:
 P403 + P233: Store in a well-ventilated place. Keep container tightly closed.
Disposal:
 P501: Dispose of contents/ container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Motor Fuel

Molecular formula : Mixture

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

Chemical Name	CAS-No. / EINECS-No.	Concentration [wt%]
2,2,4-Trimethylpentane (Isooctane)	540-84-1	30 - 80
Isopentane	78-78-4	5 - 30
Toluene	108-88-3	10 - 30
Ethanol	64-17-5	10 - 30
Isoalkanes 7-8	70024-92-9	1 - 10

4. FIRST AID MEASURES

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.
- If inhaled : If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

5. FIRE-FIGHTING MEASURES

- Flash point : < -37 °C (< -35 °F)
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion : Do not spray on an open flame or any other incandescent

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

protection material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Carbon Dioxide. Carbon oxides.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE**Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
2,2,4-Trimethylpentane (Isooctane)	Manufacturer	TWA	300 ppm,	
Isoalkanes 7-8	Manufacturer	TWA	300 ppm,	

CN

Ingredients	Basis	Value	Control parameters	Note
Toluene	CN OEL	PC-TWA	50 mg/m3	Skin,
	CN OEL	PC-STEL	100 mg/m3	Skin,
Isopentane	CN OEL	PC-TWA	500 mg/m3	
	CN OEL	PC-STEL	1.000 mg/m3	

Skin Skin

Personal protective equipment

- Respiratory protection : In the case of vapor formation use a respirator with an approved filter. Use NIOSH approved respiratory protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles. Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties****Appearance**

- Form : Liquid
- Physical state : Liquid
- Color : Various
- Odor : Strong gasoline

Safety data

- Flash point : < -37 °C (< -35 °F)
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : No
- Autoignition temperature : No data available
- Molecular formula : Mixture

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

Molecular Weight	: Not applicable
pH	: Not applicable
Freezing point	: -94,44 °C (-137,99 °F)
Pour point	No data available
Boiling point/boiling range	: 46 - 116 °C (115 - 241 °F)
Vapor pressure	: 6,70 PSI at 38 °C (100 °F)
Relative density	: 7,45, 16 °C(61 °F)
Density	: 5,97 L/G
Water solubility	: The ethanol component of this fuel is soluble in water.
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Relative vapor density	: 3,2 (Air = 1.0)
Evaporation rate	: > 1
Percent volatile	: > 99 %

10. STABILITY AND REACTIVITY**Possibility of hazardous reactions**

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Other data	: No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION**TrackTek® 100 ULE**

Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg
Method: Calculation method

TrackTek® 100 ULE

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Method: Calculation method

TrackTek® 100 ULE

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

TrackTek® 100 ULE**Skin irritation**

: May cause skin irritation in susceptible persons.

TrackTek® 100 ULE**Eye irritation**

: May cause irreversible eye damage.

TrackTek® 100 ULE**Sensitization**

: No adverse effects expected.

Repeated dose toxicity2,2,4-Trimethylpentane
(Isooctane): Species: rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 0, 668, 2220, 6646 ppm
Exposure time: 13 weeks
Number of exposures: 6 hr/day 5 d/wk
NOEL: 8,117 mg/l 2220 ppm
Method: OECD Guideline 413
Information given is based on data obtained from similar substances.

Isopentane

Species: rat
Application Route: Inhalation
Dose: 1, 1000, 4500 ppm
Exposure time: 13 wk
Number of exposures: 6 h/d, 5 d/wk
NOEL: 2250 ppm

Toluene

Species: rat
Application Route: Inhalation
Dose: 0, 100, 625, 1250, 3000 ppm
Exposure time: 15 wk
Number of exposures: 6.5 h/d, 5 d/wk
NOEL: 625 ppmSpecies: mouse
Application Route: Inhalation
Dose: 0, 100, 625, 1250, 3000 ppm
Exposure time: 14 wk
Number of exposures: 6.5 h/d, 5 d/wk
NOEL: 100 ppm

Ethanol

Species: rat
Application Route: Oral diet
Dose: 5%
Exposure time: 13 wk
Number of exposures: in drinking water
NOEL: < 5%
Lowest observable effect level: 5%
Target Organs: Liver

Isoalkanes 7-8

Species: rat
Application Route: Inhalation
Dose: 0, 385, 1180 ppm
Exposure time: 12 wk
Number of exposures: 6 hr/d, 5 d/wk
NOEL: > 1180 ppm

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

Target Organs: Kidney

Carcinogenicity

Toluene

: Species: rat
 Dose: 0, 600, 1200 ppm
 Exposure time: 2 yrs
 Number of exposures: 6.5 h/d, 5 d/wk
 Remarks: No evidence of carcinogenicity

Species: mouse
 Dose: 0, 600, 1200 ppm
 Exposure time: 2 yrs
 Number of exposures: 6.5 h/d, 5 d/wk
 Remarks: No evidence of carcinogenicity

Ethanol

Species: mouse
 Sex: male
 Dose: 2.5, 5%
 Exposure time: 2 yrs
 Number of exposures: in drinking water
 Remarks: Increase in liver tumors

Species: mouse
 Sex: female
 Dose: 2.5, 5%
 Exposure time: 2 yrs
 Number of exposures: in drinking water
 Remarks: no increase in tumors

Species: rat
 Dose: 5%
 Exposure time: 30 mo
 Number of exposures: in drinking water
 Remarks: increase number of liver, pituitary, adrenal, and pancreatic tumors

Reproductive toxicity2,2,4-Trimethylpentane
(Isooctane)

: Species: rat
 Sex: male and female
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6 h/d 5 d/wk
 Method: OECD Test Guideline 416
 NOAEL Parent: 3000 ppm
 NOAEL F1: 3000 ppm
 NOAEL F2: 3000 ppm

Toluene

Species: rat
 Application Route: Inhalation
 Dose: 0, 100, 500, 2000 ppm
 Test period: 95 d
 NOAEL Parent: 2000 ppm

Teratogenicity

2,2,4-Trimethylpentane

: Species: rat

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

(Isooctane)

Application Route: Inhalation
 Dose: 0, 400, 1200 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 NOAEL Teratogenicity: 1200 ppm
 NOAEL Maternal: 1200 ppm

Species: rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 9000 ppm
 NOAEL Maternal: 3000 ppm

Toluene

Species: rat
 Application Route: Inhalation
 Dose: 0, 100, 500, 2000 ppm
 Test period: 95 d
 NOAEL Teratogenicity: 400-750 ppm

Ethanol

Species: mouse
 Application Route: oral gavage
 Dose: 17, 25, 30 %
 NOAEL Teratogenicity: 17%

**TrackTek® 100 ULE
Aspiration toxicity**

: May be fatal if swallowed and enters airways.
 Substances known to cause human aspiration toxicity hazards
 or to be regarded as if they cause human aspiration toxicity
 hazard.

CMR effects2,2,4-Trimethylpentane
(Isooctane)

: Carcinogenicity: Not available
 Mutagenicity: Tests on bacterial or mammalian cell cultures
 did not show mutagenic effects.
 Teratogenicity: Animal testing did not show any effects on
 fetal development.
 Reproductive toxicity: Animal testing did not show any effects
 on fertility.

**TrackTek® 100 ULE
Further information**

: Solvents may degrease the skin.

12. ECOLOGICAL INFORMATION**Toxicity to fish**2,2,4-Trimethylpentane
(Isooctane)

: LC50: 0,11 mg/l
 Exposure time: 96 HR
 Species: Oncorhynchus mykiss (rainbow trout)
 semi-static test Method: OECD Test Guideline 203
 Information given is based on data obtained from similar
 substances.

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

Isopentane	LC50: 3,1 mg/l Exposure time: 96 HR Species: Oncorhynchus mykiss (rainbow trout)
Toluene	LC50: 18 - 36 mg/l Exposure time: 96 HR Species: Pimephales promelas (fathead minnow)
Ethanol	LC50: 13.480 mg/l Exposure time: 96 HR Species: Pimephales promelas (fathead minnow)
Isoalkanes 7-8	LC50: 5,4 mg/l Exposure time: 96 HR Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates.

2,2,4-Trimethylpentane (Isooctane)	: EC50: 0,4 mg/l Exposure time: 48 HR Species: Daphnia magna (Water flea) static test Information given is based on data obtained from similar substances.
Isopentane	EC50: 2,3 mg/l Exposure time: 48 HR Species: Daphnia magna (Water flea)
Toluene	EC50: 3,78 mg/l Exposure time: 48 HR Species: Daphnia magna (Water flea)
Ethanol	LC50: 12.340 mg/l Exposure time: 48 HR Species: Daphnia magna (Water flea)
Isoalkanes 7-8	7,4 mg/l Exposure time: 48 HR Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202

Toxicity to algae

2,2,4-Trimethylpentane (Isooctane)	: EL50: 2,943 mg/l Exposure time: 72 HR Method: QSAR modeled data
Toluene	EC50: 134 mg/l Exposure time: 72 HR Species: Chlamydomonas angulosa (Green algae)
Ethanol	EC50: 1.000 mg/l Exposure time: 72 HR Species: Chlorella vulgaris (Fresh water algae)
Isoalkanes 7-8	EL50: 29,0 mg/l Exposure time: 72 HR Species: Raphidocellus subcapitata (algae)

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

Growth inhibition Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates. (Chronic toxicity)

2,2,4-Trimethylpentane (Isooctane) : NOEC: 0,17 mg/l
 Exposure time: 21 D
 Species: Daphnia magna (Water flea)

Elimination information (persistence and degradability)**Bioaccumulation**

2,2,4-Trimethylpentane (Isooctane) : Bioconcentration factor (BCF): 231
 Method: Estimated based on individual component values.

Isopentane : Accumulation in aquatic organisms is unlikely.

Biodegradability : Expected to be biodegradable

Further information on ecology**Results of PBT assessment**

2,2,4-Trimethylpentane (Isooctane) : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
 Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

USDOT

UN3475, ETHANOL AND GASOLINE MIXTURE, 3, II

IMO / IMDG

UN3475, ETHANOL AND GASOLINE MIXTURE, 3, II, MP (2,2,4-TRIMETHYLPENTANE (ISOOCTANE), TOLUENE), (< -37 °C)

IATA

UN3475, ETHANOL AND GASOLINE MIXTURE, 3, II

ADR

UN3475, ETHANOL AND GASOLINE MIXTURE, 3, II

RID

UN3475, ETHANOL AND GASOLINE MIXTURE, 3, II

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

15. REGULATORY INFORMATION

Classification and Labeling of Commonly Used Dangerous Chemical Substances : Primary label: Combustible Liquid.

Notification status

Europe REACH	: On the inventory, or in compliance with the inventory
United States of America US.TSCA	: On the inventory, or in compliance with the inventory
Canada NDSL	: On the inventory, or in compliance with the inventory
Australia AICS	: On the inventory, or in compliance with the inventory
New Zealand NZIoC	: Not in compliance with the inventory
Japan ENCS	: On the inventory, or in compliance with the inventory
Korea KECI	: On the inventory, or in compliance with the inventory
Philippines PICCS	: Not in compliance with the inventory
China IECSC	: Not in compliance with the inventory

16. OTHER INFORMATION**Further information**

Legacy MSDS Number : CPC00143

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this MSDS pertains only to the product as shipped.

TrackTek® 100 ULE

Version 1.5

Revision Date 2011-05-25

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LOAEL	Lowest Observed Adverse Effect Level
AICS	Australia, Inventory of Chemical Substances	NFPA	National Fire Protection Agency
DSL	Canada, Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
NDSL	Canada, Non-Domestic Substances List	NTP	National Toxicology Program
CNS	Central Nervous System	NZIoC	New Zealand Inventory of Chemicals
CAS	Chemical Abstract Service	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration	NOEC	No Observed Effect Concentration
EC50	Effective Concentration 50%	OSHA	Occupational Safety & Health Administration
EINECS	European Inventory of Existing Chemical Substances	PEL	Permissible Exposure Limit
MAK	Germany Maximum Concentration Values	PICCS	Philippines Inventory of Commercial Chemical Substances
GHS	Globally Harmonized System	PRNT	Presumed Not Toxic
>=	Greater Than or Equal To	RCRA	Resource Conservation Recovery Act
IC50	Inhibition Concentration 50%	STEL	Short-term Exposure Limit
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act.
IECSC	Inventory of Existing Chemical Substances in China	TLV	Threshold Limit Value
ENCS	Japan, Inventory of Existing and New Chemical Substances	TWA	Time Weighted Average
KECI	Korea, Existing Chemical Inventory	TSCA	Toxic Substance Control Act
<=	Less Than or Equal To	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
LC50	Lethal Concentration 50%	WHMIS	Workplace Hazardous Materials Information System
LD50	Lethal Dose 50%		