


SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking
Product information

Product Name : SOLTROL® 10 Isoparaffin Solvent
 Material : 1089830, 1017316, 1017315, 1017318, 1017317, 1017319,
 1017320, 1017321, 1017314

Company : Chevron Phillips Chemical Company LP
 Specialty Chemicals
 10001 Six Pines Drive
 The Woodlands, TX 77380

Emergency telephone:
Health:

866.442.9628 (North America)
 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
 Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
 Mexico CHEMTREC 01-800-681-9531 (24 hours)
 South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
 Argentina: +(54)-1159839431
 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)
 Belgium: 070 245 245 (24 hours/day, 7 days/week)
 Bulgaria: +359 2 9154 233
 Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
 Cyprus: 1401
 Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
 Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212
 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Finland: 0800 147 111 09 471 977 (24 hours/day)
 France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
 Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
 Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
 Iceland: 543 2222 (24 hours/day, 7 days/week)
 Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic
 Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371
 67042473. (24 hours.)

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Lithuania: +370 (85) 2362052
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
 Malta: +356 2395 2000
 The Netherlands: NVIC: +31 (0)88 755 8000
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Portugal: CIAV phone number: +351 800 250 250
 Romania: +40213183606
 Slovakia: +421 2 5477 4166
 Slovenia: Phone number: 112
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)
 Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 2
 Skin irritation, Category 2
 Specific target organ toxicity - single exposure, Category 3,
 Central nervous system
 Aspiration hazard, Category 1

Labeling

Symbol(s) : 

Signal Word : Danger

Hazard Statements : H225: Highly flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H336: May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
 P264 Wash skin thoroughly after handling.

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3: Composition/information on ingredients

Synonyms : Not Established

Molecular formula : UVCB

Component	CAS-No.	Weight %
Isoalkanes C7-8	70024-92-9	100
2,2,4-Trimethylpentane (Isooctane)	540-84-1	60 - 80

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : -11°C (12°F)
Method: Tag closed cup

Autoignition temperature : 420°C (788°F)

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Carbon Dioxide. Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
Isoalkanes C7-8	Manufacturer	TWA	300 ppm,	

US

Components	Basis	Value	Control parameters	Note
2,2,4-Trimethylpentane (Isooctane)	ACGIH	TWA	300 ppm,	

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : liquid
- Physical state : liquid
- Color : Colorless at room temperature
- Odor : Mild

Safety data

- Flash point : -11°C (12°F)
Method: Tag closed cup
- Lower explosion limit : 1 %(V)
- Oxidizing properties : No
- Autoignition temperature : 420°C (788°F)
- Molecular formula : UVCB
- Molecular weight : Not applicable
- pH : Not applicable
- Pour point : No data available

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

Boiling point/boiling range	: 93.3-104.4°C (199.9-219.9°F)
Vapor pressure	: 114.64 MMHG at 37.8°C (100.0°F)
Relative density	: 0.697 at 15.6 °C (60.1 °F)
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 0.56 cSt at 40°C (104°F)
Relative vapor density	: 2 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur. Further information: No hazards to be specially mentioned. Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition products	: Carbon Dioxide Carbon oxides
Other data	: No decomposition if stored and applied as directed.

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

SECTION 11: Toxicological information**Acute oral toxicity**

Isoalkanes C7-8 : LD50: > 7,100 - 7,800 mg/kg
 Species: Rat
 Sex: male
 Method: OECD Test Guideline 401
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane (Isooctane) LD50: > 5,000 mg/kg
 Species: Rat
 Sex: male and female
 Method: OECD Test Guideline 401
 Symptoms: Salivation

Acute inhalation toxicity

Isoalkanes C7-8 : LC50: > 23.3 mg/l
 Exposure time: 4 h
 Species: Rat
 Sex: male and female
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane (Isooctane) LC50: > 33.52 mg/l
 Exposure time: 4 h
 Species: Rat
 Sex: male and female
 Test atmosphere: vapor
 Method: OECD Test Guideline 403

Acute dermal toxicity

Isoalkanes C7-8 : LD50: > 2,200 - 2,500 mg/kg
 Species: Rat
 Method: OECD Test Guideline 402
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane (Isooctane) LD50: > 2,000 mg/kg
 Species: Rabbit
 Sex: male and female
 Method: OECD Test Guideline 402

SOLTROL® 10 Isoparaffin Solvent

Skin irritation : Skin irritation

SOLTROL® 10 Isoparaffin Solvent

Eye irritation : Vapors may cause irritation to the eyes, respiratory system

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

and the skin.

SOLTROL® 10 Isoparaffin Solvent**Sensitization**

: Did not cause sensitization on laboratory animals.
Information given is based on data obtained from similar substances.

Repeated dose toxicity

Isoalkanes C7-8

: Species: Rat, male and female
Sex: male and female
Application Route: Inhalation
Dose: 0, 400, 1200 ppm
Exposure time: 12 wk
Number of exposures: 6 hr/d, 5 d/wk
NOEL: 1200 ppm
Method: OECD Test Guideline 413
Target Organs: Kidney
Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane
(Isooctane)

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 0, 668, 2220, 6646 ppm
Exposure time: 13 weeks
Number of exposures: 6 hr/day 5 d/wk
NOEL: 8.117 mg/l 2220 ppm
Method: OECD Guideline 413
Information given is based on data obtained from similar substances.

Genotoxicity in vitro

Isoalkanes C7-8

: Test Type: Ames test
Result: negative

2,2,4-Trimethylpentane
(Isooctane)

Test Type: Ames test
Method: Mutagenicity (Escherichia coli - reverse mutation assay)
Result: negative

Test Type: Mouse lymphoma assay
Method: OECD Guideline 476
Result: negative

Test Type: Sister Chromatid Exchange Assay
Result: negative

Test Type: Unscheduled DNA synthesis assay
Result: negative

Genotoxicity in vivo2,2,4-Trimethylpentane
(Isooctane)

: Test Type: Unscheduled DNA synthesis assay
Species: Mouse
Dose: 500 mg/kg
Result: negative

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

Test Type: Unscheduled DNA synthesis assay
 Species: Rat
 Dose: 500 mg/kg
 Result: negative

Reproductive toxicity

Isoalkanes C7-8

: Species: Rat
 Sex: male and female
 Application Route: inhalation (vapor)
 Number of exposures: 6 hr/d; 5 d/wk
 Method: OECD Test Guideline 416
 NOAEL Parent: 10,560 mg/m³
 NOAEL F1: 31,680 mg/m³
 NOAEL F2: 31,680 mg/m³
 Fertility and developmental toxicity tests did not reveal any effect on reproduction.
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane
(Isooctane)

Species: Rat
 Sex: male and female
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6 h/d 5 d/wk
 Method: OECD Test Guideline 416
 NOAEL Parent: 3000 ppm
 NOAEL F1: 3000 ppm
 NOAEL F2: 3000 ppm
 Information given is based on data obtained from similar substances.

Developmental Toxicity

Isoalkanes C7-8

: Species: Rat
 Application Route: Inhalation
 Dose: 500, 2000, 7000 ppm
 Exposure time: 6 hr/d
 Test period: GD 6-15
 Method: OECD Guideline 414
 NOAEL Teratogenicity: > 21,000 mg/m³
 NOAEL Maternal: > 21,000 mg/m³
 Animal testing did not show any effects on fetal development.
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane
(Isooctane)

Species: Rat
 Application Route: Inhalation
 Dose: 0, 400, 1200 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 NOAEL Teratogenicity: 1200 ppm
 NOAEL Maternal: 1200 ppm
 Information given is based on data obtained from similar substances.

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6h/d
 Test period: GD6-15
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 9000 ppm
 NOAEL Maternal: 3000 ppm
 Information given is based on data obtained from similar substances.

SOLTROL® 10 Isoparaffin Solvent

Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

Isoalkanes C7-8 : Carcinogenicity: Not available
 Mutagenicity: In vitro tests did not show mutagenic effects
 Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

2,2,4-Trimethylpentane (Isooctane) : Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: Animal testing did not show any effects on fertility.

SOLTROL® 10 Isoparaffin Solvent

Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity effects****Toxicity to fish**

Isoalkanes C7-8 : LL50: 3 - 10 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 Method: OECD Test Guideline 203
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane (Isooctane) : LC50: 0.11 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 semi-static test Method: OECD Test Guideline 203
 Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

Isoalkanes C7-8 : EL50: 4.6 - 10 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Method: OECD Test Guideline 202
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane (Isooctane) EC50: 0.4 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 static test Information given is based on data obtained from similar substances.

Toxicity to algae

Isoalkanes C7-8 : EL50: 29.0 mg/l
 Exposure time: 72 h
 Species: Pseudokirchneriella subcapitata (green algae)
 Growth inhibition Method: OECD Test Guideline 201

2,2,4-Trimethylpentane (Isooctane) EL50: 2.943 mg/l
 Exposure time: 72 h
 Method: QSAR modeled data

Toxicity to fish (Chronic toxicity)

Isoalkanes C7-8 : EL10: 0.38 mg/l
 Exposure time: 60 d
 Species: Oncorhynchus mykiss (rainbow trout)
 Method: QSAR modeled data

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Isoalkanes C7-8 : NOELR: 1 mg/l
 Exposure time: 21 d
 Species: Daphnia magna (Water flea)
 Method: OECD Test Guideline 211
 Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane (Isooctane) : NOEL: 0.17 mg/l
 Exposure time: 21 d
 Species: Daphnia magna (Water flea)
 Method: OECD Test Guideline 211
 Information given is based on data obtained from similar substances.

Biodegradability

Isoalkanes C7-8 : Result: Not readily biodegradable.
 60 %
 Testing period: 60 d
 Method: OECD Test Guideline 301F
 Expected to be inherently biodegradable.

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

Information given is based on data obtained from similar substances.

2,2,4-Trimethylpentane (Isooctane) : Result: Not readily biodegradable.
Method: OECD Test Guideline 301
Expected to be inherently biodegradable.
Information given is based on data obtained from similar substances.

Elimination information (persistence and degradability)

Bioaccumulation

Isoalkanes C7-8 : This material is not expected to bioaccumulate.

2,2,4-Trimethylpentane (Isooctane) : Bioconcentration factor (BCF): 231
Method: QSAR modeled data
This material is not expected to bioaccumulate.

Mobility : Medium: Air
Method: Calculation, Mackay Level III Fugacity Model
Content: 100 %

Results of PBT assessment

Isoalkanes C7-8 : Non-classified PBT substance, Non-classified vPvB substance

2,2,4-Trimethylpentane (Isooctane) : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard

Isoalkanes C7-8 : Toxic to aquatic life.

2,2,4-Trimethylpentane (Isooctane) : Very toxic to aquatic life.

Long-term (chronic) aquatic hazard

Isoalkanes C7-8 : Toxic to aquatic life with long lasting effects.

2,2,4-Trimethylpentane (Isooctane) : Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, MARINE POLLUTANT, (2,2,4-TRIMETHYLPENTANE (ISOOCTANE)), RQ (2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, (-11 °C c.c.), MARINE POLLUTANT, (ISOALKANES C7-8, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (ISOALKANES C7-8, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33, UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (ISOALKANES C7-8, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (ISOALKANES C7-8, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information**National legislation**

SDS Number:100000067719

14/18

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Aspiration hazard
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)

CERCLA Reportable Quantity : 1250 lbs
2,2,4-Trimethylpentane (Isooctane)

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):
: 2,2,4-Trimethylpentane (Isooctane) - 540-84-1

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

Pennsylvania Right To Know

: Isoalkanes C7-8 - 70024-92-9
 2,2,4-Trimethylpentane (Isooctane) - 540-84-1

California Prop. 65
Components

: WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov/food.

Ethylbenzene	100-41-4
Benzene	71-43-2

WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Toluene	108-88-3
Benzene	71-43-2

Notification status

Europe REACH : This product is in full compliance according to REACH regulation 1907/2006/EC.

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) TSCA : On or in compliance with the active portion of the TSCA inventory

Canada DSL : This product has been notified and approved for listing on the Canadian DSL. At this time, only Chevron Phillips Chemical Company LP can legally import the product into Canada.

Australia AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : Not in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory

Korea KECI : A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).

Philippines PICCS : Not in compliance with the inventory

China IECSC : Not in compliance with the inventory

Taiwan TCSI : On the inventory, or in compliance with the inventory


SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 34750

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act

SOLTROL® 10 Isoparaffin Solvent

Version 1.12

Revision Date 2022-10-21

	New Chemical Substances		
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		