

**TrusTec™ Diesel Cetane, Check Fuel, High**

Version 3.4

Revision Date 2024-02-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : TrusTec™ Diesel Cetane, Check Fuel, High
Material : 1104936, 1024267, 1024266, 1024265, 1024264, 1024263

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
Mexico CHEMTREC 01-800-681-9531 (24 hours)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Argentina: +(54)-1159839431
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)
Belgium: 070 245 245 (24 hours/day, 7 days/week)
Bulgaria: +359 2 9154 233
Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
Cyprus: 1401
Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
Denmark: Danish Poison Center (Gifftlinjen): +45 8212 1212
Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Finland: 0800 147 111 09 471 977 (24 hours/day)
France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
Iceland: 543 2222 (24 hours/day, 7 days/week)
Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 4
Acute toxicity, Category 4, Inhalation
Skin irritation, Category 2
Carcinogenicity, Category 2
Specific target organ toxicity - repeated exposure, Category 2,
Liver, Blood, thymus
Aspiration hazard, Category 1

Labeling

Symbol(s) :



Signal Word :

: Danger

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Hazard Statements : H227: Combustible liquid.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H332: Harmful if inhaled.
 H351: Suspected of causing cancer.
 H373: May cause damage to organs (Liver, Blood, thymus) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Symptoms of Overexposure : No data available

Carcinogenicity:

IARC	Group 2B: Possibly carcinogenic to humans
	Naphthalene 91-20-3
NTP	Reasonably anticipated to be a human carcinogen
	Naphthalene 91-20-3

SECTION 3: Composition/information on ingredients

Synonyms : Diesel Special Test Fuel

SDS Number:100000100063

3/17

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

High Cetane Check Fuel Diesel

Molecular formula : Mixture

Component	CAS-No.	Weight %
Diesel fuel, no. 2	68476-34-6	100
Naphthalene	91-20-3	0 - 1

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Notes to physician

- Symptoms : No data available.
- Risks : No data available.
- Treatment : No data available.

SECTION 5: Firefighting measures

- Flash point : 80.8°C (177.4°F)
Method: ASTM D 93
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon Dioxide. Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Storage

- Requirements for storage : No smoking. Keep in a well-ventilated place. Containers

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

areas and containers

which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Components	Basis	Value	Control parameters	Note
Diesel fuel, no. 2	ACGIH	TWA	100 mg/m3	A3, Skin, Inhalable fraction and vapor
Naphthalene	ACGIH	TWA	10 ppm,	A3, Skin,
	ACGIH	STEL	15 ppm,	hematologic eff, URT irr, eye irr, eye dam, (), A4, Skin,
	OSHA Z-1	TWA	10 ppm, 50 mg/m3	
	OSHA Z-1-A	TWA	10 ppm, 50 mg/m3	
	OSHA Z-1-A	STEL	15 ppm, 75 mg/m3	

- () Adopted values or notations enclosed are those for which changes are proposed in the NIC
- A3 Confirmed animal carcinogen with unknown relevance to humans
- A4 Not classifiable as a human carcinogen
- eye dam Eye damage
- eye irr Eye irritation
- hematologic eff Hematologic effects
- Skin Danger of cutaneous absorption
- URT irr Upper Respiratory Tract irritation

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Naphthalene	91-20-3	Immediately Dangerous to Life or Health Concentration Value 250 parts per million	1995-03-01

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant protective clothing. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear. Footwear protecting against chemicals.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : liquid
- Physical state : liquid
- Color : Pale yellow, Brown
- Odor : Mild

Safety data

- Flash point : 80.8°C (177.4°F)
Method: ASTM D 93
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : No
- Autoignition temperature : No data available
- Thermal decomposition : No data available
- Molecular formula : Mixture
- Molecular weight : Not applicable
- pH : Not applicable
- Pour point : -15°C (5°F)
Method: ASTM D97
- Boiling point/boiling range : 197-340°C (387-644°F)
Method: ASTM D 86
- Vapor pressure : 0.10 hPa
Method: ASTM D5191

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Relative density	: 0.831 at 16 °C (61 °F)
Density	: 0.831 g/cm3 Method: ASTM D4052
Bulk density	: 6.94 L/G
Water solubility	: negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 2.6 cSt at 40°C (104°F) Method: ASTM D 445
Relative vapor density	: No data available
Evaporation rate	: No data available
Conductivity	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Thermal decomposition	: No data available
Hazardous decomposition products	: Carbon Dioxide Carbon oxides
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Acute oral toxicity

Diesel fuel, no. 2 : LD50: > 5,000 mg/kg
Species: Rat
Sex: male and female
Method: OECD Test Guideline 401

Naphthalene : LD50: 500 mg/kg
Method: Converted acute toxicity point estimate

TrusTec™ Diesel Cetane, Check Fuel, High

Acute inhalation toxicity : Acute toxicity estimate: 4.56 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute toxicity estimate: 4.56 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

TrusTec™ Diesel Cetane, Check Fuel, High

Acute dermal toxicity : Acute toxicity estimate: 2,778 mg/kg
Method: Calculation method

TrusTec™ Diesel Cetane, Check Fuel, High

Skin irritation : May cause skin irritation in susceptible persons.

TrusTec™ Diesel Cetane, Check Fuel, High

Eye irritation : Vapors may cause irritation to the eyes, respiratory system and the skin.

TrusTec™ Diesel Cetane, Check Fuel, High

Sensitization : Did not cause sensitization on laboratory animals.

Repeated dose toxicity

Diesel fuel, no. 2 : Species: Rat, Male and female
Sex: Male and female
Application Route: Dermal
Dose: 0, 30, 125, 500 mg/kg
Exposure time: 13 wks
Number of exposures: daily, 5 days/week
NOEL: 30 mg/kg
Method: OECD Guideline 411
Target Organs: Thymus, Liver, Bone marrow
Information given is based on data obtained from similar substances.

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Species: Rat, Male and female
 Sex: Male and female
 Application Route: inhalation (dust/mist/fume)
 Dose: 0, 0.35, 0.88, 1.71 mg/l
 Exposure time: 13 wks
 Number of exposures: Twice/wk
 NOEL: > 1.71 mg/l
 Method: OECD Guideline 413

Genotoxicity in vitro

Diesel fuel, no. 2 : Test Type: Ames test
 Result: positive

Test Type: Mouse lymphoma assay
 Result: negative

Naphthalene : Test Type: Ames test
 Result: negative

Test Type: Sister Chromatid Exchange Assay
 Result: negative

Test Type: Unscheduled DNA synthesis assay
 Result: negative

Genotoxicity in vivo

Diesel fuel, no. 2 : Test Type: Dominant lethal assay
 Species: Mouse
 Dose: 100 or 400 ppm
 Result: negative

Naphthalene : Test Type: Mouse micronucleus assay
 Result: negative

Carcinogenicity

Diesel fuel, no. 2 : Species: Mouse
 Sex: male
 Dose: 0, 25 ul
 Exposure time: lifetime
 Number of exposures: 3 times/wk
 Remarks: Moderate dermal carcinogen

Naphthalene : Species: Mouse
 Sex: male
 Dose: 10, 30 ppm
 Exposure time: 105 weeks
 Number of exposures: 6 hours/day, 5 days/week
 Test substance: yes
 Print Date: No information available.
 Remarks: No evidence of carcinogenicity

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Species: Mouse
 Sex: female
 Dose: 10, 30 ppm
 Exposure time: 105 weeks
 Number of exposures: 6 hours/day, 5 days/week
 Test substance: yes
 Print Date: No information available.
 Remarks: increased incidence of alveolar/bronchiolar adenomas

Species: Rat
 Sex: male and female
 Dose: 10, 30, 60 ppm
 Exposure time: 105 weeks
 Number of exposures: 6 hours/day, 5 days/week
 Test substance: yes
 Print Date: No information available.
 Remarks: nose respiratory epithelial adenoma, increased incidence of olfactory neuroblastomas

Developmental Toxicity

Diesel fuel, no. 2

: Species: Rat
 Application Route: Inhalation
 Dose: 0, 86.9, 408.8 ppm
 Number of exposures: 6 h/d
 Test period: GD 6-15
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 408.8 ppm
 NOAEL Maternal: 408.8 ppm
 Information given is based on data obtained from similar substances.

Species: Rat
 Application Route: Dermal
 Dose: 30, 125, 500, 1000 mg/kg
 Exposure time: daily
 Test period: GD 0-20
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 125 mg/kg
 Information given is based on data obtained from similar substances.

Naphthalene

Species: Rabbit
 Application Route: oral gavage
 Dose: 40, 200, 400 mg/kg
 Test period: 29 d, GD 6-18
 NOAEL Teratogenicity: 400 mg/kg

TrusTec™ Diesel Cetane, Check Fuel, High

Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

Diesel fuel, no. 2 : Carcinogenicity: Limited evidence of carcinogenicity in animal studies
 Teratogenicity: Animal testing did not show any effects on fetal development.

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Naphthalene

Carcinogenicity: Limited evidence of carcinogenicity in animal studies

TrusTec™ Diesel Cetane, Check Fuel, High**Further information**

: Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

Diesel fuel, no. 2 : LL50: 21 mg/l
 Exposure time: 96 h
 Species: Oncorhynchus mykiss (rainbow trout)
 semi-static test Method: OECD Test Guideline 203

Naphthalene LC50: 3.2 mg/l
 Exposure time: 96 h
 Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates

Diesel fuel, no. 2 : EC50: 2 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 Method: OECD Test Guideline 202

Naphthalene LC50: 2.16 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)

Toxicity to algae

Diesel fuel, no. 2 : ErL50: 22 mg/l
 Exposure time: 72 h
 Species: Raphidocellus subcapitata (algae)
 static test Analytical monitoring: no
 Method: OECD Test Guideline 201

Naphthalene EC50: 2.96 mg/l
 Exposure time: 48 h
 Species: Selenastrum capricornutum (algae)

Biodegradability

Diesel fuel, no. 2 : aerobic
 Result: Not readily biodegradable.
 57.5 %
 Testing period: 28 d
 Method: OECD Test Guideline 301F

Bioaccumulation

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

Diesel fuel, no. 2	: Accumulation in aquatic organisms is expected.
Mobility	
Diesel fuel, no. 2	: No data available
Results of PBT assessment Diesel fuel, no. 2	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information Ecotoxicology Assessment	: Toxic to aquatic life with long lasting effects.
Short-term (acute) aquatic hazard	: Toxic to aquatic life.
Long-term (chronic) aquatic hazard	: Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1202, DIESEL FUEL, COMBUSTIBLE LIQUID, III

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIESEL FUEL), 9, III, (80.8 °C c.c.), MARINE POLLUTANT, (DIESEL FUEL)

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIESEL FUEL), 9, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1202, DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

30, UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Acute toxicity (any route of exposure)
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)
 Aspiration hazard
 Skin corrosion or irritation

CERCLA Reportable Quantity : 10000 lbs
 Naphthalene

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:

: Naphthalene - 91-20-3

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

: Naphthalene - 91-20-3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations**Pennsylvania Right To Know**

: Diesel fuel, no. 2 - 68476-34-6
Naphthalene - 91-20-3
Xylenes - 1330-20-7
Ethylbenzene - 100-41-4
Toluene - 108-88-3

California Prop. 65 Components

: WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov/food.

Naphthalene	91-20-3
Benzene	71-43-2

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Toluene	108-88-3
Benzene	71-43-2

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4


Revision Date 2024-02-05

Notification status

Europe REACH	:	This product is in full compliance according to REACH regulation 1907/2006/EC.
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AIIC	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	All substances in this product were registered, notified to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of Record themselves notified the substances.
Philippines PICCS	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : CPC00523

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic	NIOSH	National Institute for Occupational

TrusTec™ Diesel Cetane, Check Fuel, High

Version 3.4

Revision Date 2024-02-05

	Substances List		Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate