Chevron Phillips Chemical Company LP P.O. Box 4910 The Woodlands, TX 77387-4910 800.231.3260



AlphaPlus® 1-Hexadecene Sales Specifications

Characteristics	Method	Units	Target	Minimum	Maximum	Note
Less than C ₁₄	GLC	Wt %			0.10	
C ₁₄	GLC	Wt %			1.00	
C ₁₆	GLC	Wt %		97.5		
C ₁₈	GLC	Wt %			2.00	
Greater than C ₁₈	GLC	Wt %			0.10	
n-Alpha Olefin	GLC	Wt %		92.2		
Vinylidene	GLC	Wt %			6.5	
cis- and trans- 2-Hexadecene	GLC	Wt %			0.34	
Paraffin	GLC	Wt %			0.34	
Water	ASTM E1064	PPM by Wt			100	
Color	ASTM D6045	Saybolt		30		
Appearance	ASTM D4176			Clear and Bright		
API Gravity @ 60°F	ASTM D4052					note 1
Specific Gravity @ 60°F/60°F	ASTM D4052					note 1

1. Run and record

MSDS #10000065709

Revision Date July 2010



The Woodlands, Texas

ical Company

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. Chevron Phillips Chemical Company LP does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.