

Version 2.3 Revision Date 2023-10-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : Scentinel® F-20 Gas Odorant

Material : 1128539, 1124095, 1124110, 1121154, 1087135, 1024692,

1024694, 1024693, 1024690, 1024691, 1024789, 1105015

Use : Odorant

Company : Chevron Phillips Chemical Company LP

Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week) Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

SDS Number:100000013404 1/19

Version 2.3 Revision Date 2023-10-11

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371

67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24

hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

ODOR-FADE WARNING

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

- Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.
- · Contact with soil in underground leaks may de-odorize or remove odorant from the gas.
- Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
- The stench of odorized gas may not awaken sleeping persons.
- · Other odors may mask or hide the stench.
- Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

SDS Number:100000013404 2/19

Version 2.3 Revision Date 2023-10-11

Classification

Flammable liquids, Category 2 Eye irritation, Category 2B Skin sensitization, Category 1

Labeling

Symbol(s)





Signal Word : Danger

Hazard Statements : H225: Highly flammable liquid and vapor.

H317: May cause an allergic skin reaction.

H320: Causes eye irritation.

Precautionary Statements :

: Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot

surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Potential Health Effects

Symptoms of Overexposure : No data available

SDS Number:100000013404 3/19

Version 2.3 Revision Date 2023-10-11

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3: Composition/information on ingredients

Synonyms : Gas Odorant

Mercaptan Mixture

Molecular formula : Mixture

Component	CAS-No.	Weight %
t-Butyl Mercaptan	75-66-1	78 - 82
Dimethyl Sulfide	75-18-3	18 - 22

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : If unconscious, place in recovery position and seek medical

advice. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

Notes to physician

Symptoms : No data available.

Risks : No data available.

Treatment : No data available.

SECTION 5: Firefighting measures

Flash point : <-18°C (<0°F)

estimated

Autoignition temperature : No data available

SDS Number:100000013404 4/19

Scentinel® F-20 Gas Odorant

Version 2.3 Revision Date 2023-10-11

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed

containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only

explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Hazardous decomposition

products

: Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate

> ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

: Prevent product from entering drains. Prevent further leakage Environmental precautions

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

For additional details, see the Exposure Scenario in the Annex portion

SECTION 7: Handling and storage

Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

> exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against

SDS Number:100000013404 5/19

Version 2.3 Revision Date 2023-10-11

static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Control parameters

Note

Use : Odorant

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

Chevron Phillips Chemical Company LP
Components B

t-Butyl Mercaptan	Manufacturer	TWA	0.5 ppm,	
us				
Components	Basis	Value	Control parameters	Note
Dimethyl Sulfide	ACGIH	TWA	10 ppm	

Value

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection

If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

SDS Number:100000013404 6/19

Version 2.3 Revision Date 2023-10-11

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Remove and wash contaminated clothing before re-use. Skin should be washed

after contact. Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

For additional details, see the Exposure Scenario in the Annex portion

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Form : liquid
Physical state : liquid
Color : Clear
Odor : Repulsive

Safety data

Flash point : $<-18^{\circ}\text{C}$ ($<0^{\circ}\text{F}$)

estimated

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : No

Autoignition temperature : No data available

Molecular formula : Mixture

Molecular weight : Not applicable

pH : Not applicable

Pour point : No data available

Freezing point -45.6°C (-50.1°F)

SDS Number:100000013404 7/19

Version 2.3 Revision Date 2023-10-11

Boiling point/boiling range : 48.9-93.3°C (120.0-199.9°F)

Vapor pressure : 8.20 PSI

> at 38°C (100°F) estimated

Relative density : 0.816

at 15.6 °C (60.1 °F)

Density : 813.6 g/l

Water solubility : negligible

Partition coefficient: n-

octanol/water

: No data available

: 0.4 cSt Viscosity, kinematic

at 40°C (104°F)

Relative vapor density : 2

(Air = 1.0)

Evaporation rate : No data available

: > 99 % Percent volatile

Conductivity : No data available

SECTION 10: Stability and reactivity

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Hazardous reactions : Hazardous reactions: Hazardous polymerization does not

occur.

Hazardous reactions: Vapors may form explosive mixture with

air.

Conditions to avoid

Hazardous decomposition

products

: Heat, flames and sparks.

: Carbon oxides Sulfur oxides

Other data : No decomposition if stored and applied as directed.

SDS Number:100000013404 8/19

Scentinel® F-20 Gas Odorant

Version 2.3 Revision Date 2023-10-11

SECTION 11: Toxicological information

Scentinel® F-20 Gas Odorant

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Scentinel® F-20 Gas Odorant

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Scentinel® F-20 Gas Odorant

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Scentinel® F-20 Gas Odorant

Skin irritation : May cause skin irritation and/or dermatitis.

Scentinel® F-20 Gas Odorant

Eye irritation: Vapors may cause irritation to the eyes, respiratory system

and the skin.

Scentinel® F-20 Gas Odorant

Sensitization: Causes sensitization. largely based on animal evidence.

Repeated dose toxicity

t-Butyl Mercaptan : Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 9, 97, 196 ppm Exposure time: 13 wks

Number of exposures: 6 hrs/d, 5 d/wk

9/19

NOEL: > 196 ppm

SDS Number:100000013404

Version 2.3 Revision Date 2023-10-11

Species: Rat, Male and female

Sex: Male and female

Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Exposure time: 42-53 days Number of exposures: Daily NOEL: 50 mg/kg bw/day

Lowest observable effect level: 200 mg/kg bw/day

Method: OECD Guideline 422

Species: Rat, Male and female

Sex: Male and female

Application Route: Inhalation Dose: 25.1, 99.6, 403.4 ppm Exposure time: 13 wks

Number of exposures: 6 hrs/d, 5 d/wk

NOEL: 99.6 ppm

Lowest observable effect level: 403.4 ppm

Method: OECD Guideline 413

Target Organs: Liver, Kidney, Blood, Upper respiratory tract Information given is based on data obtained from similar

substances.

Dimethyl Sulfide Species: Rat, Male and female

Sex: Male and female Application Route: Oral diet

Dose: 0, 2.5, 25, 250 mg/kg bw/day

Exposure time: 14 wk Number of exposures: daily

NOEL: 250 mg/kg

Method: OECD Test Guideline 408 No adverse effects expected

Genotoxicity in vitro

SDS Number:100000013404 10/19

Version 2.3 Revision Date 2023-10-11

t-Butyl Mercaptan : Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mouse lymphoma assay

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Sister Chromatid Exchange Assay

Metabolic activation: with and without metabolic activation

Result: negative

Dimethyl Sulfide Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mouse lymphoma assay

Metabolic activation: with and without metabolic activation

Method: OECD Guideline 476

Result: negative

Genotoxicity in vivo

t-Butyl Mercaptan : Test Type: Mouse micronucleus assay

Species: Mouse

Dose: 1250, 2500, 5000 mg/kg Method: OECD Test Guideline 474

Result: negative

Dimethyl Sulfide Test Type: In vivo micronucleus test

Species: Mouse

Cell type: Bone marrow Route of Application: Oral Dose: 1250, 2500, 5000 mg/kg Method: OECD Test Guideline 474

Result: negative

Reproductive toxicity

t-Butyl Mercaptan : Species: Rat

Sex: male and female

Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Number of exposures: Daily Test period: 42 -53 days Method: OECD Guideline 422 NOAEL Parent: 200 mg/kg bw/day NOAEL F1: 50 mg/kg bw/day No adverse effects expected

Developmental Toxicity

t-Butyl Mercaptan : Species: Mouse

Application Route: Inhalation Dose: 11, 99, 195 ppm

SDS Number:100000013404 11/19

Version 2.3 Revision Date 2023-10-11

Exposure time: GD 6-16 Number of exposures: 6 hrs/d NOAEL Teratogenicity: > = 195 ppm NOAEL Maternal: > = 195 ppm

Species: Rat

Application Route: Inhalation
Dose: 11, 99, 195 ppm
Exposure time: GD6-19
Number of exposures: 6 hrs/d
NOAEL Teratogenicity: > =195 ppm
NOAEL Maternal: > = 195 ppm

Species: Rat

Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Exposure time: 42-53 days Number of exposures: Daily

NOAEL Teratogenicity: 50 mg/kg bw /day NOAEL Maternal: 200 mg/kg bw /day

Dimethyl Sulfide Species: Rat

Application Route: oral gavage Dose: 100, 500, 1000 mg/kg Exposure time: GD 6 - 19 Number of exposures: daily

Test period: 20 d

Method: OECD Guideline 414 NOAEL Teratogenicity: 1,000 mg/kg NOAEL Maternal: 1,000 mg/kg

Scentinel® F-20 Gas Odorant

Aspiration toxicity : May be harmful if swallowed and enters airways.

CMR effects

t-Butyl Mercaptan : Carcinogenicity: Not available

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show

mutagenic effects

Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on

animal experiments.

Dimethyl Sulfide Carcinogenicity: Not available

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show

mutagenic effects

Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on

animal experiments.

Scentinel® F-20 Gas Odorant

Further information : Solvents may degrease the skin.

SECTION 12: Ecological information

SDS Number:100000013404 12/19

Version 2.3 Revision Date 2023-10-11

Toxicity to fish

t-Butyl Mercaptan : LC50: 34 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203

Dimethyl Sulfide LC50: 213 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

t-Butyl Mercaptan : EC50: 6.7 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Dimethyl Sulfide EC50: 29 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Toxicity to algae

t-Butyl Mercaptan : EC50: 24 mg/l

Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae)

Method: OECD Test Guideline 201

Dimethyl Sulfide IC50: > 113.7 mg/l

Exposure time: 72 h

Species: Selenastrum capricornutum (algae)

Method: OECD Test Guideline 201

Biodegradability

t-Butyl Mercaptan : aerobic

Result: Not readily biodegradable.

6 %

Testing period: 63 d

Method: OECD Test Guideline 301

Dimethyl Sulfide : aerobic

Result: Readily biodegradable.

77 %

Method: OECD Test Guideline 301

Bioaccumulation

t-Butyl Mercaptan : Bioconcentration factor (BCF): 12

Method: QSAR modeled data

This material is not expected to bioaccumulate.

SDS Number:100000013404 13/19

Version 2.3 Revision Date 2023-10-11

Dimethyl Sulfide : No bioaccumulation is to be expected (log Pow <= 4).

Mobility

t-Butyl Mercaptan : Method: Calculation, Mackay Level III Fugacity Model

The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

Dimethyl Sulfide : Method: Calculation, Mackay Level III Fugacity Model

The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

Results of PBT assessment

t-Butyl Mercaptan : Non-classified PBT substance, Non-classified vPvB substance

Dimethyl Sulfide : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological

information

: Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard

t-Butyl Mercaptan : Toxic to aquatic life.

Dimethyl Sulfide : Harmful to aquatic life.

Long-term (chronic) aquatic hazard

t-Butyl Mercaptan : Toxic to aquatic life with long lasting effects.

Dimethyl Sulfide : This material is not expected to be harmful to aquatic

organisms.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

For additional details, see the Exposure Scenario in the Annex portion

SDS Number:100000013404 14/19

Version 2.3 Revision Date 2023-10-11

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, (< -18 °C c.c.), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33,UN3336,MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, DIMETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

National legislation

SDS Number:100000013404 15/19

Scentinel® F-20 Gas Odorant

Version 2.3 Revision Date 2023-10-11

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

> Respiratory or skin sensitization Serious eye damage or eye irritation

CERCLA Reportable

Quantity

: Calculated RQ exceeds reasonably attainable upper limit.

Carbon disulfide

SARA 302 Reportable

Quantity

: Calculated RQ exceeds reasonably attainable upper limit.

Carbon disulfide

SARA 302 Threshold

Planning Quantity

: This material does not contain any components with a section

302 EHS TPQ.

SARA 304 Reportable

Quantity

: Calculated RQ exceeds reasonably attainable upper limit.

Carbon disulfide 75-15-0 100 lbs

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

: Dimethyl Sulfide - 75-18-3

US State Regulations

SDS Number:100000013404 16/19

Version 2.3 Revision Date 2023-10-11

Pennsylvania Right To Know

t-Butyl Mercaptan - 75-66-1
 Dimethyl Sulfide - 75-18-3
 Carbon disulfide - 75-15-0
 Methyl Mercaptan - 74-93-1
 Dimethyl Disulfide - 624-92-0

California Prop. 65 Components : WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to

cause cancer. For more information go to

www.P65Warnings.ca.gov/food.

Benzene 71-43-2

WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Carbon disulfide 75-15-0
Toluene 108-88-3
Benzene 71-43-2

Notification status

Philippines PICCS

Europe REACH : This product is in full compliance according to REACH

regulation 1907/2006/EC.

Switzerland CH INV

United States of America (USA)

TSCA

Canada DSL : All components of this product are on the Canadian

TSCA inventory

DSL

Australia AIIC : On the inventory, or in compliance with the inventory Japan ENCS : On the inventory, or in compliance with the inventory New Zealand NZIoC : On the inventory, or in compliance with the inventory

Korea KECI : A substance(s) in this product was not registered,

notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).

On the inventory, or in compliance with the inventory

On the inventory, or in compliance with the inventory

On or in compliance with the active portion of the

quantity of the non-registered substance(s).

Taiwan TCSI : On the inventory, or in compliance with the inventory China IECSC : On the inventory, or in compliance with the inventory


SDS Number:100000013404 17/19

Version 2.3 Revision Date 2023-10-11

SECTION 16: Other information

NFPA Classification : Health Hazard: 2

Fire Hazard: 3 Reactivity Hazard: 0



Further information

Legacy SDS Number : 34930

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet				
ACGIH	American Conference of	LD50	Lethal Dose 50%	
	Government Industrial Hygienists			
AIIC	Australian Inventory of Industrial	LOAEL	Lowest Observed Adverse Effect	
	Chemicals		Level	
DSL	Canada, Domestic Substances	NFPA	National Fire Protection Agency	
	List			
NDSL	Canada, Non-Domestic	NIOSH	National Institute for Occupational	
	Substances List		Safety & Health	
CNS	Central Nervous System	NTP	National Toxicology Program	
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of	
			Chemicals	
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect	
			Level	
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration	
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health	
	Scenario Tool		Administration	
EOSCA	European Oilfield Specialty	PEL	Permissible Exposure Limit	
	Chemicals Association		·	
EINECS	European Inventory of Existing	PICCS	Philippines Inventory of	
	Chemical Substances		Commercial Chemical Substances	
MAK	Germany Maximum Concentration	PRNT	Presumed Not Toxic	
	Values			
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery	
	-		Act	
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit	
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and	
			Reauthorization Act.	
IARC	International Agency for Research	TLV	Threshold Limit Value	
	on Cancer			
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average	
	Substances in China			
ENCS	Japan, Inventory of Existing and	TSCA	Toxic Substance Control Act	

SDS Number:100000013404 18/19

Scentinel® F-20 Gas Odorant

Version 2.3 Revision Date 2023-10-11

	New Chemical Substances		
KECI	Korea, Existing Chemical	UVCB	Unknown or Variable Composition,
	Inventory		Complex Reaction Products, and
			Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials
			Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

SDS Number:100000013404 19/19