

SCENTINEL® S-20 Gas Odorant

Version 2.3

ECTION 1: Identification of the substance/mixture and of the company/undertaking		
Product information		
Product Name Material	 SCENTINEL® S-20 Gas Odorant 1096889, 1098465, 1024714, 1024715, 1024716, 1024722, 1024719, 1024718, 1024717, 1024713, 1024721, 1033064, 1024720 	
Use	: Odorant	
Company	 Chevron Phillips Chemical Company LP Specialty Chemicals 10001 Six Pines Drive The Woodlands, TX 77380 	
Emergency telephone:		
Mexico CHEMTREC 01-80 South America SOS-Cotec Argentina: +(54)-11598394 EUROPE: BIG +32.14.584 Austria: VIZ +43 1 406 43 Belgium: 070 245 245 (24 Bulgaria: +359 2 9154 233 Croatia: +3851 2348 342 (Cyprus: 1401 Czech Republic: Toxicolog Denmark: Danish Poison 0	nal) 0 or 703.527.3887(int'l) 2 9186 1132) China: 0532 8388 9090 00-681-9531 (24 hours) c Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600 431 545 (phone) or +32.14583516 (telefax) 43 (24 hours/day, 7 days/week) hours/day, 7 days/week) 24 hours/day, 7 days/week) jical Information Center +420 224 919 293, +420 224 915 402 Center (Giftlinjen): +45 8212 1212	
Finland: 0800 147 111 09 France: ORFILA number (Germany: BIG +32.14.584 Greece: (0030) 210779375 Hungary: +36-80-201-199 Iceland: 543 2222 (24 hou Ireland: BIG +32.14.58454	NRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week) 545 (phone) or +32.14583516 (telefax) 77 (24 hours/day, 7 days/week) (24 hours/day, 7 days/week)	
SDS Number:100000013388	1/17	

SCENTINEL® S-20 Gas Odorant

Version 2.3

Revision Date 2023-10-17

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.) Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Lithuania: +370 (85) 2362052 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week) Malta: +356 2395 2000 The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week) Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Portugal: CIAV phone number: +351 800 250 250 Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week) Sweden: 112 - ask for Poisons Information : Product Safety and Toxicology Group Responsible Department E-mail address : SDS@CPChem.com

ODOR-FADE WARNING

Website

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

www.CPChem.com

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

• Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.

· Contact with soil in underground leaks may de-odorize or remove odorant from the gas.

Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
The stench of odorized gas may not awaken sleeping persons.

• Other odors may mask or hide the stench.

• Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

SDS Number:100000013388

Version 2.3

Classification	: Flammable liquids, Category 2 Eye irritation, Category 2A Skin sensitization, Category 1
Labeling	
Symbol(s)	
Signal Word	: Danger
Hazard Statements	 H225: Highly flammable liquid and vapor. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.
Precautionary Statements	 Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Storage: P403 + P235 Store in a well-ventilated place. Keep cool. Disposal plant.
Carcinogenicity: IARC	No ingredient of this product present at levels greater than or
	equal to 0.1% is identified as probable, possible or confirmed

ENTINEL® S-20 Gas	s Odorant	SAFETY DATA SH		
sion 2.3		Revision Date 2023-1		
NTP	human carcinogen by IARC. No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.			
TION 3: Composition/inform	nation on ingredients			
Synonyms	: Gas Odorant Mixture of t-butyl mercapt Mercaptan Mixture	Mixture of t-butyl mercaptan and methy ethyl sulfide		
Molecular formula	: Mixture			
Component	CAS-No.	Weight %		
t-Butyl Mercaptan	75-66-1	76 - 80		
Methyl Ethyl Sulfide	624-89-5	20 - 24		
TION 4: First aid measures				
General advice	sheet to the doctor in atte	Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.		
If inhaled		If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.		
In case of skin contact		If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.		
In case of eye contact	lenses. Protect unharmed	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.		
If swallowed		ar. Never give anything by mouth to f symptoms persist, call a physician. o hospital.		
TION 5: Firefighting measu	res			
Flash point	: <-18°C (<0°F) estimated			
Autoignition temperature	: No data available			
Suitable extinguishing media	: Alcohol-resistant foam. C	Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.		
Unsuitable extinguishing media	: High volume water jet.	High volume water jet.		
Coopific homordo during fire	: Do not allow run-off from	(in fighting to option during an exception		
Specific hazards during fire fighting	courses.	fire fighting to enter drains or water		

SAFETY DATA SH as Odorant
Revision Date 2023-
: Wear self-contained breathing apparatus for firefighting if necessary.
: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, ho surfaces and sources of ignition.
: Carbon oxides. Sulfur oxides.
e measures
: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
rage
: Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, ho

	• •		SAF	ETY DATA SHEE
CENTINEL® S-20 Ga	s Odora	nt		
ersion 2.3			Revisio	on Date 2023-10-1
	surface	es and sources o	of ignition.	
Storage				
Requirements for storage areas and containers	ventilat careful Observ	ted place. Contail ly resealed and re label precauti	ntainer tightly closed in a ainers which are opened kept upright to prevent le ons. Electrical installation with the technological sa	must be akage. ns / working
Use	: Odorar	nt		
ECTION 8: Exposure controls	/personal p	rotection		
Ingredients with workplace	e control pa	rameters		
nevron Phillips Chemical Company L	-	rameters		
evron Phillips Chemical Company L	.P Basis	Value	Control parameters	Note
evron Phillips Chemical Company L Components Butyl Mercaptan	.P		Control parameters 0.5 ppm,	Note
evron Phillips Chemical Company L Components Butyl Mercaptan	.P Basis	Value		Note Note
Ingredients with workplace hevron Phillips Chemical Company L Components -Butyl Mercaptan S Components Engineering measures	P Basis Manufacturer	Value TWA	0.5 ppm,	

Personal protective equipment

Respiratory protection	: If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
Hand protection	: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Tightly fitting safety goggles.
SDS Number:100000013388	6/17

ENTINEL® S-20 Ga	SAFETY DATA S	SH
sion 2.3	Revision Date 2023	2 1
Skin and body protection	 Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to specific work-place. Wear as appropriate:. Remove and wa contaminated clothing before re-use. Skin should be washe after contact. Footwear protecting against chemicals. 	the ish
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	
TION 9: Physical and cher	nical properties	
Information on basic phy	sical and chemical properties	
Appearance		
Form Physical state Color	: liquid : liquid : Clear	
Odor Odor Threshold	: Repulsive : No data available	
Safety data		
Flash point	: <-18°C (<0°F) estimated	
Lower explosion limit	: Not applicable	
Upper explosion limit	: Not applicable	
Oxidizing properties	: no	
Autoignition temperature	: No data available	
Thermal decomposition	: No data available	
Molecular formula	: Mixture	
Molecular weight	: Not applicable	
рН	: Not applicable	
Pour point	: <-54°C (<-65°F)	
Boiling point/boiling range	: 63-68°C (145-154°F)	
Vapor pressure	: 5.70 PSI at 38°C (100°F)	
Relative density	: 0.813 at 16 °C (61 °F)	
Density	: 6.78 L/G	
Water solubility	: slightly soluble	

ENTINEL® S-20 Gas	SAFETY DATA SH
sion 2.3	Revision Date 2023-1
Partition coefficient: n-	: No data available
octanol/water Viscosity, dynamic	: 0.5 cP
	at 16°C (60°F)
Relative vapor density	: 3
	(Air = 1.0)
Evaporation rate	: 1
Percent volatile	: >99 %
CTION 10: Stability and reactiv	vity
Reactivity	: Stable at normal ambient temperature and pressure.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous rea	ctions
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.
	Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Thermal decomposition	: No data available
Hazardous decomposition products	: Carbon oxides Sulfur oxides
Other data	: No decomposition if stored and applied as directed.
CTION 11: Toxicological inform	nation
SCENTINEL® S-20 Gas Odo	rant
Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
SCENTINEL® S-20 Gas Odo Acute inhalation toxicity	rant : Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
S Number:100000013388	8/17
5 Nullibel, 100000015500	0/17

SCENTINEL® S-20 Gas Odorant

Version 2.3

SCENTINEL® S-20 Gas C Acute dermal toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
SCENTINEL® S-20 Gas C Skin irritation	Ddorant : May cause skin irritation and/or dermatitis.
SCENTINEL® S-20 Gas C Eye irritation	Ddorant : Eye irritation largely based on animal evidence.
SCENTINEL® S-20 Gas C Sensitization	Odorant : Causes sensitization. largely based on animal evidence.
Repeated dose toxicity	
t-Butyl Mercaptan	 Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 9, 97, 196 ppm Exposure time: 13 wks Number of exposures: 6 hrs/d, 5 d/wk NOEL: > 196 ppm
	Species: Rat, Male and female Sex: Male and female Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Exposure time: 42-53 days Number of exposures: Daily NOEL: 50 mg/kg bw/day Lowest observable effect level: 200 mg/kg bw/day Method: OECD Guideline 422
	Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 25.1, 99.6, 403.4 ppm Exposure time: 13 wks Number of exposures: 6 hrs/d, 5 d/wk NOEL: 99.6 ppm Lowest observable effect level: 403.4 ppm Method: OECD Guideline 413 Target Organs: Liver, Kidney, Blood, Upper respiratory tract Information given is based on data obtained from similar substances.
Genotoxicity in vitro	
t-Butyl Mercaptan	: Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative

Version 2.3	Revision Date 2023-10-17
	Test Type: Mouse lymphoma assay Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative
	Test Type: Sister Chromatid Exchange Assay Metabolic activation: with and without metabolic activation Result: negative
Methyl Ethyl Sulfide	Test Type: Ames test Method: OECD Test Guideline 471 Result: negative
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Genotoxicity in vivo	
t-Butyl Mercaptan	: Test Type: Mouse micronucleus assay Species: Mouse Dose: 1250, 2500, 5000 mg/kg Method: OECD Test Guideline 474 Result: negative
Reproductive toxicity	
t-Butyl Mercaptan	: Species: Rat Sex: male and female Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Number of exposures: Daily Test period: 42 -53 days Method: OECD Guideline 422 NOAEL Parent: 200 mg/kg bw/day NOAEL F1: 50 mg/kg bw/day No adverse effects expected
Developmental Toxicity	
t-Butyl Mercaptan	: Species: Mouse Application Route: Inhalation Dose: 11, 99, 195 ppm Exposure time: GD 6-16 Number of exposures: 6 hrs/d NOAEL Teratogenicity: > = 195 ppm NOAEL Maternal: > = 195 ppm
SDS Number:100000013388	10/17

SCENTINEL® S-20 Gas Odorant

/ersion 2.3	
C131011 2.5	Revision Date 2023-10-1
	Species: Rat Application Route: Inhalation Dose: 11, 99, 195 ppm Exposure time: GD6-19 Number of exposures: 6 hrs/d NOAEL Teratogenicity: > =195 ppm NOAEL Maternal: > = 195 ppm
	Species: Rat Application Route: oral gavage Dose: 10, 50, 200 mg/kg bw/day Exposure time: 42-53 days Number of exposures: Daily NOAEL Teratogenicity: 50 mg/kg bw /day NOAEL Maternal: 200 mg/kg bw /day
SCENTINEL® S-20 Gas O Aspiration toxicity	Odorant : May be harmful if swallowed and enters airways.
CMR effects	
t-Butyl Mercaptan	 Carcinogenicity: Not available Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.
SCENTINEL® S-20 Gas O	dorant
Further information ECTION 12: Ecological infor	: Solvents may degrease the skin.
	: Solvents may degrease the skin.
	: Solvents may degrease the skin.
ECTION 12: Ecological infor	: Solvents may degrease the skin.
ECTION 12: Ecological infor Toxicity to fish	 Solvents may degrease the skin. mation LC50: 34 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout)
ECTION 12: Ecological infor Toxicity to fish t-Butyl Mercaptan Methyl Ethyl Sulfide	 Solvents may degrease the skin. mation LC50: 34 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 LC50: > 49.8 mg/l Exposure time: 96 h
ECTION 12: Ecological infor Toxicity to fish t-Butyl Mercaptan Methyl Ethyl Sulfide	: Solvents may degrease the skin. mation : LC50: 34 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 LC50: > 49.8 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
ECTION 12: Ecological infor Toxicity to fish t-Butyl Mercaptan Methyl Ethyl Sulfide Toxicity to daphnia and c	 Solvents may degrease the skin. mation : LC50: 34 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 LC50: > 49.8 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 other aquatic invertebrates : EC50: 6.7 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)

ENTINEL® S-20 Ga	
sion 2.3	Revision Date 2023-10-
	Method: OECD Test Guideline 202
Toxicity to algae	
t-Butyl Mercaptan	: EC50: 24 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (green algae) Method: OECD Test Guideline 201
Methyl Ethyl Sulfide	ErC50: > 500 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (green algae) Method: OECD Test Guideline 201
	EbC50: 310 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (green algae) Method: OECD Test Guideline 201
Toxicity to bacteria	
Methyl Ethyl Sulfide	: EC50: > 1,000 mg/l Exposure time: 3 h Species: Bacteria Respiration inhibition Method: OECD Test Guideline 209
Biodegradability	
t-Butyl Mercaptan	 aerobic Result: Not readily biodegradable. 6 % Testing period: 63 d Method: OECD Test Guideline 301
Methyl Ethyl Sulfide	: aerobic 41 % Testing period: 28 d Method: OECD Test Guideline 301D According to the results of tests of biodegradability this product is not readily biodegradable.
	: aerobic 92 % Testing period: 31 d Method: OECD Test Guideline 301D Expected to be inherently biodegradable.
Bioaccumulation	
t-Butyl Mercaptan	: Bioconcentration factor (BCF): 12 Method: QSAR modeled data This material is not expected to bioaccumulate.
Methyl Ethyl Sulfide	: This material is not expected to bioaccumulate.

SAFETY DATA SHEET

Version 2.3

Revision Date 2023-10-17

Mc	hi	litv
1010		iicy

, see the second s	
t-Butyl Mercaptan	: Method: Calculation, Mackay Level III Fugacity Model The product will be dispersed amongst the various environmental compartments (soil/ water/ air).
Methyl Ethyl Sulfide	: The product evaporates readily.
Results of PBT assessment	
t-Butyl Mercaptan	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information Ecotoxicology Assessmen	: Toxic to aquatic life with long lasting effects.
Short-term (acute) aquatic h	azard
t-Butyl Mercaptan	: Toxic to aquatic life.
Methyl Ethyl Sulfide	: Harmful to aquatic life.
Long-term (chronic) aquatic	hazard
t-Butyl Mercaptan	: Toxic to aquatic life with long lasting effects.
Methyl Ethyl Sulfide	: Harmful to aquatic life with long lasting effects.
SECTION 13: Disposal conside	erations
The information in this SDS	pertains only to the product as shipped.
	purpose or recycle if possible. This material, if it must be discarded, azardous waste as defined by US EPA under RCRA (40 CFR 261) or

may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the

SDS Number:100000013388

SCENTINEL® S-20 Gas Odorant

Revision Date 2023-10-17

bill of lading.

Version 2.3

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION) UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II				
IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS) UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, (< -18 °C c.c.), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN)				
IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION) UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II				
ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE)) UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)				
RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE)) 33,UN3336,MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)				
ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS) UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)				
Maritime transport in bulk according to IMO instruments				
SECTION 15: Regulatory information				
National legislation				
SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids) Respiratory or skin sensitization Serious eye damage or eye irritation				
CERCLA Reportable : Calculated RQ exceeds reasonably attainable upper limit. Quantity Ethyl Chloride				
SDS Number:100000013388 14/17				

Version 2.3

SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.			
SARA 302 Threshold Planning Quantity	 This material does not contain any components with a section 302 EHS TPQ. 			
SARA 304 Reportable Quantity	This material does not contain any components with a section 304 EHS RQ.			
SARA 313 Components	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.			
Clean Air Act				
Ozone-Depletion : This product neither contains, nor was manufactured with a Class I or Potential : Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).				
This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).				
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).				
This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).				
US State Regulations				
Pennsylvania Right To Know	: t-Butyl Mercaptan - 75-66-1 Methyl Ethyl Sulfide - 624-89-5 Ethyl Chloride - 75-00-3			
SDS Number:100000013388	15/17			

SAFETY DATA SHEET SCENTINEL® S-20 Gas Odorant Version 2.3 Revision Date 2023-10-17 California Prop. 65 : WARNING! This product contains a chemical known in the Components State of California to cause cancer. Ethyl Chloride 75-00-3 **Notification status** Europe REACH A substance or substances in this product is not registered or notified to be registered. Importation or manufacture of this product is still permitted provided that it does not exceed the REACH minimum threshold quantity of the non-regulated substances. Switzerland CH INV Not in compliance with the inventory United States of America (USA) On or in compliance with the active portion of the **TSCA** inventory TSCA Canada DSL 2 All components of this product are on the Canadian DSL Australia AIIC On the inventory, or in compliance with the inventory : New Zealand NZIoC Not in compliance with the inventory 2 On the inventory, or in compliance with the inventory Japan ENCS 2 Korea KECI A substance(s) in this product was not registered, : notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s). Philippines PICCS On the inventory, or in compliance with the inventory Taiwan TCSI On the inventory, or in compliance with the inventory 1 China IECSC On the inventory, or in compliance with the inventory 5 **SECTION 16: Other information** NFPA Classification : Health Hazard: 2 Fire Hazard: 3 Reactivity Hazard: 0 2 0 **Further information** Legacy SDS Number : 34330 Significant changes since the last version are highlighted in the margin. This version replaces all previous versions. The information in this SDS pertains only to the product as shipped. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the SDS Number:100000013388 16/17

SCENTINEL® S-20 Gas Odorant

Version 2.3

Revision Date 2023-10-17

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

k	Key or legend to abbreviations and a	cronyms use	d in the safety data sheet
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

SDS Number:100000013388