

Version 3.6 Revision Date 2023-11-15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : CF Desco® II Deflocculant

Material: 1036678

Use : Drilling Mud Additive

Company : Chevron Phillips Chemical Company LP

Drilling Specialties Company LLC

10001 Six Pines Drive The Woodlands, TX 77380

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Italy: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371

67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

SDS Number:100000013722 1/14

Version 3.6 Revision Date 2023-11-15

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24

hours/day, 7 days/week)

Sweden: 112 - ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Combustible dust

Skin irritation, Category 2 Eye irritation, Category 2A Carcinogenicity, Category 1A

Labeling

Symbol(s)





Signal Word : Danger

Hazard Statements : May form combustible dust concentrations in air.

H315: Causes skin irritation. H319: Causes serious eye irritation.

H350: May cause cancer.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been

read and understood.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

2/14

and easy to do. Continue rinsing.

SDS Number:100000013722

Version 3.6 Revision Date 2023-11-15

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Potential Health Effects

Physical Hazards : Mechanical processing may form combustible dust

concentrations in air and thermal processing at elevated temperatures may generate simple hydrocarbons and carbon

oxides.

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

Crystalline Silica 14808-60-7

NTP Known to be human carcinogen

Crystalline Silica 14808-60-7

SECTION 3: Composition/information on ingredients

Synonyms : Drilling Mud Deflocculant

Molecular formula : Mixture

Component	CAS-No.	Weight %
Methyl ester of sulfonated tannin	Proprietary	40 - 55
Ferrous Sulfate	17375-41-6	5 - 9
Crystalline Silica	14808-60-7	0.1 - 0.4

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

SDS Number:100000013722 3/14

SAFETY DATA SHEET

CF Desco® II Deflocculant

Version 3.6 Revision Date 2023-11-15

If swallowed : Induce vomiting immediately and call a physician. Keep

respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to

hospital.

SECTION 5: Firefighting measures

Flash point : Not applicable

Autoignition temperature : No data available

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in

accordance with local regulations.

Fire and explosion

protection

: Avoid dust formation. Provide appropriate exhaust ventilation

at places where dust is formed.

Hazardous decomposition

products

: Sulfur oxides. Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Avoid dust formation.

Avoid breathing dust.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Advice on safe handling : Avoid formation of respirable particles. Do not breathe

vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in

accordance with local and national regulations.

SDS Number:100000013722 4/14

Version 3.6 Revision Date 2023-11-15

Advice on protection against fire and explosion

: Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Storage

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Drilling Mud Additive

SECTION 8: Exposure controls/personal protection

Ingredients with workplace control parameters

US

Components	Basis	Value	Control parameters	Note
Ferrous Sulfate	ACGIH	TWA	1 mg/m3	
	OSHA Z-1-A	TWA	1 mg/m3	
Crystalline Silica	OSHA Z-3	TWA	250mppcf / %SiO2+5	respirable
	OSHA Z-3	TWA	10mg/m3 / %SiO2+2	respirable
	OSHA Z-3	TWA	0.1 mg/m3	Respirable fraction
	OSHA Z-1-A	TWA	0.1 mg/m3	respirable dust fraction
	ACGIH	TWA	0.025 mg/m3	A2, Respirable particulate matter
	OSHA Z-1	TWA	0.05 mg/m3	Respirable fraction
	OSHA Z-1	TWA	0.05 mg/m3	(respirable dust)
	OSHA CARC	PEL	0.05 mg/m3	respirable

A2 Suspected human carcinogen

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Crystalline Silica	14808-60-7	Immediately Dangerous to Life or Health Concentration Value 50 mg/m³	1995-03-01

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection

: If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Dusts and Mists / P100. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not

SDS Number:100000013722 5/14

Version 3.6 Revision Date 2023-11-15

known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Safety glasses.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Protective suit.

Safety shoes.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Form : Powder Physical state : solid

Color : Fine reddish-brown with small white specks

Odor : Odorless
Odor Threshold : Not applicable

Safety data

Flash point : Not applicable

Lower explosion limit : Not applicable

Upper explosion limit : Not applicable

Oxidizing properties : No

Autoignition temperature : No data available

Thermal decomposition : No data available

Molecular formula : Mixture

Molecular weight : No data available

pH : Not applicable

Pour point : No data available

SDS Number:100000013722 6/14

SAFETY DATA SHEET

CF Desco® II Deflocculant

Version 3.6 Revision Date 2023-11-15

Boiling point/boiling range : Not applicable

Vapor pressure : Not applicable

Relative density : 1.5

Density : Not applicable

Water solubility : partly soluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, kinematic : Not applicable

Relative vapor density : Not applicable

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

Reactivity: Stable at normal ambient temperature and pressure.

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Hazardous reactions : Further information: No decomposition if stored and applied as

directed.

Conditions to avoid : No data available.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Thermal decomposition : No data available

Hazardous decomposition

products

: Sulfur oxides Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

CF Desco® II Deflocculant

Acute oral toxicity : Acute toxicity estimate: 2,900 mg/kg

Method: Calculation method

SDS Number:100000013722 7/14

Version 3.6 Revision Date 2023-11-15

Acute toxicity estimate: 2,900 mg/kg

Method: Calculation method

Acute dermal toxicity

Methyl ester of sulfonated

tannin

No data available

CF Desco® II Deflocculant

Skin irritation

: May irritate skin.

May cause skin irritation in susceptible persons.

CF Desco® II Deflocculant

Eye irritation

: May irritate eyes.

May cause irreversible eye damage.

Repeated dose toxicity

Methyl ester of sulfonated

tannin

: Species: Rat, male

Sex: male

Application Route: oral gavage Dose: 100, 300, 1000 mg/kg

Exposure time: 32 d Number of exposures: Daily NOEL: 1,000 mg/kg

Method: OECD Guideline 422 No adverse effects expected

Species: Rat, female

Sex: female

Application Route: oral gavage Dose: 100, 300, 1000 mg/kg Exposure time: 39 - 47 d Number of exposures: Daily NOEL: 1,000 mg/kg

Method: OECD Guideline 422 No adverse effects expected

Genotoxicity in vitro

Methyl ester of sulfonated

tannin

: Test Type: Chromosome aberration test in vitro

Metabolic activation: with and without metabolic activation

Method: OECD Guideline 473

Result: negative

Reproductive toxicity

Methyl ester of sulfonated

tannin

: Species: Rat Sex: male

Application Route: oral gavage Dose: 100, 300, 1000 mg/kg

Exposure time: 32 d Number of exposures: Daily Method: OECD Guideline 422 NOAEL Parent: 1,000 mg/kg

Fertility and developmental toxicity tests did not reveal any

8/14

effect on reproduction.

SDS Number:100000013722

Version 3.6 Revision Date 2023-11-15

Species: Rat Sex: female

Application Route: oral gavage Dose: 100, 300, 1000 mg/kg Exposure time: 39 - 47 d Number of exposures: Daily Method: OECD Guideline 422 NOAEL Parent: 1,000 mg/kg NOAEL F1: 1,000 mg/kg

Fertility and developmental toxicity tests did not reveal any

effect on reproduction.

CF Desco® II Deflocculant

Aspiration toxicity : No aspiration toxicity classification.

CMR effects

Crystalline Silica : Carcinogenicity: Human carcinogen.

CF Desco® II Deflocculant

Further information : No data available.

SECTION 12: Ecological information

Ecotoxicity effects Toxicity to fish

Methyl ester of sulfonated

tannin

: LL50: > 1,800 mg/l Exposure time: 96 h

Species: Scophthalmus maximus (Flatfish, Flounder)

Method: OECD Test Guideline 203

Ferrous Sulfate LL50: > 6.25 mg/l

Exposure time: 96 h

Species: Cyprinodon variegatus (sheepshead minnow) semi-static test Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Methyl ester of sulfonated

: EL50: 73.2 mg/l Exposure time: 48 h

tannin

Species: Acartia tonsa (Marine Copepod)

Method: ISO TC147/SC5/WG2

Ferrous Sulfate LC50: 190 mg/l

Exposure time: 48 h

Species: Acartia tonsa (Marine Copepod)

Method: ISO TC147/SC5/WG2

Toxicity to algae

Methyl ester of sulfonated

tannin

: ErC50: > 100 mg/l Exposure time: 72 h

SDS Number:100000013722

9/14

Revision Date 2023-11-15 Version 3.6

Species: Desmodesmus subspicatus (green algae)

Method: OECD Test Guideline 201

EbC50: 79 mg/l Exposure time: 72 h

Species: Desmodesmus subspicatus (green algae)

Method: OECD Test Guideline 201

Ferrous Sulfate EL50: 45 mg/l

Exposure time: 72 h

Species: Skeletonema costatum (Marine Algae)

Method: ISO 10253

: Taking into consideration the properties of several ingredients, Biodegradability

the product is estimated not to be readily biodegradable

according to OECD classification.

Elimination information (persistence and degradability)

Bioaccumulation : This material is not expected to bioaccumulate.

: No data available Mobility

Additional ecological

information

: Harmful to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard

Methyl ester of sulfonated

tannin

: Harmful to aquatic life.

Long-term (chronic) aquatic hazard

Methyl ester of sulfonated

tannin

: Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

> courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

SDS Number:100000013722 10/14

Version 3.6 Revision Date 2023-11-15

Do not re-use empty containers.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S., (FERROUS SULFATE), 9, III, RQ (FERROUS SULFATE)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NÒT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

National legislation

SARA 311/312 Hazards : Combustible dust Carcinogenicity

SDS Number:100000013722 11/14

SAFETY DATA SHEET

CF Desco® II Deflocculant

Version 3.6 Revision Date 2023-11-15

Skin corrosion or irritation

Serious eye damage or eye irritation

CERCLA Reportable

Quantity

: Calculated RQ exceeds reasonably attainable upper limit.

Acrylic Acid

SARA 302 Reportable

Quantity

: This material does not contain any components with a SARA

302 RQ.

SARA 302 Threshold

Planning Quantity

: This material does not contain any components with a section

302 EHS TPQ.

SARA 304 Reportable

Quantity

: This material does not contain any components with a section

304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with

> known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion

Potential

: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR

82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

SDS Number:100000013722 12/14

Version 3.6 Revision Date 2023-11-15

Pennsylvania Right To Know

: Methyl ester of sulfonated tannin - Proprietary

Ferrous Sulfate - 17375-41-6

California Prop. 65

Components

: WARNING! This product contains a chemical known in the

State of California to cause cancer.

Crystalline Silica 14808-60-7

Notification status

Europe REACH A substance or substances in this product is not

> registered or notified to be registered. Importation or manufacture of this product is still permitted provided that it does not exceed the REACH minimum threshold

quantity of the non-regulated substances.

Switzerland CH INV Not in compliance with the inventory

On or in compliance with the active portion of the United States of America (USA)

TSCA TSCA inventory

Canada DSL All components of this product are on the Canadian

Australia AIIC On the inventory, or in compliance with the inventory

Not in compliance with the inventory New Zealand NZIoC Japan ENCS Not in compliance with the inventory

A substance(s) in this product was not registered. Korea KECI

notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold

quantity of the non-registered substance(s).

Philippines PICCS Not in compliance with the inventory Taiwan TCSI Not in compliance with the inventory

China IECSC On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 1

Fire Hazard: 2 Reactivity Hazard: 0



Further information

Legacy SDS Number : 704530

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

SDS Number:100000013722 13/14

Version 3.6 Revision Date 2023-11-15

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet				
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%	
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level	
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency	
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health	
CNS	Central Nervous System	NTP	National Toxicology Program	
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals	
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level	
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration	
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration	
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit	
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances	
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic	
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act	
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit	
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.	
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value	
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average	
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act	
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials	
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System	
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate	

SDS Number:100000013722 14/14