

## Marlex® D350 Polyethylene

Version 3.6

Revision Date 2024-08-14

## SECTION 1: Identification of the substance/mixture and of the company/undertaking **Product information** Product Name : Marlex® D350 Polvethylene 1130009, 1130010, 1130008, 1080521, 1019024, 1019023, Material 1019021, 1019020, 1019019, 1019566, 1019565, 1019564, 1019022, 1019568, 1018364, 1018361, 1019567 Company : Chevron Phillips Chemical Company LP 10001 Six Pines Drive The Woodlands, TX 77380 **Emergency telephone:** Health: 866.442.9628 (North America) 1.832.813.4984 (International) Transport: CHEMTREC 800.424.9300 or 703.527.3887(int'l) Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090 Mexico CHEMTREC 01-800-681-9531 (24 hours) South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600 Argentina: +(54)-1159839431 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week) Belgium: 070 245 245 (24 hours/day, 7 days/week) Bulgaria: +359 2 9154 233 Croatia: +3851 2348 342 (24 hours/day, 7 days/week) Cyprus: 1401 Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402 Denmark: Danish Poison Center (Giftlinien): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Finland: 0800 147 111 09 471 977 (24 hours/day) France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week) Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week) Iceland: 543 2222 (24 hours/day, 7 days/week) Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) SDS Number:10000000668 1/13

SAFETY DATA SHEET

Version 3.6

Revision Date 2024-08-14

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME - Policlinico "Agostino Gemelli", Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME - Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000; POISON CENTER FOGGIA - Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA - IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO - Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883 300; POISON CENTER VERONA - Azienda Ospedaliera Universitaria integrata Tel. 800 011 858: Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.) Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Lithuania: +370 (85) 2362052 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week) Malta: +356 2395 2000 The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week) Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Portugal: CIAV phone number: +351 800 250 250 Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week) Sweden: 112 - ask for Poisons Information : Product Safety and Toxicology Group Responsible Department SDS@CPChem.com E-mail address Website www.CPChem.com : MEDICAL APPLICATION CAUTION: Do not use this material in medical applications involving permanent implantation in the human body or permanent contact with internal body fluids or tissues fluids or tissues.

Do not use this material in medical applications involving brief or temporary implantation in the human body or contact with internal body fluids or tissues unless the material has been provided directly from Chevron Phillips Chemical Company LP or its legal affiliates under an agreement which expressly acknowledges the contemplated use.

Chevron Phillips Chemical Company LP and its legal affiliates makes no representation, promise, express warranty or implied warranty concerning the suitability of this material for use in implantation in the human body or in contact with internal body fluids or tissues.

#### **SECTION 2: Hazards identification**

	<b>Ibstance or mixture</b> lassified in accordance with the hazard communication standard 29 CFR d labels contain all the information as required by the standard.
Classification	: Combustible dust
Labeling	

SDS Number:10000000668

## Marlex® D350 Polyethylene

Warlex® D350 Polyeth Version 3.6	Revision Date 2024-08-14		
Signal Word	: Warning		
Hazard Statements	<ul> <li>Warning</li> <li>May form combustible dust concentrations in air.</li> <li>While this product may not be a combustible dust as sold, further processing or handling may form combustible dust concentration in air.</li> </ul>		
Potential Health Effects			
Physical Hazards	<ul> <li>Pellets may cause a slip hazard on hard surfaces. Mechanical processing may form combustible dust concentrations in air and thermal processing at elevated temperatures may generate formaldehyde.</li> </ul>		
Inhalation	<ul> <li>Repeated exposure to dust from this material may cause respiratory irritation.</li> <li>Fumes generated during thermal processing may cause irritation of the upper respiratory tract.</li> </ul>		
Skin	<ul> <li>Contact with the skin is not expected to cause prolonged or significant irritation.</li> <li>Contact with the skin is not expected to cause an allergic response.</li> <li>If this material is heated, thermal burns may result from contact.</li> <li>Thermal burns may include pain or feeling of heat, discolorations, swelling, and blistering.</li> </ul>		
Eyes	<ul> <li>Contact with the eyes may cause irritation due to the abrasive action.</li> <li>Not expected to cause prolonged or significant eye irritation.</li> </ul>		
Ingestion	Thermal burns may result if heated material contacts eye. : Ingestion of this product is not a likely route of exposure.		
Carcinogenicity:			
IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.		
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.		
SECTION 3: Composition/infor	mation on ingredients		
Component	CAS-No. Weight %		
Polyethylene Hexene Copol	lymer 25213-02-9 99 - 100		
SECTION 4: First aid measures	5		
If inhaled	: Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If symptoms persist, call a physician.		
SDS Number:10000000668	3/13		

rlex® D350 Polyeth	vle	ne
sion 3.6	<i>.</i>	Revision Date 2024-08
In case of skin contact	:	If the molten material gets on skin, quickly cool in water. Seek immediate medical attention. Do not try to peel the solidified material from the skin or use solvents or thinners to dissolve it.
In case of eye contact	:	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If swallowed	:	Do not induce vomiting without medical advice.
TION 5: Firefighting measu	res	
Flash point	:	No data available
Autoignition temperature	:	No data available
Suitable extinguishing media	:	Water. Water mist. Dry chemical. Carbon dioxide (CO2). Foam. If possible, water should be applied as a spray from a fogging nozzle since this is a surface burning material. The application of high velocity water will spread the burning surface layer. Avoid the use of straight streams that may create a dust cloud and the risk of a dust explosion. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific hazards during fire fighting	:	Risks of ignition followed by flame propagation or secondary explosions can be caused by the accumulation of dust, e.g. on floors and ledges.
Special protective equipment for fire-fighters	:	Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	This material will burn although it is not easily ignited.
Fire and explosion protection	:	Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Hazardous decomposition products	:	Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, other hydrocarbons and hydrocarbon oxidation products (ketones, aldehydes, organic acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.
TION 6: Accidental release	mea	asures
Personal precautions	:	Sweep up to prevent slipping hazard. Avoid breathing dust. Avoid dust formation.
Environmental precautions	:	Do not contaminate surface water. Prevent product from entering drains.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum.
Additional advice	:	Dust deposits should not be allowed to accumulate on
Number:10000000668		4/13

## Marlex® D350 Polyethylene

Version 3.6

Revision Date 2024-08-14

surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

## **SECTION 7: Handling and storage** Handling Advice on safe handling Use good housekeeping for safe handling of the product. Keep out of water sources and sewers. Spilled pellets may create a slipping hazard. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. At elevated temperatures (>350°F, >177°C), polyethylene can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, formaldehyde has been listed as a carcinogen. Following all recommendations within this SDS should minimize exposure to thermal processing emissions. Advice on protection Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the against fire and explosion presence of an ignition source is a potential dust explosion hazard. Storage Requirements for storage : Keep in a dry place. Keep in a well-ventilated place. areas and containers Advice on common storage : Do not store together with oxidizing and self-igniting products. **SECTION 8: Exposure controls/personal protection**

#### Ingredients with workplace control parameters

#### US

Components	Basis	Value	Control parameters	Note
Nuisance Dust	OSHA Z-3	TWA	15 mg/m3	Total dust
	OSHA Z-3	TWA	5 mg/m3	(respirable dust)

Control as Particulate Not Otherwise Classified (PNOC). The ACGIH Guideline\* for respirable dust is 3.0 mg/m3 and 10.0 mg/m3 for total dust. The OSHA PEL for respirable dust is 5.0 mg/m3 and 15.0 mg/m3 for total dust.

\* This value is for inhalable (total) particulate matter containing no asbestos and < 1.0% crystalline silica.

### Engineering measures

SDS Number:10000000668

## Marlex® D350 Polyethylene

Version 3.6

Revision Date 2024-08-14

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

#### Personal protective equipment

Respiratory protection	:	No respiratory protection is normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear an appropriate respirator. Use the following elements for air-purifying respirators: Organic Vapor and Formaldehyde. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. Dust safety masks are recommended when the dust concentration is excessive.
Eye protection	:	Use of safety glasses with side shields for solid handling is good industrial practice. If this material is heated, wear chemical goggles or safety glasses with side shields or a face shield. If there is potential for dust, use chemical goggles.
Skin and body protection	:	At ambient temperatures use of clean and protective clothing is good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate.

#### **SECTION 9: Physical and chemical properties**

Appearance	
Form Physical state Color Odor Odor Threshold	<ul> <li>Pellets</li> <li>solid</li> <li>Opaque</li> <li>Mild to no odor</li> <li>No data available</li> </ul>
Safety data	
Flash point	: No data available
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Autoignition temperature	: No data available
Thermal decomposition	: Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
S Number:100000000668	6/13

Version 3.6

SAFETY DATA SHEET

Revision Date 2024-08-14

рН	: Not applicable
Melting point/range	: 90-140°C (194-284°F)
Freezing point	Not applicable
Initial boiling point and boiling	: Not applicable
range Vapor pressure	: Not applicable
Relative density	: Not applicable
Density	<ul> <li>0.91 - 0.97 g/cm3</li> <li>Please refer to the Technical Data Sheet (TDS) for more detailed information relating to the nominal physical properties, including density, of this polyethylene resin grade.</li> </ul>
Water solubility	: negligible
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: No data available
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable
Relative vapor density	: Not applicable
Evaporation rate	: Not applicable
Dust deflagration index Kst	: > 0.0 m.b_/s
SECTION 10: Stability and reactiv	vity
Reactivity	: This material is considered non-reactive under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous read	tions
Hazardous reactions	: Hazardous reactions: None known.
Conditions to avoid	: Avoid prolonged storage at elevated temperature.
SDS Number:10000000668	7/13
	1/15

arlex® D350 Polyethy	SAFETY DATA SHEE
ersion 3.6	Revision Date 2024-08-1
Materials to avoid	: Avoid contact with strong oxidizing agents.
Thermal decomposition	: Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
Hazardous decomposition products	: Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, other hydrocarbons and hydrocarbon oxidation products (ketones, aldehydes, organic acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.
Other data	: No decomposition if stored and applied as directed.
CTION 11: Toxicological infor	mation
Marlex® D350 Polyethylene Acute oral toxicity	: Presumed Not Toxic
Marlex® D350 Polyethylene Acute inhalation toxicity	: Presumed Not Toxic
Marlex® D350 Polyethylene Acute dermal toxicity	: Presumed Not Toxic
Marlex® D350 Polyethylene Skin irritation	: No skin irritation
Marlex® D350 Polyethylene Eye irritation	: No eye irritation
Marlex® D350 Polyethylene Sensitization	: Did not cause sensitization on laboratory animals.
Marlex® D350 Polyethylene Further information	: This product contains POLYMERIZED OLEFINS. During thermal processing (>350°F, >177°C) polyolefins can release vapors and gases (aldehydes,ketones and organic acids) which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a carcinogen based on animal data and limited epidemiological evidence.
CTION 12: Ecological informa	tion
OS Number:100000000668	8/13

sion 3.6	Revision Date 2024-08
Ecotoxicity effects	
Toxicity to fish	: Not applicable
Toxicity to daphnia and other aquatic invertebrates	: No data available
Biodegradability	: This material is not expected to be readily biodegradable.
Elimination information (persis	tence and degradability)
Bioaccumulation	: Does not bioaccumulate.
Mobility	: The product is insoluble and floats on water.
Additional ecological information	: This material is not expected to be harmful to aquatic organisms., Fish or birds may eat pellets which may obstruct their digestive tracts.
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: This product has no known ecotoxicological effects.
Long-term (chronic) aquatic hazard	: This product has no known ecotoxicological effects.
CTION 13: Disposal considera	ations
The information in this SDS pe	ertains only to the product as shipped.
Use material for its intended p may meet the criteria of a haz other State and local regulatio regulated components may be	urpose or recycle if possible. This material, if it must be discarded, ardous waste as defined by US EPA under RCRA (40 CFR 261) or ns. Measurement of certain physical properties and analysis for e necessary to make a correct determination. If this material is te, federal law requires disposal at a licensed hazardous waste
CTION 14: Transport informat	ion
	hown here are for bulk shipments only, and may not apply to ages (see regulatory definition).
Consult the appropriate dome	stic or international mode-specific and quantity-specific Dangerous

С Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)** NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS) NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR

SDS Number:10000000668

9/13

# Marlex® D350 Polyethylene

SDS Number:10000000668

Revision Date 2024-08-14

Version 3.6

TRANSPORTATION BY THIS AGENCY.

	AIR TRANSPORT ASSOCIATION) A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR ( THIS AGENCY.
	<b>ANGEROUS GOODS BY ROAD (EUROPE))</b> A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR ( THIS AGENCY.
DANGEROUS GOODS (EI	A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR
OF DANGEROUS GOODS	EMENT CONCERNING THE INTERNATIONAL CARRIAGE BY INLAND WATERWAYS) A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR ( THIS AGENCY.
Maritime transport in bull SECTION 15: Regulatory infor	k according to IMO instruments
National legislation	
SARA 311/312 Hazards	: Combustible dust
CERCLA Reportable Quantity	: This material does not contain any components with a CERCLA RQ.
SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.
SARA 302 Threshold Planning Quantity SARA 304 Reportable Quantity	<ul> <li>No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.</li> <li>This material does not contain any components with a section 304 EHS RQ.</li> </ul>
SARA 313 Components	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

10/13

SAFETY DATA SHEET

Version 3.6

Revision Date 2024-08-14

#### **Clean Air Act**

Ozone-Depletion : This product neither contains, nor was manufactured with a Class I or Potential Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

#### **US State Regulations**

Pennsylvania Right To Know : No components are subject to the Pennsylvania Right to Know Act.

California Prop. 65 : This product, as shipped, does not contain any carcinogens or reproductive toxins presently known by the State of California to cause cancer or reproductive toxicity at a level of exposure subject to the requirements of California Proposition 65.

## Notification status

Europe REACH This product is in full compliance according to REACH 5 regulation 1907/2006/EC. Switzerland CH INV On the inventory, or in compliance with the inventory 5 United States of America (USA) On or in compliance with the active portion of the : TSCA **TSCA** inventory Canada DSL All components of this product are on the Canadian : DSL Australia AIIC : On the inventory, or in compliance with the inventory New Zealand NZIoC On the inventory, or in compliance with the inventory : Japan ENCS On the inventory, or in compliance with the inventory : Philippines PICCS On the inventory, or in compliance with the inventory 5 China IECSC On the inventory, or in compliance with the inventory 2 Korea KECI A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. SDS Number:10000000668 11/13

000668

	SAFETY DATA SHEET
Marlex® D350 Polyet	hylene
Version 3.6	Revision Date 2024-08-14
	Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
Taiwan TCSI	: On the inventory, or in compliance with the inventory
<b>SECTION 16: Other informati</b>	on
NFPA Classification	: Health Hazard: 0 Fire Hazard: 1 Reactivity Hazard: 0
Further information Legacy SDS Number	: 240370
Significant changes since	the last version are highlighted in the margin. This version replaces all

previous versions.

The information in this SDS pertains only to the product as shipped.

Г

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effe
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agenc
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupatio Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentra
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substan
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recov

#### SAFETY DATA SHEET

Version 3.6

Revision Date 2024-08-14

		1	
			Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate