

Version 1.13 Revision Date 2025-06-12

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1

**Product information** 

Product Name : Sodium Methyl Mercaptide

Material : 1114147, 1114146, 1114145, 1065936, 1066239, 1030037,

1029154, 1029192, 1034903

1.2

1.3

Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses : Use as an intermediate

Supported

Details of the supplier of the safety data sheet

Company : Chevron Phillips Chemical Company LP

Specialty Chemicals 9500 Lakeside Blvd. The Woodlands, TX 77381

Local : Chevron Phillips Chemicals International N.V.

Airport Plaza (Stockholm Building)

Leonardo Da Vincilaan 19

1831 Diegem Belgium

SDS Requests: (800) 852-5530

Responsible Party: Product Safety Group

Email:sds@cpchem.com

1.4

## **Emergency telephone:**

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week) Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

SDS Number:100000013985 1/18

Version 1.13 Revision Date 2025-06-12

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax) Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: POISON CENTER MILÂN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico "Agostino Gemelli", Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24

hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

### **SECTION 2: Hazards identification**

## 2.1

# Classification of the substance or mixture REGULATION (EC) No 1272/2008

Flammable liquids, Category 3 H226:

Flammable liquid and vapor.

Acute toxicity, Category 4 H302:

Harmful if swallowed.

Skin corrosion, Sub-category 1A H314:

Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318:

Causes serious eye damage.

SDS Number:100000013985 2/18

Version 1.13 Revision Date 2025-06-12

#### 2.2

## Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal Word Danger

Hazard Statements H226 Flammable liquid and vapor.

> H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

**Precautionary Statements** Prevention:

> Keep away from heat, hot surfaces, sparks, P210

> > open flames and other ignition sources. No

smoking.

Wear protective gloves/ protective clothing/ P280

eye protection/ face protection/ hearing

protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing.

Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

> air and keep comfortable for breathing. Immediately call a POISON CENTER/

doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

In case of fire: Use dry sand, dry chemical P370 + P378

or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

5188-07-8 Sodium Methanethiolate 1310-73-2 Sodium Hydroxide

#### 2.3

#### Other hazards

Results of PBT and vPvB

assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1%

or higher.

Endocrine disrupting

properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SDS Number:100000013985

## **Sodium Methyl Mercaptide**

Version 1.13 Revision Date 2025-06-12

#### **SECTION 3: Composition/information on ingredients**

Synonyms : Methanethiol sodium salt

SMM

Sodium methanethiolate

Sodium methyl mercaptide 21%

Molecular formula : CH3SNa

## Hazardous ingredients

| Chemical name             | CAS-No.<br>EC-No.<br>Index No.         | Classification<br>(REGULATION (EC)<br>No 1272/2008)                                 | Concentration [wt%] | Specific Conc.<br>Limits, M-factors<br>and ATEs |
|---------------------------|--|---|---------------------|---|
| Sodium<br>Methanethiolate | 5188-07-8<br>225-969-9                 | Flam. Liq. 3; H226<br>Acute Tox. 4; H302<br>Skin Corr. 1A; H314<br>Eye Dam. 1; H318 | 20 - 25             |   |
| Sodium Hydroxide          | 1310-73-2<br>215-185-5<br>011-002-00-6 | Met. Corr. 1; H290<br>Skin Corr. 1A; H314<br>Eye Dam. 1; H318                       | 0,4 - 1             |   |

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

## 4.1

#### **Description of first-aid measures**

General advice : Move out of dangerous area. Consult a physician. Show this

material safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical

advice. If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with difficulty. If on skin, rinse well with water. If on clothes,

remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a

specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

# 4.2 Most important symptoms and effects, both acute and delayed Notes to physician

SDS Number:100000013985 4/18

## Sodium Methyl Mercaptide

Version 1.13 Revision Date 2025-06-12

**Symptoms** No data available.

: No data available. Risks

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No data available.

#### **SECTION 5: Firefighting measures**

Flash point 29°C (84°F)

Method: Tag closed cup

Autoignition temperature : No data available

5.1

**Extinguishing media** 

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

5.2

Special hazards arising from the substance or mixture

fighting

Specific hazards during fire : Do not allow run-off from fire fighting to enter drains or water

courses.

5.3

Advice for firefighters

Special protective

equipment for fire-fighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

: Collect contaminated fire extinguishing water separately. This Further information

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed

containers.

Fire and explosion

protection

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition

products

: Sulfur oxides.

## **SECTION 6: Accidental release measures**

#### 6.1

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment. Remove all sources of

> ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can

accumulate in low areas.

SDS Number:100000013985 5/18

Version 1.13 Revision Date 2025-06-12

6.2

## **Environmental precautions**

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

6.3

## Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

6.4

#### Reference to other sections

Reference to other sections : For personal protection see section 8. For disposal

considerations see section 13.

### **SECTION 7: Handling and storage**

7.1

# Precautions for safe handling Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with

local and national regulations.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

7.2

## Conditions for safe storage, including any incompatibilities

### **Storage**

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and wellventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working

Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1

#### **Control parameters**

SDS Number:100000013985 6/18

Version 1.13 Revision Date 2025-06-12

| Version 1.13                |                                   |                              | Revisio                    | n Date 2025-06-12                            |
|-----------------------------|-----------------------------------|------------------------------|----------------------------|--|
| la anno di casto caitle con |                                   |                              |                            |  |
| Ingredients with wo         | rkplace control para              | meters                       |                            |  |
| CK.                         |                                   |                              |                            |  |
| <b>SK</b><br>Zložky         | Podstata                          | Hodnota                      | Kontrolné parametre        | Poznámka                                     |
| Sodium Hydroxide            | SK OEL                            | NPEL priemerný               | 2 mg/m3                    | FUZIIAIIIKA                                  |
| - Coarani i iyaroxiao       | OK OLL                            | THE EL PHOMOTHY              | 2 mg/mo                    |  |
| SE                          |                                   |                              | T                          |  |
| Beståndsdelar               | Grundval                          | Värde                        | Kontrollparametrar         | Anmärkning                                   |
| Sodium Hydroxide            | AFS 2023:14                       | NGV                          | 1 mg/m3                    | Inhalerbart                                  |
|                             | AFS 2023:14<br>AFS 2023:14        | TGV<br>NGV                   | 2 mg/m3<br>1 mg/m3         | Inhalerbart inhalabel fraktion               |
|                             | AFS 2023:14                       | KGV                          | 2 mg/m3                    | inhalabel fraktion                           |
|                             | <u> </u>                          |                              | <u> </u>                   |  |
| RU                          |                                   | T n                          | 1-                         | Το   |
| Компоненты                  | Основа                            | Величина                     | Параметры контроля         |  |
| Гидроксид натрия            | RU OEL<br>RU OEL                  | ПДК разовая<br>ПДК разовая   | 0,5 mg/m3<br>0,5 mg/m3     | 2, Аэрозоль<br>2, Аэрозоль                   |
|                             | РФ ПДК                            | ПДК разовая                  | 0,5 mg/m3                  | 2, нарозоль<br>2, н, аэрозоль                |
| + вещества, при ра          | боте с которыми требуется сг      |                              |                            | 2, 1, 40,00013                               |
| 2 2 класс - высокос         | пасные                            |                              |                            |  |
| RO                          |                                   |                              |                            |  |
| Componente                  | Sursă                             | Valoare                      | Parametri de control       | Notă   |
| Sodium Hydroxide            | RO OEL                            | TWA                          | 1 mg/m3                    | 11010  |
| Social Hydroxide            | RO OEL                            | STEL                         | 3 mg/m3                    |  |
|                             | <u> </u>                          |                              | <u> </u>                   |  |
| PT                          |                                   | T.,,,                        | 15 4                       | T.v.   |
| Componentes                 | Base                              | Valor                        | Parâmetros de              | Nota   |
| Codings Underside           | DT OF                             | \/I F OF                     | controle                   |  |
| Sodium Hydroxide            | PT OEL                            | VLE-CE                       | 2 mg/m3                    |  |
| PL                          |                                   |                              |                            |  |
| Składniki                   | Podstawa                          | Wartość                      | Parametry dotyczące        | Uwaga  |
|                             |                                   |                              | kontroli                   | •  |
| Sodium Hydroxide            | PL NDS                            | NDS                          | 0,5 mg/m3                  |  |
|                             | PL NDS                            | NDSch                        | 1 mg/m3                    |  |
| NO                          |                                   |                              |                            |  |
| Komponenter                 | Grunnlag                          | Verdi                        | Kontrollparametrer         | Nota   |
| Sodium Hydroxide            | FOR-2011-12-06-                   | Т                            | 2 mg/m3                    |  |
| 30didili Flydroxide         | 1358                              | 1                            | 2 1119/1113                |  |
| MK                          |                                   |                              |                            |  |
| Съставки                    | Основа                            | Стойност                     | Параметри на               | Бележка                                      |
| O Bortabilli                | 0011054                           | Growniegr                    | контрол                    | Borionila                                    |
|                             |                                   |                              | •                          | Inhalable fraction - the                     |
| Sodium Hydroxide            | MK OEL                            | MV                           | 2 mg/m3                    | part of the total<br>suspended material that |
| 30didili Fiyaroxide         | WIN OLL                           | IVIV                         | 2 1119/1113                | is inhaled by the                            |
|                             |                                   |                              |                            | employees                                    |
| LV                          |                                   |                              |                            |  |
| Sastāvdalas                 | Bāze                              | Vērtība                      | Kontroles parametri        | Piezīme                                      |
| Sodium Hydroxide            | LV OEL                            | AER 8 st                     | 0,5 mg/m3                  |  |
|                             |                                   |                              | J. J.                      |  |
| LT                          |                                   | •                            | 1                          | _  |
| Komponentai                 | Šaltinis                          | Vertė                        | Kontrolės parametrai       | Pastaba                                      |
| Sodium Hydroxide            | LT OEL                            | NRD                          | 2 mg/m3                    |  |
| ıs                          |                                   |                              |                            |  |
| Komponenter                 | Grunnlag                          | Verdi                        | Kontrollparametrer         | Nota   |
| Sodium Hydroxide            | IS OEL                            | STEL                         | 2 mg/m3                    |  |
|                             |                                   | 1 -                          |                            | - I  |
| IE                          | T -                               | T                            | 1 -                        |  |
| Components                  | Basis                             | Value                        | Control parameters         | Note   |
| Sodium Hydroxide            | IE OEL                            | OELV - 15 min (STEL)         | 2 mg/m3                    |  |
| ни                          |                                   |                              |                            |  |
| Komponensek                 | Bázis                             | Érték                        | Ellenőrzési                | Megjegyzés                                   |
|                             | 542.0                             |                              | paraméterek                |  |
| Sodium Hydroxide            | HU OEL                            | AK-érték                     | 1 mg/m3                    | N, m,  |
|                             | HU OEL                            | CK-érték                     | 2 mg/m3                    | N, m,  |
|                             | g (felmarja a bőrt, nyálkahártyát |                              |                            |  |
| N Irritáló anyagok, e       | gyszerű fojtógázok, csekély egé   | eszsegkarosito hatással bíró | о апуадок. Korrekció NEM s | zukseges.                                    |
| HR                          |                                   |                              |                            |  |

| Sastojci                     | Temelj | Vrijednost | Nadzorni parametri | Bilješka |
|------------------------------|--------|------------|--------------------|----------|
| SDS Number:100000013985 7/18 |        |            |                    |          |

| Sodium Hydroxide   HR OEL   KGVI   2 mg/m3   3R  2.corranxd   860m   Turk   Repéterpor eAcyyou   Expeliador   Sodium Hydroxide   OR OEL   TVWA   2 mg/m3    2.corranxd   Sodium Hydroxide   OR OEL   TVWA   2 mg/m3    2.corranxd   Sodium Hydroxide   OR OEL   TVWA   2 mg/m3    2.corranxd   Sodium Hydroxide   OB EH40   STEL   2 mg/m3    2.corranxd   Sodium Hydroxide   OB EH40   STEL   2 mg/m3    2.corranxd   Sodium Hydroxide   FR VLE   VME   2 mg/m3   Valuers imites admises (circulaires) admises (circulaires)   3.corranxe   Sodium Hydroxide   FR VLE   VME   2 mg/m3   Valuers imites admises (circulaires)   3.corranxe   Peruste   Arvo   Valvontaa koskevat muuttujat   3.corranxe   Peruste   Arvo   Valvontaa koskevat muuttujat   3.corranxe   Peruste   Arvo   Valvontaa koskevat muuttujat   3.corranxe   Peruste   Arvo   Parámetros de control   3.corranxe   Parametros   Parametros   Parametros   3.corranxe   Parametro   Parametro   Parametro   3.corranxe   Parametro   Parametro   Parametro   3.corranxe   Parametro   Parameter   Parameter   3.corranxe   Parameter   Parameter   Parameter   Parameter   3.corranxe   Parameter  | Varaian 1 12                                    |                                 |   | Dovision                              | Doto 2025 06            |
|--|---|---------------------------------|---|---------------------------------------|-------------------------|
| Section Hydroxide Bádon Tiµn Ropóperpol Exégyou Enpletium Sodium Hydroxide GR OEL TWA 2 mg/m3  GR OEL STEL 2 mg/m3  Section Hydroxide GR OEL STEL 2 mg/m3  Section Hydroxide GR OEL STEL 2 mg/m3  Section Hydroxide GR EH40 STEL 2 mg/m3  Note Control parameters Note Section STEL 2 mg/m3  Section Hydroxide FR VLE WME 2 mg/m3 Valeur interes and control of c | Version 1.13                                    |                                 |   | Revision                              | 1 Date 2025-06          |
| Σucranxix         Bódn (PL)         Tuyl (PVA)         2 mg/m3         Physicion (PVA)         2 mg/m3         2   | Sodium Hydroxide                                | HR OEL                          | KGVI                                    | 2 mg/m3                               |                         |
| Sodium Hydroxide GR OEL TVIA 2 mgm3   2 mgm3   388   378   2 mgm3   389  | GR  |                                 |   |                                       |                         |
| SB Components Basis Value Control parameters Note Sodium Hydroxide GB EH40 STEL 2 mg/m3  FR Composants Base Valeur Parameters de control control fel c |   |                                 |   |                                       | Σημείωση                |
| Components Basis Value Control parameters Note Sodium Hydroxide GB EH40 STEL 2 mg/m3  R Composants Base Valeur Paramètres de contrôle Sodium Hydroxide FR VLE VME 2 mg/m3 Valeurs limites admises (circulaires) admises (circulaires) demises demises (circulaires) demises demises (circulaires) demises  | Sodium Hydroxide                                |                                 |   |                                       |                         |
| Components Basis Value Control parameters Note Sodium Hydroxide GB EH40 STEL 2 mg/m3  R Composants Base Valeur Paramètres de contrôle (contrôle Maries) (con |   | GROEL                           | SIEL                                    | z mg/ms                               |                         |
| Sodium Hydroxide   GB EH40   STEL   2 mg/m3  |   | Dania                           | Value                                   | Control norometers                    | Note                    |
| Composants Base Valeur Paramètres de contrôle Note Contrôle FR VLE VME 2 mg/m3 Valeurs limites de (cinculaires) domines de (cinculaires) de contrôle Valeurs limites admises (circulaires) de contrôle Valeurs limites admises (circulaires) de cinculaires) de cinculaires) de cinculaires) de cinculaires) Valeurs limites admises (circulaires) Valeurs limites admises valeurs limites admises (circulaires) Valeurs limites admises (circulaires) Valeurs limites admises valeurs limites admises (circulaires) Valeurs limites admises valeurs limites valeurs |   |                                 |   | •                                     | Note                    |
| Composants   Base   Valeur   Paramètres de contrôle     | •   | 05 21110                        | 0122                                    | 2 mg/mo                               |                         |
| Sodium Hydroxide FR VLE VME 2 mg/m3 Valeurs limites admises (circulaires) admises desires valeurs limites admises (circulaires) admistures admisturates (circulaires) admisturates (circulaires) admisturates (circulaires)  |   | Paga                            | Volour                                  | Doromòtros do                         | Note                    |
| Sodium Hydroxide   Peruste   Vale   2 mg/m3   (circulaires), Valeurs limites Valeurs limites admises (circulaires) admises (circulaires)   | Composants                                      | Dase                            | valeui                                  |                                       | Note                    |
| Valeurs limites         Valeurs limites admises (circulaires) admises (circulaires)           FI           Aineosat         Peruste         Arvo         Valvontaa koskevat muuttujat muuttujat           Sodium Hydroxide         FI OEL         CEIL         2 mg/m3           Sodium Hydroxide         Base         Valor         Parâmetros de control         Nota           Sodium Hydroxide         ES VLA         VLA-EC         2 mg/m3           EE         Componenties         Sodium Hydroxide         ES VLA         VLA-EC         2 mg/m3           EE         CEL         Piimorm         1 mg/m3         Märkused           Sodium Hydroxide         EE OEL         Piimorm         1 mg/m3         Valvontaa koskevaut           DK         EE OEL         Piimorm         1 mg/m3         Valvontaa koskevat         Märkused           DK         Sodium Hydroxide         EE OEL         Piimorm         1 mg/m3         Valvontaa koskevat         Märkused           DK         Sodium Hydroxide         DK OEL         L         2 mg/m3         Note           Sodium Hydroxide         CZ OEL         PEL         1 mg/m3         1.           L         J dráždí siliznice (očl, dychaci cesty), respektíve kúž         Z         Z         Z  | Sodium Hydroxide                                | FR VLE                          | VME                                     | 2 mg/m3                               | Valeurs limites admis   |
| Aineosat Peruste Arvo Valvontaa koskevat muuttujat Muuttujat Sodium Hydroxide FI OEL CEIL 2 mgm3 SES  Sodium Hydroxide ES VLA VLA-EC 2 mgm3 SES VLA VLA-E  | admises<br>(circulaires)                        | mises (circulaires)             |   |                                       | (circulaires),          |
| Sodium Hydroxide Sodiu  |   | Peruste                         | Arvo                                    | Valvontaa koskevat                    | Huomautus               |
| Sodium Hydroxide  Base Valor Parámetros de control Nota Sodium Hydroxide  ES VLA VLA-EC 2 mg/m3  EE CEL VLA VLA-EC 2 mg/m3  EE CEL Pimorom 1 mg/m3  EE OEL Pimorom 1 mg/m3  EE OEL Lúhlajalise kokkupuute pimorom 2 mg/m3  Komponendid, osad Alused Väärtus Kontrolliparameetrid Märkused Sodium Hydroxide  EE OEL Lúhlajalise kokkupuute pimorom 2 mg/m3  Komponenter Basis Værdi Kontrolparametre Note Sodium Hydroxide DK OEL L 2 mg/m3  ZZ  ZZ  ZZ  Základ Hodnota Kontrolni parametry Poznámka CZ OEL PEL 1 mg/m3 I. dráždí sliznice (oči, dýchad cesty), respektive kuži  ZY  Συστατικά Sodium Hydroxide CY OEL PEL 1 mg/m3 I. dráždí sliznice (oči, dýchad cesty), respektive kuži  ZY  Συστατικά Bάση Τιμή Παράμετροι ελέγχου Σημείωση  CY OEL M.E.Σ. 2 mg/m3  CH  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter NIOSH, OSHA, St einatembarer Stat NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheit OSHA Stellen Schalen Sch  | Cardinas I hodoredda                            | 51.051                          | OFIL                                    | •                                     |                         |
| Componentes         Base         Valor         Parámetros de control         Nota           Sodium Hydroxide         ES VLA         VLA-EC         2 mg/m3           Komponendid, osad         Alused         Väärtus         Kontrolliparameetrid         Märkused           Sodium Hydroxide         EE OEL         Pilmorm         1 mg/m3         2 mg/m3           DK         Lühişajalise kokkupuute pilmorm         2 mg/m3         Note           DK         Komponenter         Basis         Værdi         Kontrolparametre         Note           Sodium Hydroxide         DK OEL         L         2 mg/m3         I.           22         Slöžky         Základ         Hodnota         Kontrolní parametry         Poznámka           Sodium Hydroxide         C2 OEL         PEL         1 mg/m3         I.           I dráždí sliznice (oči, dýchaci cesty), respektive kúži         2Y           Συστατικά         Bάση         Tjuή         Παράμετροι ελέχου         Σημείωση           Sodium Hydroxide         CY OEL 2         M.Ε.Σ.         2 mg/m3         I.           CH         Inhaltestoffe         Grundlage         Wert         Zu überwachende Parameter         NIOSH, OSHA, Sienater Sienatembarer Stater State State State State State State State State St   | Soaium Hydroxide                                | FI OEL                          | UEIL                                    | ∠ mg/m3                               |                         |
| Sodium Hydroxide   ES VLA   VLA-EC   2 mg/m3   |   |                                 |   | T                                     | T                       |
| Fig.      |   |                                 |   |                                       | Nota                    |
| Komponendid, osad   Alused   Väärtus   Kontrolliparameetrid   Märkused   Sodium Hydroxide   EE OEL   Pilmorm   1 mg/m3   2 mg/m3   Normore   2 mg/m3   Normore   2 mg/m3   Normore   Note       | Sodium Hydroxide                                | ES VLA                          | VLA-EC                                  | 2 mg/m3                               |                         |
| Sodium Hydroxide   EE OEL   Pirinorm   1 mg/m3   EE OEL   Lühiajalise   kokkupuute piirnorm   2 mg/m3   Pirinorm   Pirinorm   2 mg/m3   Pirinorm   Pirinorm   2 mg/m3   Pirinorm   Pirinorm   Pirinorm   2 mg/m3   Pirinorm     |   |                                 |   | _                                     |                         |
| BEE DEL Lühiajalise kökküpüüre piimorm 2 mg/m3    Mathematical Parameter   |   |                                 |   | · · · · · · · · · · · · · · · · · · · | Märkused                |
| DK  Komponenter Basis Værdi Kontrolparametre Note Sodium Hydroxide DK OEL L 2 mg/m3   ZZ  Složky Základ Hodnota Kontrolní parametry Poznámka Sodium Hydroxide CZ OEL PEL 1 mg/m3 I. CZ OEL NPK-P 2 mg/m3 I.  I dráždí sliznice (oči, dýchací cesty), respektíve kůži  ZY  Συστατικά Bάση Τιμή Παράμετροι ελέγχου Σημείωση Sodium Hydroxide CY OEL 2 M.E.Σ. 2 mg/m3  Snijestembarer Stat  CH SUVA MAK-Wert 2 mg/m3 NIOSH OSHA, Steinatembarer Stat  NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheit Sosh Arbeitssicherheit-und Gesundheit Sos Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  SGE  CE-CTABKN OCHOBA CTOЙHOCT Параметри на KOHTPORI SOdium Hydroxide BG OEL TWA 2 mg/m3 Eenexkka KOHTPORI SOdium Hydroxide BG OEL TWA 2 mg/m3 Eenexkka KOHTPORI SOdium Hydroxide BE OEL TGG 8 hr  Zu überwachende Benerkung Benerkung NIOSH OSHA, Steinatembarer Stat KOHTPORI SOdium Hydroxide BG OEL TWA 2 mg/m3 Eenexkka KOHTPORI SOdium Hydroxide BE OEL TGG 8 hr Zu überwachende Bemerkung Eenexkka KOHTPORI SOdium Hydroxide BE OEL TGG 8 hr Zu überwachende Bemerkung Sodium Hydroxide BE OEL TGG 8 hr Zu überwachende Bemerkung Bemerkung Parameter   | Sodium Hydroxide                                |                                 |   |                                       |                         |
| Komponenter   Basis   Værdi   Kontrolparametre   Note   Sodium Hydroxide   DK OEL   L   2 mg/m3  |   | EE OEL                          |   | 2 mg/m3                               |                         |
| Komponenter   Basis   Værdi   Kontrolparametre   Note   Sodium Hydroxide   DK OEL   L   2 mg/m3  | nk  |                                 |   |                                       |                         |
| Složky Základ Hodnota Kontrolní parametry Poznámka Sodium Hydroxide CZ OEL PEL 1 mg/m3 I,  |   | Basis                           | Værdi                                   | Kontrolparametre                      | Note                    |
| Složky Základ Hodnota Kontrolní parametry Poznámka Sodium Hydroxide CZ OEL PEL 1 mg/m3 I.  CZ OEL NPK-P 2 mg/m3 I.  I dráždí sliznice (oči, dýchací cesty), respektive kúži  CY  Συστατικά Βάση Τιμή Παράμετροι ελέγχου Σημείωση Sodium Hydroxide CY OEL 2 M.E.Σ. 2 mg/m3  CH  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter  Sodium Hydroxide CH SUVA MAK-Wert 2 mg/m3 NIOSH, OSHA, Steinatembarer Stat  NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitsbehörde SSC Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G  CLOSEL PEL 1 TWA 2 mg/m3  Sodium Hydroxide BG OEL TWA 2 mg/m3  Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Bemerkung Bemerk  |   | DK OEL                          | L                                       |                                       |                         |
| Složky   | 27  |                                 |   |                                       |                         |
| Sodium Hydroxide   CZ OEL   PEL   1 mg/m3   1,   |   | Základ                          | Hodnota                                 | Kontrolní parametry                   | Poznámka                |
| Tiμή Παράμετροι ελέγχου Σημείωση Sodium Hydroxide Βάση Τiμή Παράμετροι ελέγχου Σημείωση Sodium Hydroxide CY OEL 2 M.Ε.Σ. 2 mg/m3  CH  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter  Sodium Hydroxide CH SUVA MAK-Wert 2 mg/m3 NIOSH, OSHA, Steinatembarer Stat  NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitsbehörde SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G  CЪСТАВКИ ОСНОВА СТОЙНОСТ Параметри на КОНТРОЛ  SODIum Hydroxide BG OEL TWA 2 mg/m3  SODIum Hydroxide BG OEL TWA 2 mg/m3  SODIum Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Bemerkung Sodium Hydroxide Bemerkung Sodium Hydroxide Bemerkung Bemerkung Bemerkung  Bemerkung  Sodium Hydroxide Bemerkung Bemerkung Bemerkung  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Bemerkung Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt  | Sodium Hydroxide                                | CZ OEL                          | PEL                                     | · · · · · · · · · · · · · · · · · · · | l,                      |
| Συστατικά Βάση Τιμή Παράμετροι ελέγχου Σημείωση Sodium Hydroxide CY OEL 2 Μ.Ε.Σ. 2 mg/m3  CH  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter  Sodium Hydroxide CH SUVA MAK-Wert 2 mg/m3 NIOSH, OSHA, St einatembarer Stat  CH SUVA KZGW 2 mg/m3 NIOSH, OSHA, St einatembarer Stat  NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitbehörde SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G  Cъставки Основа Стойност Параметри на контрол Sodium Hydroxide BG OEL TWA 2 mg/m3  Selber Schädigung der Leibesfrucht Schünder Schünd  | 1 dráždí olimpiao (ož                           |                                 |   | 2 mg/m3                               | I,                      |
| ΣυστατικάΒάσηΤιμήΠαράμετροι ελέγχουΣημείωσηSodium HydroxideCY OEL 2M.E.Σ.2 mg/m3ΣημείωσηCHInhaltsstoffeGrundlageWertZu überwachende ParameterBemerkungSodium HydroxideCH SUVAMAK-Wert2 mg/m3NIOSH, OSHA, Steinatembarer StatNIOSHNationales Institut für Arbeitssicherheit und Gesundheit2 mg/m3NIOSH, OSHA, Steinatembarer StatNIOSHNationales Institut für Arbeitssicherheit und GesundheitOSHAArbeitssicherheit-und Gesundheit bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.3GCEEine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.GE3GCEСъставкиOCHOBACTOЙHOCTПараметри на контролБележкаSodium HydroxideBG OELTWA2 mg/m33EBestanddelenBasisWaardeControleparametersOpmerkingSodium HydroxideBE OELTGG 8 hr2 mg/m3ATInhaltsstoffeGrundlageWertZu überwachende<br>ParameterBemerkungSodium HydroxideAT OELMAK-TMW2 mg/m3einatembare Frakt  | ·   | i, dychaci cesty), respektive i | Kuzi                                    |                                       |                         |
| Sodium Hydroxide CY OEL 2 M.E.Σ. 2 mg/m3  CH  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Bemerkung  Sodium Hydroxide CH SUVA MAK-Wert 2 mg/m3 NIOSH, OSHA, Steinatembarer Stat  CH SUVA KZGW 2 mg/m3 NIOSH, OSHA, Steinatembarer Stat  NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitsbehörde SSC Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G  Cъставки Oснова Стойност Параметри на контрол  Sodium Hydroxide BG OEL TWA 2 mg/m3  Selbestanddelen Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Bemerkung Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt   |   | 15/                             | 1- /                                    |                                       | l = <i>(</i>            |
| CH Inhaltsstoffe   |   |                                 |   |                                       | Σημείωση                |
| Inhaltsstoffe Grundlage Wert Zu überwachende Parameter  Sodium Hydroxide CH SUVA MAK-Wert 2 mg/m3 NIOSH, OSHA, Steinatembarer State CH SUVA KZGW 2 mg/m3 NIOSH, OSHA, Steinatembarer State NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitsbehörde SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  GG  CЪСТАВКИ ОСНОВА СТОЙНОСТ Параметри на КОНТРОЛ SOdium Hydroxide BG OEL TWA 2 mg/m3  BESTANDER BESTANDE  | Sodium Hydroxide                                | CY OEL 2                        | M.E.Z.                                  | 2 mg/m3                               |                         |
| Sodium Hydroxide  CH SUVA  MAK-Wert  2 mg/m3  NIOSH, OSHA, Steinatembarer State  CH SUVA  KZGW  2 mg/m3  NIOSH, OSHA, Steinatembarer State  NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit  OSHA Arbeitssicherheit-und Gesundheitsbehörde  SSc Eine Schädigung der Leibesfrucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G  Cъставки  Основа  Стойност  Параметри на контрол  Sodium Hydroxide  BG OEL  TWA  2 mg/m3  Selestanddelen  Basis  Waarde  Controleparameters  Opmerking  Sodium Hydroxide  BE OEL  TGG 8 hr  2 mg/m3  AT  Inhaltsstoffe  Grundlage  Wert  Zu überwachende  Parameter  Sodium Hydroxide  AT OEL  MAK-TMW  2 mg/m3  einatembare Frakt  |   |                                 |   | 1                                     | T = .                   |
| Sodium Hydroxide CH SUVA MAK-Wert 2 mg/m3 NIOSH, OSHA, Steinatembarer Stat CH SUVA KZGW 2 mg/m3 NIOSH, OSHA, Steinatembarer Stat NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitsbehörde SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G Cъставки Oснова Стойност Параметри на контрол Sodium Hydroxide BG OEL TWA 2 mg/m3  SE Bestanddelen Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt  | Inhaltsstoffe                                   | Grundlage                       | Wert                                    |                                       | Bemerkung               |
| CH SUVA KZGW 2 mg/m3 NIOSH, OSHA, St einatembarer Stat.  NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitsbehörde SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G  Съставки Основа Стойност Параметри на контрол Sodium Hydroxide BG OEL TWA 2 mg/m3  Bestanddelen Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt   | Sodium Hydroxide                                | CH SUVA                         | MAK-Wert                                |                                       | NIOSH, OSHA, SSc,       |
| NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit OSHA Arbeitssicherheit-und Gesundheitsbehörde SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G Cъставки Основа Стойност Параметри на контрол Sodium Hydroxide BG OEL TWA 2 mg/m3  3E Bestanddelen Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt   | <u> </u>  | CH SHIVA                        | KZCW                                    | + -                                   | NIOSH, OSHA, SSc,       |
| OSHA Arbeitssicherheit-und Gesundheitsbehörde SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.  3G  Съставки Основа Стойност Параметри на контрол Sodium Hydroxide BG OEL TWA 2 mg/m3  Bestanddelen Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt   | NIOSH Nationales Institut                       |                                 | 1                                       | 2 1119/1113                           | einatembarer Staub      |
| Sodium Hydroxide  BG OEL  TWA  2 mg/m3  Bestanddelen  Basis  Bestanddelen  Basis  Waarde  Controleparameters  Opmerking  TGG 8 hr  2 mg/m3  AT  Inhaltsstoffe  Grundlage  Wert  Zu überwachende  Parameter  Sodium Hydroxide  AT OEL  MAK-TMW  2 mg/m3  einatembare Frakt  | OSHA Arbeitssicherheit-u<br>SSc Eine Schädigung | und Gesundheitsbehörde          |   | nicht befürchtet zu werden.           |                         |
| Sodium Hydroxide BG OEL TWA 2 mg/m3  BESTANDER SODIUM Hydroxide Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt   |   | Основа                          | Стойност                                | · ·                                   | Бележка                 |
| Bestanddelen Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt  | Sodium Hydroxide                                | BG OFI                          | TWA                                     | <del></del>                           |                         |
| Bestanddelen Basis Waarde Controleparameters Opmerking Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt  | -   | I DO OLL                        | 1 | mg/mo                                 | I                       |
| Sodium Hydroxide BE OEL TGG 8 hr 2 mg/m3  AT  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter  Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt  |   | Dania                           | Moordo                                  | Controlonororo                        | Opmorting               |
| AT  Inhaltsstoffe Grundlage Wert Zu überwachende Parameter  Sodium Hydroxide AT OEL MAK-TMW 2 mg/m3 einatembare Frakt  |   |                                 |   | •                                     | Opmerking               |
| Inhaltsstoffe     Grundlage     Wert     Zu überwachende Parameter     Bemerkung       Sodium Hydroxide     AT OEL     MAK-TMW     2 mg/m3     einatembare Frakt   | •   | DL OCL                          | 100 0 111                               | z mymo                                | <u>I</u>                |
| Sodium Hydroxide         AT OEL         MAK-TMW         2 mg/m3         einatembare Frakt  |   | Grundlage                       | Wert                                    | Zu überwachende                       | Bemerkung               |
|  | 0 1 11 1 11                                     |                                 | A444 =                                  |                                       |                         |
| AT OEL   IVIAN-NZVV   4 MIG/MIS   EINATEMBARE FRAK   | Sodium Hydroxide                                |                                 |   |                                       | einatembare Fraktion    |
|  |   | ATOLL                           | WAN-NZVV                                | 1 4 mg/mo                             | elilateribare i faktioi |

## Sodium Methyl Mercaptide

Version 1.13 Revision Date 2025-06-12

## Exposure controls Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

## Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to

maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not

known, or other circumstances where air-purifying respirators

may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed

with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear. Complete head face and neck protection. Rubber

apron. Footwear protecting against chemicals.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9: Physical and chemical properties**

9.1

## Information on basic physical and chemical properties

#### **Appearance**

Form : liquid
Physical state : liquid
Color : Colorless
Odor : Pungent

Safety data

SDS Number:100000013985 9/18

Version 1.13 Revision Date 2025-06-12

Flash point : 29°C (84°F)

Method: Tag closed cup

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : No

Autoignition temperature : No data available

Thermal decomposition : No data available

Molecular formula : CH3SNa

Molecular weight : 70,08 g/mol

pH : > 10

Pour point : No data available

Boiling point/boiling range : Not applicable, Decomposes

Vapor pressure : 20,00 MMHG

at 24°C (75°F)

Relative density : No data available

Density : 1,138 G/ML

at 30°C (86°F)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, kinematic : No data available

Relative vapor density : 1

(Air = 1.0)

Evaporation rate : No data available

Percent volatile : 79 %

9.2

Other information

Conductivity : No data available

## **SECTION 10: Stability and reactivity**

10.1

**Reactivity** : Stable under recommended storage conditions.

SDS Number:100000013985 10/18

## **Sodium Methyl Mercaptide**

Version 1.13 Revision Date 2025-06-12

10.2

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

10.3

Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerization does not

occur.

Hazardous reactions: Vapors may form explosive mixture with

air.

10.4

**Conditions to avoid** : Heat, flames and sparks.

10.5

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

**Thermal decomposition**: No data available

10.6

Hazardous decomposition

products

: Sulfur oxides

Other data : No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

## 11.1

## Information on toxicological effects

**Acute oral toxicity** 

Sodium Methanethiolate : LD50: 581 mg/kg

Species: Rat

Sex: male and female

Method: OECD Test Guideline 401

Acute inhalation toxicity

Sodium Methanethiolate : No data available

**Acute dermal toxicity** 

Sodium Methanethiolate : LD50: > 400 mg/kg

Species: Rat

Sex: male and female

Method: OECD Test Guideline 402

**Sodium Methyl Mercaptide** 

**Skin irritation** : Extremely corrosive and destructive to tissue.

SDS Number:100000013985 11/18

Version 1.13 Revision Date 2025-06-12

Information given is based on tests on the mixture itself.

**Sodium Methyl Mercaptide** 

Eye irritation : Irreversible effects on the eye

**Sodium Methyl Mercaptide** 

Sensitization : Did not cause sensitization on laboratory animals.

Repeated dose toxicity

Sodium Methanethiolate : Species: Rat, male

Sex: male

Application Route: Inhalation Dose: 0, 2, 17, 57 ppm Exposure time: 13 wk

Number of exposures: 7 h/d, 5 d/wk

NOEL: 0,033 mg/l 17 ppm

Lowest observable effect level: 0,118 mg/l 57 ppm

Target Organs: Liver

Information given is based on data obtained from similar

substances.

Species: Rat, male

Sex: male

Application Route: oral gavage Dose: 5, 15, 45 mg/kg/day Exposure time: 8 wk

Number of exposures: once/d, 7 d/wk

NOEL: 15 mg/kg

Lowest observable effect level: 45 mg/kg Method: OECD Test Guideline 422 Target Organs: Blood, spleen

Species: Rat, female

Sex: female

Application Route: oral gavage Dose: 5, 15, 45 mg/kg/day Exposure time: 8 - 9 wk

Number of exposures: once/d, 7 d/wk

NOEL: 15 mg/kg

Lowest observable effect level: 45 mg/kg Method: OECD Test Guideline 422 Target Organs: Blood, spleen

Genotoxicity in vitro

Sodium Methanethiolate : Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Cytogenetic assay

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: Ambiguous

Sodium Hydroxide Test Type: Ames test

Result: negative

SDS Number:100000013985 12/18

Version 1.13 Revision Date 2025-06-12

Test Type: DNA damage and repair assay

Result: negative

Test Type: Mammalian cell gene mutation assay

Result: positive

Genotoxicity in vivo

Sodium Methanethiolate : Test Type: Micronucleus test

> Species: Mouse Cell type: Bone marrow Route of Application: Oral

Method: OECD Test Guideline 474

Result: negative

Sodium Hydroxide Test Type: Mouse micronucleus assay

Result: negative

Reproductive toxicity

Sodium Methanethiolate : Species: Rat

Sex: male

Application Route: oral gavage

Dose: 5, 15, 45 mg/kg Exposure time: 8 wk

Number of exposures: once/d, 7 d/wk Test period: 4 wks premating, mating and...

Method: OECD Guideline 422 NOAEL Parent: > 45 mg/kg NOAEL F1: > 45 mg/kg

Species: Rat Sex: female

Application Route: oral gavage

Dose: 5, 15, 45 mg/kg Exposure time: 8 - 9 wk

Number of exposures: once/d, 7 d/wk Test period: 4 wks premating, mating and...

Method: OECD Guideline 422 NOAEL Parent: > 45 mg/kg NOAEL F1: > 45 mg/kg

**Sodium Methyl Mercaptide** 

**Aspiration toxicity** : No aspiration toxicity classification.

11.2

Information on other hazards

**Sodium Methyl Mercaptide** 

Further information

Endocrine disrupting

properties

: Solvents may degrease the skin.

: The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SDS Number:100000013985 13/18

Version 1.13 Revision Date 2025-06-12

#### **SECTION 12: Ecological information**

#### 12.1

### **Toxicity**

## Toxicity to fish

Sodium Methanethiolate : LC50: 1,8 mg/l

Exposure time: 96 h

Species: Danio rerio (Zebra Fish)

semi-static test Method: OECD Test Guideline 203

## Toxicity to daphnia and other aquatic invertebrates

Sodium Methanethiolate : EC50: 1,32 - 2,46 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Toxicity to algae

Sodium Methanethiolate : ErC50: 15 mg/l

Exposure time: 72 h

Species: Pseudokirchneriella subcapitata (green algae)

static test Method: OECD Test Guideline 201

12.2

## Persistence and degradability

Biodegradability

Sodium Methanethiolate : aerobic

Result: Readily biodegradable.

64 %

Testing period: 28 d

Method: OECD Test Guideline 301D

12.3

## Bioaccumulative potential

Bioaccumulation

Sodium Methanethiolate : This material is not expected to bioaccumulate.

12.4

## Mobility in soil

Mobility

Sodium Methanethiolate : No data available

12.5

#### Results of PBT and vPvB assessment

Results of PBT assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

SDS Number:100000013985 14/18

## Sodium Methyl Mercaptide

Version 1.13 Revision Date 2025-06-12

0.1% or higher.

12.6

**Endocrine disrupting properties** 

Endocrine disrupting properties

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7

Other adverse effects

Additional ecological

information

: Toxic to aquatic life.

12.8

**Additional Information** 

## **Ecotoxicology Assessment**

Short-term (acute) aquatic hazard

Sodium Methanethiolate : Toxic to aquatic life.

Long-term (chronic) aquatic hazard

Sodium Methanethiolate : This product has no known ecotoxicological effects.

## **SECTION 13: Disposal considerations**

#### 13.1

#### Waste treatment methods

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

#### **SECTION 14: Transport information**

#### 14.1 - 14.7

**Transport information** 

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

SDS Number:100000013985 15/18

Version 1.13 Revision Date 2025-06-12

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

#### **US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

UN2920, CORROSIVE LIQUIDS, FLAMMABLE, N.O.S., (SODIUM METHANETHIOLATE, SODIUM HYDROXIDE), 8 (3), I, RQ (SODIUM HYDROXIDE)

#### **IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

UN2920, CORROSIVE LIQUID, FLAMMABLE, N.O.S., (SODIUM METHANETHIOLATE, SODIUM HYDROXIDE), 8 (3), I, (29 °C c.c.)

## IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN2920, CORROSIVE LIQUID, FLAMMABLE, N.O.S., (SODIUM METHANETHIOLATE, SODIUM HYDROXIDE), 8 (3), I

## ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN2920, CORROSIVE LIQUID, FLAMMABLE, N.O.S., (SODIUM METHANETHIOLATE, SODIUM HYDROXIDE), 8 (3), I, (D/E)

# RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

883,UN2920,CORROSIVE LIQUID, FLAMMABLE, N.O.S., (SODIUM METHANETHIOLATE, SODIUM HYDROXIDE), 8 (3), I

# ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN2920, CORROSIVE LIQUID, FLAMMABLE, N.O.S., (SODIUM METHANETHIOLATE, SODIUM HYDROXIDE), 8 (3), I

Maritime transport in bulk according to IMO instruments

### **SECTION 15: Regulatory information**

15.1

# Safety, health and environmental regulations/legislation specific for the substance or mixture National legislation

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Water hazard class (Germany)

: WGK 1 slightly hazardous to water

•

15.2

SDS Number:100000013985 16/18

Version 1.13 Revision Date 2025-06-12

**Major Accident Hazard** 

Legislation

: 96/82/EC Update: 2003

Highly flammable

7b

Quantity 1: 5.000 t Quantity 2: 50.000 t

ZEU SEVES3 Update: FLAMMABLE LIQUIDS

P<sub>5</sub>c

Quantity 1: 5.000 t Quantity 2: 50.000 t

**Notification status** 

Europe REACH Not in compliance with the inventory Switzerland CH INV Not in compliance with the inventory

United States of America (USA) On or in compliance with the active portion of the

TSCA inventory

**TSCA** 

None of the components of this product are on the Canada NDSL

Canadian DSL, but all are on the NDSL Not in compliance with the inventory

Australia AIIC New Zealand NZIoC Not in compliance with the inventory

On the inventory, or in compliance with the inventory Japan ENCS On the inventory, or in compliance with the inventory Japan ISHL Korea KECI All substances in this product were registered, notified

> to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of

Record themselves notified the substances.

Philippines PICCS On the inventory, or in compliance with the inventory Taiwan TCSI On the inventory, or in compliance with the inventory China IECSC On the inventory, or in compliance with the inventory

Other TECI Not in compliance with the inventory

#### **SECTION 16: Other information**

NFPA Classification : Health Hazard: 3

> Fire Hazard: 2 Reactivity Hazard: 0



### **Further information**

Legacy SDS Number : 681520

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

SDS Number:100000013985 17/18

Version 1.13 Revision Date 2025-06-12

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

| ŀ      | Key or legend to abbreviations and a                     | cronyms use | d in the safety data sheet   |
|--------|--|-------------|--|
| ACGIH  | American Conference of Government Industrial Hygienists  | LD50        | Lethal Dose 50%  |
| AIIC   | Australian Inventory of Industrial Chemicals             | LOAEL       | Lowest Observed Adverse Effect<br>Level  |
| DSL    | Canada, Domestic Substances<br>List                      | NFPA        | National Fire Protection Agency  |
| NDSL   | Canada, Non-Domestic<br>Substances List                  | NIOSH       | National Institute for Occupational Safety & Health  |
| CNS    | Central Nervous System                                   | NTP         | National Toxicology Program  |
| CAS    | Chemical Abstract Service                                | NZIoC       | New Zealand Inventory of Chemicals   |
| EC50   | Effective Concentration                                  | NOAEL       | No Observable Adverse Effect Level   |
| EC50   | Effective Concentration 50%                              | NOEC        | No Observed Effect Concentration   |
| EGEST  | EOSCA Generic Exposure<br>Scenario Tool                  | OSHA        | Occupational Safety & Health Administration  |
| EOSCA  | European Oilfield Specialty Chemicals Association        | PEL         | Permissible Exposure Limit   |
| EINECS | European Inventory of Existing Chemical Substances       | PICCS       | Philippines Inventory of Commercial Chemical Substances                                    |
| MAK    | Germany Maximum Concentration Values                     | PRNT        | Presumed Not Toxic   |
| GHS    | Globally Harmonized System                               | RCRA        | Resource Conservation Recovery Act   |
| >=     | Greater Than or Equal To                                 | STEL        | Short-term Exposure Limit  |
| IC50   | Inhibition Concentration 50%                             | SARA        | Superfund Amendments and Reauthorization Act.  |
| IARC   | International Agency for Research on Cancer              | TLV         | Threshold Limit Value  |
| IECSC  | Inventory of Existing Chemical Substances in China       | TWA         | Time Weighted Average  |
| ENCS   | Japan, Inventory of Existing and New Chemical Substances | TSCA        | Toxic Substance Control Act  |
| KECI   | Korea, Existing Chemical Inventory                       | UVCB        | Unknown or Variable Composition,<br>Complex Reaction Products, and<br>Biological Materials |
| <=     | Less Than or Equal To                                    | WHMIS       | Workplace Hazardous Materials<br>Information System  |
| LC50   | Lethal Concentration 50%                                 | ATE         | Acute toxicity estimate  |

## Full text of H-Statements referred to under sections 2 and 3.

| H226 | Flammable liquid and vapor.              |
|------|--|
| H290 | May be corrosive to metals.              |
| H302 | Harmful if swallowed.                    |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage.               |

SDS Number:100000013985 18/18