

Version 1.18 Revision Date 2025-06-16

according to GB/T 16483 and GB/T 17519

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : AlphaPlus® 1-Octene

Material : 1128499, 1117428, 1064097, 1021765, 1015426, 1037082

Use : Monomer

Company : Chevron Phillips Chemical Company LP

Normal Alpha Olefins (NAO)

9500 Lakeside Blvd.

The Woodlands, TX 77381

Emergency telephone:

Health:

866.442.9628 (North America) 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week) Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: POISON CENTER MILÂN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico "Agostino Gemelli", Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

SDS Number:100000068580

Version 1.18 Revision Date 2025-06-16

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371

67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000 Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606 Slovakia: +421 2 5477 4166 Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24

hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com Website : www.CPChem.com

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS Classification and Labeling: Follow GB 13690, GB 15258 and GB 30000.2 to GB 30000.29 (GHS 2013)

Emergency Overview

Danger

Form: liquid Physical state: liquid Color: Clear, colorless Odor: No information

available.

Hazards : Highly flammable liquid and vapor. May be harmful if inhaled.

May be harmful in contact with skin. Causes mild skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Very toxic to aquatic life. Very toxic to aquatic life with long lasting

effects.

Classification

: Flammable liquids, Category 2 Acute toxicity, Category 5, Inhalation Acute toxicity, Category 5, Dermal

Skin corrosion/irritation, Category 3

Serious eye damage/eye irritation, Category 2A

Specific target organ toxicity - single exposure, Category 3,

Narcotic effects

Aspiration hazard, Category 1

Short-term (acute) aquatic hazard, Category 1 Long-term (chronic) aquatic hazard, Category 1

Labeling

SDS Number:100000068580 2/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

Symbol(s)









Signal Word : Danger

Hazard Statements : H225: Highly flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H313 + H333: May be harmful in contact with skin or if inhaled.

H316: Causes mild skin irritation. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements : Prevention:

P210: Keep away from heat/ sparks/ open flames/ hot

surfaces. No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P264: Wash skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/ eye protection/ face protection.

Response:

P301+P310: IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P312: IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.

P304 + P340 + P312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/ doctor if you feel unwell.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER/doctor if you feel unwell.

P331: Do NOT induce vomiting.

P332 + P313: If skin irritation occurs: Get medical advice/

attention.

P337 + P313: If eye irritation persists: Get medical advice/

attention.

P370+P378: In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391: Collect spillage.

Storage:

P403 + P233: Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/ container to an approved waste

disposal plant.

Version 1.18 Revision Date 2025-06-16

SECTION 3: Composition/information on ingredients

Synonyms : Octene-n-1

Octene-1 (C8) AlphaPlus™ NAO 8

C8H16

Molecular formula : C8H16

Chemical name	CAS-No. / EINECS-No.	Concentration
		[wt%]
1-Octene	111-66-0	95 - 100
2-Ethyl-1-Hexene	1632-16-2	1 - 5

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data

sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious,

place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well

with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact

lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

an unconscious person. If symptoms persist, call a physician.

Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : 13° C (55°F)

Method: Tag closed cup

Autoignition temperature : 221°C (430°F)

Suitable extinguishing

media

: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing

media

: High volume water jet.

Specific hazards during fire

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Special protective : Wear self-contained breathing apparatus for firefighting if

SDS Number:100000068580 4/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

equipment for fire-fighters

necessary.

Further information

: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion

protection

 Do not spray on a naked flame or any incandescent material.
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

surfaces and sources of ignition.

Hazardous decomposition

products

: Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate

ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low

areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage

or spillage if safe to do so. If the product contaminates rivers

and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7: Handling and storage

Handling

Advice on safe handling

Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. Review all operations, which have the potential to generating and accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum

gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106 "Flammable and Combustible Liquids"; National Fire Protection Association (NFPA 77), "Recommended Practice on Static Electricity"; and/or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising Out of Static, Lightning, and stray Currents". Avoid formation of aerosol. Do not breathe vapors/dust. Avoid

exposure - obtain special instructions before use. Avoid

SDS Number:100000068580 5/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers

No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Monomer

SECTION 8: Exposure controls/personal protection

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection

If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection

The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the

SDS Number:100000068580 6/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic

footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Form : liquid Physical state : liquid

Color : Clear, colorless

Odor : No information available.

Odor Threshold : No data available

Safety data

Flash point : 13°C (55°F)

Method: Tag closed cup

Lower explosion limit : 0.7 %(V)

Upper explosion limit : 6.8 %(V)

Oxidizing properties : no

Autoignition temperature : 221°C (430°F)

Molecular formula : C8H16

Molecular weight : 112.24 g/mol

pH : No data available

Pour point : Not applicable

Melting point/freezing point -102°C (-152°F)

Boiling point/boiling range : 121°C (250°F)

Vapor pressure : 1.75 kPa

at 20°C (68°F)

15.30 kPa at 65°C (149°F)

SDS Number:100000068580 7/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

Relative density : 0.72

at 15.6 °C (60.1 °F)

: 719 kg/m3 Density

at 15°C (59°F)

710 kg/m3 at 20°C (68°F)

690 kg/m3 at 50°C (122°F)

Water solubility : Soluble in hydrocarbon solvents; insoluble in water.

Partition coefficient: n-

octanol/water

: No data available

: 0.38 cSt

Viscosity, kinematic

at 40°C (104°F)

Relative vapor density : 3.9

(Air = 1.0)

Evaporation rate : No data available

Percent volatile : > 99 %

Conductivity : 2.9 pSm

Method: ASTM D4308

SECTION 10: Stability and reactivity

Reactivity : Stable at normal ambient temperature and pressure.

Chemical stability : This material is considered stable under normal ambient and

anticipated storage and handling conditions of temperature

and pressure.

Possibility of hazardous reactions

Hazardous reactions : Hazardous reactions: Hazardous polymerization does not

occur.

Further information: No decomposition if stored and applied as

directed.

Hazardous reactions: Vapors may form explosive mixture with

Conditions to avoid : Heat, sparks, fire, and oxidizing agents.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as

chlorates, nitrates, peroxides, etc.

Hazardous decomposition : Carbon oxides

SDS Number:100000068580 8/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

products

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Acute oral toxicity

1-Octene : LD50: > 10,000 mg/kg

Species: Rat

Sex: male and female Method: Fixed Dose Method

AlphaPlus® 1-Octene

Acute inhalation toxicity : Acute toxicity estimate: 26.04 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

AlphaPlus® 1-Octene

Acute dermal toxicity : Acute toxicity estimate: 2,605 mg/kg

Method: Calculation method

AlphaPlus® 1-Octene

Skin irritation : Mild skin irritation

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of

the skin.

AlphaPlus® 1-Octene

Eye irritation : No eye irritation.

AlphaPlus® 1-Octene

Sensitization : Did not cause sensitization on laboratory animals.

Did not cause sensitization on laboratory animals.

Repeated dose toxicity

1-Octene : Species: Rat, Male and female

Sex: Male and female Application Route: Oral diet Dose: 0, 100, 500, 1000 mg/kg

Exposure time: 13 wk Number of exposures: daily NOEL: 1,000 mg/kg

Method: OCED Guideline 408

Information given is based on data obtained from similar

substances.

SDS Number:100000068580 9/14

Version 1.18 Revision Date 2025-06-16

Species: Rat, Male and female

Sex: Male and female Application Route: Inhalation Dose: 0, 300, 1000, 3000 ppm

Exposure time: 13 wk

Number of exposures: 6 hrs/d, 5 d/wk

NOEL: 3000 ppm

Method: OECD Guideline 413

Information given is based on data obtained from similar

substances.

Genotoxicity in vitro

1-Octene : Test Type: Ames test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: Cell transformation assay

Result: negative

Genotoxicity in vivo

1-Octene : Remarks: Not classified due to data which are conclusive

although insufficient for classification.

Reproductive toxicity

1-Octene : Species: Rat

Sex: male

Application Route: Oral diet Dose: 0, 100, 500, or 1000 mg/kg

Exposure time: 44 D Number of exposures: daily Method: OECD Guideline 421 NOAEL Parent: 1,000 mg/kg NOAEL F1: 1,000 mg/kg

Species: Rat Sex: female

Application Route: Oral diet Dose: 0, 100, 500, or 1000 mg/kg

Exposure time: 41-55 D Number of exposures: daily Method: OECD Guideline 421 NOAEL Parent: 1,000 mg/kg NOAEL F1: 1,000 mg/kg

AlphaPlus® 1-Octene

Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

1-Octene : Carcinogenicity: Not available

Mutagenicity: Tests on bacterial or mammalian cell cultures

did not show mutagenic effects. Teratogenicity: Not available

SDS Number:100000068580 10/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

Reproductive toxicity: Animal testing did not show any effects

on fertility.

AlphaPlus® 1-Octene

Further information : Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents

may degrease the skin.

SECTION 12: Ecological information

Toxicity to fish

1-Octene : LC50: 0.87 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar

substances.

Toxicity to daphnia and other aquatic invertebrates

1-Octene : EC50: 1 mg/l

Exposure time: 48 h

Species: Daphnia magna (Water flea) static test Method: OECD Test Guideline 202

Information given is based on data obtained from similar

substances.

Toxicity to algae

1-Octene : EC50: 1 - 10 mg/l

Exposure time: 96 h

Species: Pseudokirchneriella subcapitata (microalgae)

Method: OECD Test Guideline 201

Information given is based on data obtained from similar

substances.

M-Factor

oct-1-ene : M-Factor (Acute Aquat. Tox.) 1

Biodegradability : This material is expected to be readily biodegradable.

Elimination information (persistence and degradability)

Bioaccumulation

1-Octene : Bioconcentration factor (BCF): 1,259

Method: QSAR modeled data

Mobility

1-Octene : No data available

SDS Number:100000068580 11/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

Results of PBT assessment

1-Octene : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological

information

: Very toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life

with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: Very toxic to aquatic life.

Long-term (chronic) aquatic

hazard

: Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

Do not re-use empty containers. Do not burn, or use a cutting

torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, (13 °C c.c.), MARINE POLLUTANT, (1-OCTENE)

SDS Number:100000068580 12/14

Version 1.18 Revision Date 2025-06-16

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (1-OCTENE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33,UN3295,HYDROCARBONS, LIQUID, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (1-OCTENE)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (1-OCTENE)

Other information : Octene (all isomers), S.T.2, Cat. Y

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

Classification and Labeling of

Commonly Used Dangerous Chemical Substances : Primary label: Combustible Liquid.

Notification status

Europe REACH : This product is in full compliance according to REACH

regulation 1907/2006/EC.

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) : On or in compliance with the active portion of the

TSCA TSCA inventory

Canada DSL : All components of this product are on the Canadian

DSL

Australia AIIC : On the inventory, or in compliance with the inventory
Japan ENCS : On the inventory, or in compliance with the inventory
New Zealand NZIoC : On the inventory, or in compliance with the inventory
Philippines PICCS : On the inventory, or in compliance with the inventory

Korea KECI : All substances in this product were registered, notified

to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was

included on CPChem's notifications or if the Importer of

Record themselves notified the substances.

Taiwan TCSI : On the inventory, or in compliance with the inventory China IECSC : On the inventory, or in compliance with the inventory

SDS Number:100000068580 13/14

AlphaPlus® 1-Octene

Version 1.18 Revision Date 2025-06-16

SECTION 16: Other information

Further information

Legacy SDS Number : PE0017

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

SDS Number:100000068580 14/14