

**SCENTINEL® S-20 Gas Odorant**

Version 2.4

Revision Date 2025-07-17

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : SCENTINEL® S-20 Gas Odorant
Material : 1096889, 1098465, 1024714, 1024715, 1024716, 1024722,
1024719, 1024718, 1024717, 1024713, 1024721, 1033064,
1024720
Use : Odorant
Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
9500 Lakeside Blvd.
The Woodlands, TX 77381

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

ODOR-FADE WARNING

A GAS LEAK CAN CAUSE A FIRE OR EXPLOSION RESULTING IN SERIOUS INJURY OR DEATH.

Be aware that the stenching chemical added to gas to make it detectable may not warn of a gas leak or the presence of propane or natural gas to all persons in every instance.

Instances where the odorant in an odorized gas may be undetectable include:

- Odor intensity may fade or be eliminated for a variety of chemical and physical causes, including the oxidation of rusting pipes, adsorption into or sticking onto the interior of pipes or appliances, or absorption into liquids.
- Contact with soil in underground leaks may de-odorize or remove odorant from the gas.
- Some people have a diminished ability, or inability to smell the stench. Factors that negatively affect a person's sense of smell include age, gender, medical conditions, and alcohol/tobacco usage.
- The stench of odorized gas may not awaken sleeping persons.
- Other odors may mask or hide the stench.
- Exposure to the odor for even a short period of time, may cause nasal fatigue, where a person can no longer smell the stench.

Gas detectors listed by the Underwriters Laboratories (UL) can be used as an extra measure of safety for detecting gas leaks, especially under conditions where the odorant alone may not provide an adequate warning. Gas detectors emit a loud, shrill sound when gas is present and do not depend on sense of smell. Because the odor intensity can fade or people may have problems with their sense of smell, we recommend installing, per manufacturer's instructions, one or more

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

combustible gas detectors, in suitable locations to ensure adequate coverage to detect gas leaks.

Educate yourself, your employees, and your customers with the content of this warning and other important facts associated with the so-called "odor-fade phenomenon."

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 2
Eye irritation, Category 2A
Skin sensitization, Category 1

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.

Precautionary Statements

: **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P235 Store in a well-ventilated place. Keep cool.

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Symptoms of Overexposure : No data available

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3: Composition/information on ingredientsSynonyms : Gas Odorant
Mixture of t-butyl mercaptan and methy ethyl sulfide
Mercaptan Mixture

Molecular formula : Mixture

Component	CAS-No.	Weight %
t-Butyl Mercaptan	75-66-1	76 - 80
Methyl Ethyl Sulfide	624-89-5	20 - 24

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Notes to physician

Symptoms : No data available.

Risks : No data available.

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Treatment : No data available.

SECTION 5: Firefighting measures

Flash point : -26--15°C (-15-5°F)
estimated

Autoignition temperature : No data available

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Odorant

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
t-Butyl Mercaptan	Manufacturer	TWA	0.5 ppm,	

US

Components	Basis	Value	Control parameters	Note
------------	-------	-------	--------------------	------

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate. Remove and wash contaminated clothing before re-use. Skin should be washed after contact. Footwear protecting against chemicals.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : liquid
- Physical state : liquid
- Color : Clear
- Odor : Repulsive
- Odor Threshold : No data available

Safety data

- Flash point : -26--15°C (-15-5°F)
estimated
- Lower explosion limit : Not applicable
- Upper explosion limit : Not applicable
- Oxidizing properties : no
- Autoignition temperature : No data available
- Thermal decomposition : No data available

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Molecular formula	: Mixture
Molecular weight	: Not applicable
pH	: Not applicable
Pour point	: <-54°C (<-65°F)
Boiling point/boiling range	: 63-68°C (145-154°F)
Vapor pressure	: 5.70 PSI at 38°C (100°F)
Relative density	: 0.813 at 16 °C (61 °F)
Density	: 6.78 L/G
Water solubility	: slightly soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity, dynamic	: 0.5 cP at 16°C (60°F)
Relative vapor density	: 3 (Air = 1.0)
Evaporation rate	: 1
Percent volatile	: > 99 %
Conductivity	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Stable at normal ambient temperature and pressure.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur. Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Thermal decomposition : No data available

Hazardous decomposition products : Carbon oxides
Sulfur oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**SCENTINEL® S-20 Gas Odorant**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

SCENTINEL® S-20 Gas Odorant

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

SCENTINEL® S-20 Gas Odorant

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

SCENTINEL® S-20 Gas Odorant

Skin irritation : May cause skin irritation and/or dermatitis.

SCENTINEL® S-20 Gas Odorant

Eye irritation : Eye irritation
largely based on animal evidence.

SCENTINEL® S-20 Gas Odorant

Sensitization : Causes sensitization. largely based on animal evidence.

Repeated dose toxicity

t-Butyl Mercaptan : Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 9, 97, 196 ppm
Exposure time: 13 wks
Number of exposures: 6 hrs/d, 5 d/wk
NOEL: > 196 ppm

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Species: Rat, Male and female
 Sex: Male and female
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Exposure time: 42-53 days
 Number of exposures: Daily
 NOEL: 50 mg/kg bw/day
 Lowest observable effect level: 200 mg/kg bw/day
 Method: OECD Guideline 422

Species: Rat, Male and female
 Sex: Male and female
 Application Route: Inhalation
 Dose: 25.1, 99.6, 403.4 ppm
 Exposure time: 13 wks
 Number of exposures: 6 hrs/d, 5 d/wk
 NOEL: 99.6 ppm
 Lowest observable effect level: 403.4 ppm
 Method: OECD Guideline 413
 Target Organs: Liver, Kidney, Blood, Upper respiratory tract
 Information given is based on data obtained from similar substances.

Genotoxicity in vitro

t-Butyl Mercaptan

: Test Type: Ames test
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Mouse lymphoma assay
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative

Test Type: Sister Chromatid Exchange Assay
 Metabolic activation: with and without metabolic activation
 Result: negative

Methyl Ethyl Sulfide

Test Type: Ames test
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Test Guideline 473
 Result: negative

Genotoxicity in vivo

t-Butyl Mercaptan

: Test Type: Mouse micronucleus assay
 Species: Mouse
 Dose: 1250, 2500, 5000 mg/kg
 Method: OECD Test Guideline 474
 Result: negative

Reproductive toxicity

t-Butyl Mercaptan

: Species: Rat

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Sex: male and female
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/day
Number of exposures: Daily
Test period: 42 -53 days
Method: OECD Guideline 422
NOAEL Parent: 200 mg/kg bw/day
NOAEL F1: 50 mg/kg bw/day
No adverse effects expected

Developmental Toxicity

t-Butyl Mercaptan

: Species: Mouse
Application Route: Inhalation
Dose: 11, 99, 195 ppm
Exposure time: GD 6-16
Number of exposures: 6 hrs/d
NOAEL Teratogenicity: > = 195 ppm
NOAEL Maternal: > = 195 ppm

Species: Rat
Application Route: Inhalation
Dose: 11, 99, 195 ppm
Exposure time: GD6-19
Number of exposures: 6 hrs/d
NOAEL Teratogenicity: > =195 ppm
NOAEL Maternal: > = 195 ppm

Species: Rat
Application Route: oral gavage
Dose: 10, 50, 200 mg/kg bw/day
Exposure time: 42-53 days
Number of exposures: Daily
NOAEL Teratogenicity: 50 mg/kg bw /day
NOAEL Maternal: 200 mg/kg bw /day

SCENTINEL® S-20 Gas Odorant

Aspiration toxicity : May be harmful if swallowed and enters airways.

CMR effects

t-Butyl Mercaptan

: Carcinogenicity: Not available
Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects
Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

SCENTINEL® S-20 Gas Odorant

Further information : Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

t-Butyl Mercaptan

: LC50: 34 mg/l
Exposure time: 96 h

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Species: Oncorhynchus mykiss (rainbow trout)
semi-static test Method: OECD Test Guideline 203

Methyl Ethyl Sulfide

LC50: > 49.8 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

t-Butyl Mercaptan

: EC50: 6.7 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
static test Method: OECD Test Guideline 202

Methyl Ethyl Sulfide

EC50: 16 mg/l
Exposure time: 48 h
Species: Daphnia
Method: OECD Test Guideline 202

Toxicity to algae

t-Butyl Mercaptan

: EC50: 24 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (green algae)
Method: OECD Test Guideline 201

Methyl Ethyl Sulfide

ErC50: > 500 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (green algae)
Method: OECD Test Guideline 201

EbC50: 310 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (green algae)
Method: OECD Test Guideline 201

Toxicity to bacteria

Methyl Ethyl Sulfide

: EC50: > 1,000 mg/l
Exposure time: 3 h
Species: Bacteria
Respiration inhibition
Method: OECD Test Guideline 209

Biodegradability

t-Butyl Mercaptan

: aerobic
Result: Not readily biodegradable.
6 %
Testing period: 63 d
Method: OECD Test Guideline 301

Methyl Ethyl Sulfide

: aerobic
41 %
Testing period: 28 d

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Method: OECD Test Guideline 301D
According to the results of tests of biodegradability this product is not readily biodegradable.

: aerobic
92 %
Testing period: 31 d
Method: OECD Test Guideline 301D
Expected to be inherently biodegradable.

Bioaccumulation

t-Butyl Mercaptan : Bioconcentration factor (BCF): 12
Method: QSAR modeled data
This material is not expected to bioaccumulate.

Methyl Ethyl Sulfide : This material is not expected to bioaccumulate.

Mobility

t-Butyl Mercaptan : Method: Calculation, Mackay Level III Fugacity Model
The product will be dispersed amongst the various environmental compartments (soil/ water/ air).

Methyl Ethyl Sulfide : The product evaporates readily.

Results of PBT assessment

t-Butyl Mercaptan : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment**Short-term (acute) aquatic hazard**

t-Butyl Mercaptan : Toxic to aquatic life.

Methyl Ethyl Sulfide : Harmful to aquatic life.

Long-term (chronic) aquatic hazard

t-Butyl Mercaptan : Toxic to aquatic life with long lasting effects.

Methyl Ethyl Sulfide : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

- Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, (-26 - -15 °C c.c.), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33, UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN3336, MERCAPTAN MIXTURE, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, METHYL ETHYL SULFIDE), 3, II, ENVIRONMENTALLY HAZARDOUS, (TERTIARY BUTYL MERCAPTAN)

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Serious eye damage or eye irritation

CERCLA Reportable Quantity : Calculated RQ exceeds reasonably attainable upper limit.
Ethyl Chloride

SARA 302 Reportable Quantity :
This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

US State Regulations

Pennsylvania Right To Know

: t-Butyl Mercaptan - 75-66-1
 Methyl Ethyl Sulfide - 624-89-5
 Ethyl Chloride - 75-00-3

California Prop. 65
Components

: WARNING! This product contains a chemical known in the
 State of California to cause cancer.
 Ethyl Chloride 75-00-3

Notification status

Europe REACH

: A substance or substances in this product is not
 registered or notified to be registered. Importation or
 manufacture of this product is still permitted provided
 that it does not exceed the REACH minimum threshold
 quantity of the non-regulated substances.

Switzerland CH INV

: Not in compliance with the inventory

United States of America (USA)
TSCA

: On or in compliance with the active portion of the
 TSCA inventory

Canada DSL

: All components of this product are on the Canadian
 DSL

Australia AIIC

: On the inventory, or in compliance with the inventory

New Zealand NZIoC

: Not in compliance with the inventory

Japan ENCS

: On the inventory, or in compliance with the inventory

Korea KECI

: A substance(s) in this product was not registered,
 notified to be registered, or exempted from registration
 by CPChem according to K-REACH regulations.

Philippines PICCS

: On the inventory, or in compliance with the inventory

Taiwan TCSI


: On the inventory, or in compliance with the inventory

China IECSC

: On the inventory, or in compliance with the inventory

SECTION 16: Other information**NFPA Classification**

: Health Hazard: 2
 Fire Hazard: 3
 Reactivity Hazard: 0



SCENTINEL® S-20 Gas Odorant

Version 2.4

Revision Date 2025-07-17

Further information

Legacy SDS Number : 34330

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AiIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate