

**Styrene**

Version 2.3

Revision Date 2025-09-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Styrene
Material : 1037612, 1037607, 1037608, 1037609
Company : Chevron Phillips Chemical Company LP
9500 Lakeside Blvd.
The Woodlands, TX 77381

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02

66101029; POISON CENTER ROME – Policlinico "Agostino Gemelli", Servizio di tossicologia

clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù

Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000;

POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326;

POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870;

POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055

7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382

24444; POISON CENTER BERGAMO – Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883

300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011

858;

Styrene

Version 2.3

Revision Date 2025-09-29

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)
 Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Lithuania: +370 (85) 2362052
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
 Malta: +356 2395 2000
 The Netherlands: NVIC: +31 (0)88 755 8000
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Portugal: CIAV phone number: +351 800 250 250
 Romania: +40213183606
 Slovakia: +421 2 5477 4166
 Slovenia: Phone number: 112
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)
 Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 3
 Skin irritation, Category 2
 Eye irritation, Category 2A
 Specific target organ toxicity - repeated exposure, Category 1,
 Inhalation, Auditory organs
 Aspiration hazard, Category 1

Labeling

Symbol(s) : 

Signal Word : Danger

Hazard Statements : H226: Flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H372: Causes damage to organs (Auditory organs) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/

Styrene

Version 2.3

Revision Date 2025-09-29

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

Group 2A: Probably carcinogenic to humans

Styrene 100-42-5

NTP

Reasonably anticipated to be a human carcinogen

Styrene 100-42-5

SECTION 3: Composition/information on ingredients

Synonyms : Inhibited Styrene
Phenylethylene
Benzene, Ethenyl
Styrol
Cinnamene
Vinylbenzene
Styrolene
Styrene Monomer

Molecular formula : C₈H₈

Styrene

Version 2.3

Revision Date 2025-09-29

Component	CAS-No.	Weight %
Styrene	100-42-5	99.9 - 100

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

- Flash point : 31°C (88°F)
Method: closed cup
- Autoignition temperature : 490°C (914°F)
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away

Styrene

Version 2.3

Revision Date 2025-09-29

from open flames, hot surfaces and sources of ignition.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Storage

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Components	Basis	Value	Control parameters	Note
Styrene	OSHA Z-2	TWA	100 ppm,	
	OSHA Z-2	CEIL	200 ppm,	
	OSHA Z-2	Peak	600 ppm,	
	OSHA Z-1-A	TWA	50 ppm, 215 mg/m3	
	OSHA Z-1-A	STEL	100 ppm, 425 mg/m3	

Styrene

Version 2.3

Revision Date 2025-09-29

	ACGIH	TWA	10 ppm,	OTO, A3,
	ACGIH	STEL	20 ppm,	OTO, A3,

A3 Confirmed animal carcinogen with unknown relevance to humans
OTO Ototoxicant

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Styrene	100-42-5	Immediately Dangerous to Life or Health Concentration Value 700 parts per million	1995-03-01

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties**

Styrene

Version 2.3

Revision Date 2025-09-29

Appearance

Physical state : liquid
Color : Colorless
Odor : Sweet

Safety data

Flash point : 31°C (88°F)
Method: closed cup

Lower explosion limit : 0.9 %(V)

Upper explosion limit : 6.8 %(V)

Oxidizing properties : no

Autoignition temperature : 490°C (914°F)

Molecular formula : C₈H₈

Molecular weight : 104.16 g/mol

pH : Not applicable

Freezing point : -30.63°C (-23.13°F)

Pour point : No data available

Boiling point/boiling range : 145.15°C (293.27°F)

Vapor pressure : 4.50 MMHG
at 20°C (68°F)

Relative density : 0.91
at 20 °C (68 °F)

Water solubility : 0.029 wt.% styrene in water @ 20 °C (68°F)

Partition coefficient: n-octanol/water : log Pow: 2.96
at 25°C (77°F)

Viscosity, dynamic : 0.763 cP

Relative vapor density : 3.6
(Air = 1.0)

Evaporation rate : No data available

Conductivity : < 50 pSm

SECTION 10: Stability and reactivity

Styrene

Version 2.3

Revision Date 2025-09-29

- Reactivity** : Stable at normal ambient temperature and pressure.
- Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
- Possibility of hazardous reactions**
- Hazardous reactions** : Further information: No decomposition if stored and applied as directed.
Hazardous reactions: Vapors may form explosive mixture with air.
- Conditions to avoid** : Heat, flames and sparks.
- Materials to avoid** : No data available.
- Other data** : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

- Styrene : LD50: > 5,000 mg/kg
Species: Rat
Sex: male and female

Styrene

- Acute inhalation toxicity** : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Styrene

- Acute dermal toxicity** : Acute toxicity estimate: 2,500 mg/kg
Method: Calculation method

Styrene

- Skin irritation** : May cause skin irritation in susceptible persons.

Styrene

- Eye irritation** : May cause irreversible eye damage.

Sensitization

- Styrene : Classification: Does not cause skin sensitization.
largely based on human evidence.

Repeated dose toxicity

- Styrene : Species: Mouse, Male and female
Sex: Male and female

Styrene

Version 2.3

Revision Date 2025-09-29

Application Route: Oral
Dose: 0. 150, 300 mg/kg
Exposure time: 78 wk
Number of exposures: 5 d/wk
NOEL: 150 mg/kg
Lowest observable effect level: 300 mg/kg

Species: Rat, male
Sex: male
Application Route: Inhalation
Dose: 0. 500, 650, 850, 1000 ppm
Exposure time: 4 wk
Number of exposures: 6 h/d, 5 d/wk
NOEL: 500 ppm
Target Organs: Ototoxicity

Genotoxicity in vitro

Styrene

: Test Type: Ames test
Result: negative

Test Type: Cytogenetic assay
Result: positive

Test Type: Reverse mutation assay
Result: negative

Test Type: Mouse lymphoma assay
Result: negative

Test Type: Sister Chromatid Exchange Assay
Result: positive

Test Type: Mammalian cell gene mutation assay
Result: negative

Genotoxicity in vivo

Styrene

: Remarks: No significant adverse effects were reported

Aspiration toxicity

Styrene

: May be fatal if swallowed and enters airways.

CMR effects

Styrene

: Carcinogenicity: This substance has been reported to cause tumors in certain animal species.
Mutagenicity: In vitro tests showed mutagenic effects which were not observed with in vivo test.
Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.
Reproductive toxicity: No toxicity to reproduction

Styrene**Further information**

: Solvents may degrease the skin.

Styrene

Version 2.3

Revision Date 2025-09-29

SECTION 12: Ecological information**Ecotoxicity effects****Toxicity to fish**

Styrene : LC50: 4.02 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)
flow-through test Test substance: yes
Toxic to fish.

Toxicity to daphnia and other aquatic invertebrates

Styrene : EC50: 4.7 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
flow-through test

Toxicity to algae

Styrene : EC50: 4.9 mg/l
Exposure time: 72 h
Species: Selenastrum capricornutum (algae)

Toxicity to bacteria

Styrene : EC10: 0.28 mg/l
Exposure time: 96 h
Growth rate
Species: Skeletonema costatum (Marine Algae)
Test substance: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Styrene : NOEC: 1.01 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
semi-static test
Test substance: yes
Method: OECD Test Guideline 211

Biodegradability

Styrene : According to the results of tests of biodegradability this product is considered as being readily biodegradable.

Elimination information (persistence and degradability)**Bioaccumulation**

Styrene : Does not significantly accumulate in organisms.

Mobility : Medium: Soil

Styrene

Version 2.3

Revision Date 2025-09-29

Method: Calculation, Mackay Level I Fugacity Model
Content: 0.09 %

Medium: Water
Method: Calculation, Mackay Level I Fugacity Model
Content: 1.21 %

Medium: Air
Method: Calculation, Mackay Level I Fugacity Model
Content: 98.6 %

Medium: Biota
Method: Calculation, Mackay Level I Fugacity Model
Content: 0 %

Results of PBT assessment
Styrene

: Not very persistent and very bioaccumulative (vPvB)., Not persistent, bioaccumulative, and toxic (PBT).

Additional ecological
information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping

Styrene

Version 2.3

Revision Date 2025-09-29

description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)
UN2055, STYRENE MONOMER, STABILIZED, 3, III, RQ (STYRENE)

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)
UN2055, STYRENE MONOMER, STABILIZED, 3, III, (31 °C c.c.)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)
UN2055, STYRENE MONOMER, STABILIZED, 3, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))
UN2055, STYRENE MONOMER, STABILIZED, 3, III, (D/E)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))
39,UN2055,STYRENE MONOMER, STABILIZED, 3, III

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)
UN2055, STYRENE MONOMER, STABILIZED, 3, III, ENVIRONMENTALLY HAZARDOUS, (STYRENE)
For Tank Vessels and/or Barges:
UN2055, STYRENE MONOMER, STABILIZED, 3, (UNST., N3), III, ENVIRONMENTALLY HAZARDOUS, (STYRENE)

Other information	: Styrene Monomer, S.T.3, Cat. Y
--------------------------	---

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

National legislation

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

CERCLA Reportable Quantity : 1000 lbs
Styrene

Styrene

Version 2.3

Revision Date 2025-09-29

- SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.
- SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.
- SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.
- SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:
: Styrene - 100-42-5

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):
: Styrene - 100-42-5

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):
: Styrene - 100-42-5

US State Regulations

Pennsylvania Right To Know : Styrene - 100-42-5
Cumene - 98-82-8

California Prop. 65 Components : WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov/food.

Styrene	100-42-5
α-Methylstyrene	98-83-9
Cumene	98-82-8
Ethylbenzene	100-41-4
Benzene	71-43-2

Styrene

Version 2.3

Revision Date 2025-09-29

WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Toluene
Benzene


108-88-3
71-43-2

Notification status

Europe REACH	:	On the inventory, or in compliance with the inventory
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AIIC	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Japan ISHL	:	On the inventory, or in compliance with the inventory
Korea KECI	:	Not in compliance with the inventory
Philippines PICCS	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
Other TECI	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 2



Revision Date : 2025-09-29
Date of last issue : 2022-04-04

Further information

Legacy SDS Number : CPC00089

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Styrene

Version 2.3

Revision Date 2025-09-29

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate