

**TrusTec™ Diesel Reference Fuel T-36**

Version 2.2

Revision Date 2025-10-23

MSDS number: AA00974-0000000616

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product Name : TrusTec™ Diesel Reference Fuel T-36
Material : 1024272, 1108916, 1024276, 1024273, 1024274, 1024275,
1032194

Recommended use of the product : Reference Fuel
Restrictions on use : None known.

Address : Chevron Phillips Chemical Company LP
Specialty Chemicals
9500 Lakeside Blvd.
The Woodlands, TX 77381

Address : CHEVRON PHILLIPS CHEMICALS ASIA PTE. LTD.
C/O DONG WOO CORPORATION
#B-2601, JEONGJAIL-RO,
BUNDANG-GU, SEONGNAMI-SI,
GYEONGGI-DO, 13557
SOUTH KOREA
Telephone no.: +612-9186-1132

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Bulgaria: +359 2 9154 233
 Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
 Cyprus: 1401
 Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
 Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212
 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Finland: 0800 147 111 09 471 977 (24 hours/day)
 France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
 Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
 Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
 Iceland: 543 2222 (24 hours/day, 7 days/week)
 Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;
 Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)
 Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Lithuania: +370 (85) 2362052
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
 Malta: +356 2395 2000
 The Netherlands: NVIC: +31 (0)88 755 8000
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Portugal: CIAV phone number: +351 800 250 250
 Romania: +40213183606
 Slovakia: +421 2 5477 4166
 Slovenia: Phone number: 112
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)
 Sweden: 112 – ask for Poisons Information

Organization that prepared : Product Safety and Toxicology Group
the SDS

E-mail address : SDS@CPChem.com

Website : www.CPChem.com

Appointees : 회사명: 리이치24시코리아(주).

주소: 서울특별시 강남구 강남대로 94길 34,4층

전화: +82-02-6245-1610

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

SECTION 2: Hazards identification**Hazard classification**

Standards for classification and labeling of chemical substances and material safety data sheet (ministry of employment and labor public notice No. 2020-130) (GHS 2015)

Classification

: Acute toxicity, Category 4, Inhalation
 Skin corrosion/irritation, Category 2
 Carcinogenicity, Category 2
 Specific target organ toxicity - repeated exposure, Category 2,
 Liver, Blood, thymus
 Aspiration hazard, Category 1
 Long-term (chronic) aquatic hazard, Category 2

Warning label elements including precautionary statements

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H332: Harmful if inhaled.
 H351: Suspected of causing cancer.
 H373: May cause damage to organs (Liver, Blood, thymus) through prolonged or repeated exposure.
 H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**
 P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P260: Do not breathe mist or vapors.
 P264: Wash skin thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302 + P352: IF ON SKIN: Wash with plenty of water.
 P304 + P340 + P312: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
 P308 + P313: IF exposed or concerned: Get medical advice/

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

attention.

P321: Specific treatment (see supplemental first aid instructions on this label).

P331: Do NOT induce vomiting.

P332 + P313: If skin irritation occurs: Get medical advice/attention.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P391: Collect spillage.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of contents/ container according to waste-related laws

Other hazards which do : None
not result in classification

SECTION 3: Composition/information on ingredients

Synonyms : Diesel Reference Fuel T

Molecular formula : Mixture

Common name	Synonyms	CAS-No.	Concentration	KECI Number
Diesel fuel, no. 2	Fuels, diesel, no. 2	68476-34-6	100%	KE-17287
Naphthalene	naphthalene	91-20-3	0 % - 1%	KE-25545

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Other cautions for Doctors

- Symptoms : No information available.
- Risks : No information available.
- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

- Flash point : 99.9°C (211.8°F)
Method: closed cup
- Autoignition temperature : No data available
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Fire and explosion protection : Normal measures for preventive fire protection.
- Hazardous decomposition products : Hydrocarbons. Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation.

Number:100000100097

5/19

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Secure storage

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Uses advised against : None known.
- Specific Use : Reference Fuel

SECTION 8: Exposure controls/personal protection**KR**

Components	Basis	Value	Control parameters	Note
Naphthalene	KR OEL	TWA	10 ppm,	carc 2, Skin,
	KR OEL	STEL	15 ppm,	carc 2, Skin,

carc 2 Limited evidence of carcinogenicity in humans or animals, which is not sufficiently convincing to place the substance in Category 1
 Skin Substances designated by 'Skin' may be absorbed into the bloodstream through the skin, mucous membrane and eye and contribute to the overall effect. (Skin notation does not apply to the skin irritant)

Chemical exposure standards, biological exposure standards, etc.

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Protective suit. Safety shoes.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties**

Appearance

Physical state : liquid at 20°C (68°F)
(101.30 kPa)

Color : Pale yellow, Brown

Odor : Mild

Odor Threshold : No data available

pH : Not applicable

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Pour point	: -6.7°C (19.9°F) Method: ASTM D97
Melting point/freezing point	No data available
Boiling point/boiling range	: 222-366°C (432-691°F) Method: ASTM D 86
Flash point	: 99.9°C (211.8°F) Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Vapor pressure	: 0.10 kPa at 40°C (104°F)
Solubility	: negligible
Relative density	: 0.8101
Density	: 6.76 g/cm ³
Bulk density	: 6.75 L/G
Vapor density	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 3.088 cSt at 40°C (104°F)
Molecular weight	: Not applicable

SECTION 10: Stability and reactivity

Number:100000100097

8/19

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.
Conditions to avoid	: No data available.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Thermal decomposition	: No data available
Hazardous decomposition products	: Hydrocarbons Carbon oxides
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Information on exposure routes****Acute oral toxicity**

Diesel fuel, no. 2 : LD50: > 5,000 mg/kg
Species: Rat
Sex: male and female
Method: OECD Test Guideline 401

Naphthalene : LD50: 500 mg/kg
Method: Converted acute toxicity point estimate

Acute inhalation toxicity

Diesel fuel, no. 2 : LC50: 4.1 mg/l
Exposure time: 4 h
Species: Rat
Sex: male and female
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Test substance: yes

Acute dermal toxicity

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Diesel fuel, no. 2 : LD50 Dermal: > 4,300 mg/kg
Species: Rabbit
Sex: male and female
Test substance: yes

TrusTec™ Diesel Reference Fuel T-36

Skin corrosion or irritation : Skin irritation

May cause skin irritation in susceptible persons.

TrusTec™ Diesel Reference Fuel T-36

Eye corrosion or irritation : Vapors may cause irritation to the eyes, respiratory system and the skin.

TrusTec™ Diesel Reference Fuel T-36

Respiratory Sensitization : Did not cause sensitization on laboratory animals.

TrusTec™ Diesel Reference Fuel T-36

Skin sensitization Not applicable

Carcinogenicity

Diesel fuel, no. 2 : Species: Mouse
Sex: male
Dose: 0, 25 ul
Exposure time: lifetime
Number of exposures: 3 times/wk
Remarks: Moderate dermal carcinogen

Naphthalene : Species: Mouse
Sex: male
Dose: 10, 30 ppm
Exposure time: 105 weeks
Number of exposures: 6 hours/day, 5 days/week
Test substance: yes
Print Date: No information available.
Remarks: No evidence of carcinogenicity

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Species: Mouse
 Sex: female
 Dose: 10, 30 ppm
 Exposure time: 105 weeks
 Number of exposures: 6 hours/day, 5 days/week
 Test substance: yes
 Print Date: No information available.
 Remarks: increased incidence of alveolar/bronchiolar adenomas

Species: Rat
 Sex: male and female
 Dose: 10, 30, 60 ppm
 Exposure time: 105 weeks
 Number of exposures: 6 hours/day, 5 days/week
 Test substance: yes
 Print Date: No information available.
 Remarks: nose respiratory epithelial adenoma, increased incidence of olfactory neuroblastomas

Repeated dose toxicity

Diesel fuel, no. 2 : Species: Rat, Male and female
 Sex: Male and female
 Application Route: Dermal
 Dose: 0, 30, 125, 500 mg/kg
 Exposure time: 13 wks
 Number of exposures: daily, 5 days/week
 NOEL: 30 mg/kg
 Method: OECD Guideline 411
 Target Organs: Thymus, Liver, Bone marrow
 Information given is based on data obtained from similar substances.

Species: Rat, Male and female
 Sex: Male and female
 Application Route: inhalation (dust/mist/fume)
 Dose: 0, 0.35, 0.88, 1.71 mg/l
 Exposure time: 13 wks
 Number of exposures: Twice/wk
 NOEL: > 1.71 mg/l
 Method: OECD Guideline 413

Germ cell mutagenicity (in vitro)

Diesel fuel, no. 2 : Test Type: Ames test
 Result: positive

 Test Type: Mouse lymphoma assay
 Result: negative

 Naphthalene : Test Type: Ames test
 Result: negative

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Test Type: Sister Chromatid Exchange Assay
Result: negative

Test Type: Unscheduled DNA synthesis assay
Result: negative

Germ cell mutagenicity (in vivo)

Diesel fuel, no. 2 : Test Type: Dominant lethal assay
Species: Mouse
Dose: 100 or 400 ppm
Result: negative

Naphthalene Test Type: Mouse micronucleus assay
Result: negative

Developmental Toxicity

Diesel fuel, no. 2 : Species: Rat
Application Route: Inhalation
Dose: 0, 86.9, 408.8 ppm
Number of exposures: 6 h/d
Test period: GD 6-15
Method: OECD Guideline 414
NOAEL Teratogenicity: 408.8 ppm
NOAEL Maternal: 408.8 ppm
Information given is based on data obtained from similar substances.

Species: Rat
Application Route: Dermal
Dose: 30, 125, 500, 1000 mg/kg
Exposure time: daily
Test period: GD 0-20
Method: OECD Guideline 414
NOAEL Teratogenicity: 125 mg/kg
Information given is based on data obtained from similar substances.

Naphthalene Species: Rabbit
Application Route: oral gavage
Dose: 40, 200, 400 mg/kg
Test period: 29 d, GD 6-18
NOAEL Teratogenicity: 400 mg/kg

**Specific Target Organ
Toxicity (Single Exposure)**

No data available

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

**Specific Target Organ
Toxicity (Repeated
Exposure)**

No data available

TrusTec™ Diesel Reference Fuel T-36**Aspiration toxicity** : May be fatal if swallowed and enters airways.**CMR effects**

Diesel fuel, no. 2 : Carcinogenicity: Limited evidence of carcinogenicity in animal studies
Teratogenicity: Animal testing did not show any effects on fetal development.

Naphthalene Carcinogenicity: Limited evidence of carcinogenicity in animal studies

TrusTec™ Diesel Reference Fuel T-36**Further information** : Solvents may degrease the skin.**SECTION 12: Ecological information**

Ecological Toxicity

Toxicity to fish

Diesel fuel, no. 2 : LL50: 21 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
semi-static test Method: OECD Test Guideline 203

Naphthalene LC50: 3.2 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates

Diesel fuel, no. 2 : EC50: 2 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

Naphthalene LC50: 2.16 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Toxicity to algae

Diesel fuel, no. 2 : ErL50: 22 mg/l
Exposure time: 72 h
Species: Raphidocellus subcapitata (algae)
static test Analytical monitoring: no
Method: OECD Test Guideline 201

Naphthalene EC50: 2.96 mg/l
Exposure time: 48 h
Species: Selenastrum capricornutum (algae)

Persistence and degradability

Diesel fuel, no. 2 : aerobic
Result: Not readily biodegradable.
57.5 %
Testing period: 28 d
Method: OECD Test Guideline 301F

Bioaccumulative

Diesel fuel, no. 2 : Accumulation in aquatic organisms is expected.

Mobility

Diesel fuel, no. 2 : No data available

Results of PBT assessment

Diesel fuel, no. 2 : Non-classified PBT substance, Non-classified vPvB substance

Other adverse effects : Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Disposal method : The product should not be allowed to enter drains, water

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Disposal precaution : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

UN Number	:	UN1202
UN Product Shipping Name	:	DIESEL FUEL
Hazard Class	:	3
Packing Group	:	III - Less Hazardous Properties
Marine Pollutant	:	Yes
Special Safety Measures on Mode of Transport	:	No data available

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIESEL FUEL), 9, III, (99.9°C), MARINE POLLUTANT, (DIESEL FUEL)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (DIESEL FUEL), 9, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

UN1202, DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (DIESEL FUEL)

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****National legislation****Regulation under the Occupational Safety and Health Act**

A Material Safety Datasheet (MSDS) for this product is not required according to article 41 of the ISHA.

Regulation		Chemical name	Threshold limits
Harmful Substances Prohibited from Manufacturing	:	Not applicable	
Harmful Substances Required Permission for Manufacture	:	Not applicable	

Act on the Registration and Evaluation, etc. of Chemical Substances, Chemicals Control Act

Regulation		Chemical name	Threshold limits
Toxic Chemicals	:	Not applicable	
Prohibited Chemicals	:	Not applicable	
Restricted Chemicals	:	Not applicable	
Toxic Release Inventory	:	naphthalene	>= 0.1 %

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

Dangerous Substances Safety Management Act

Dangerous Substances : Flammable liquids, Type 3 petroleums, Water insoluble liquid
Safety Management Act

Regulations by the Waste Management Act

:
Not applicable

Regulations by other domestic and foreign laws

Europe REACH : This product is in full compliance according to REACH regulation 1907/2006/EC.
Switzerland CH INV : On the inventory, or in compliance with the inventory
United States of America (USA) : On or in compliance with the active portion of the
TSCA : TSCA inventory
Canada DSL : All components of this product are on the Canadian
DSL
Australia AIC : On the inventory, or in compliance with the inventory
New Zealand NZIoC : Not in compliance with the inventory
Japan ENCS : On the inventory, or in compliance with the inventory
Japan ISHL : On the inventory, or in compliance with the inventory
Korea KECI : All substances in this product were registered, notified
to be registered, or exempted from registration by
CPChem through an Only Representative according to
K-REACH regulations. Importation of this product is
permitted if the Korean Importer of Record was
included on CPChem's notifications or if the Importer of
Record themselves notified the substances.
Philippines PICCS : On the inventory, or in compliance with the inventory
China IECSC : On the inventory, or in compliance with the inventory
Taiwan TCSI : On the inventory, or in compliance with the inventory
Other TECI : On the inventory, or in compliance with the inventory

Other regulations : No data available

TrusTec™ Diesel Reference Fuel T-36


Version 2.2

Revision Date 2025-10-23

SECTION 16: Other information

Source of data	:	Korea. GHS based classification
Date of initial writing	:	2024-11-09
Revision number	:	1
Last revision date	:	2029-11-09

NFPA Classification : Health Hazard: 2
Fire Hazard: 1
Reactivity Hazard: 0

**Other information**

None.

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIRC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level

TrusTec™ Diesel Reference Fuel T-36

Version 2.2

Revision Date 2025-10-23

EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate