

**Benzene / Toluene Mixture - Kingwood**

Version 1.5

Revision Date 2025-11-19

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Benzene / Toluene Mixture - Kingwood
Use : Feedstock
Company : Chevron Phillips Chemical Company LP
9500 Lakeside Blvd.
The Woodlands, TX 77381

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02

66101029; POISON CENTER ROME – Policlinico "Agostino Gemelli", Servizio di tossicologia

clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù

Tel. +39 06 68593726; POISON CENTER ROME – Policlinico "Umberto I" Tel. +39 06 4997 8000;

POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326;

POISON CENTER NAPLES – Azienda Ospedaliera "Antonio Cardarelli" Tel. +39 081 7472870;

POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055

7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382

24444; POISON CENTER BERGAMO – Azienda Ospedaliera "Papa Giovanni XXIII" Tel. 800 883

300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011

858;

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)
 Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Lithuania: +370 (85) 2362052
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
 Malta: +356 2395 2000
 The Netherlands: NVIC: +31 (0)88 755 8000
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Portugal: CIAV phone number: +351 800 250 250
 Romania: +40213183606
 Slovakia: +421 2 5477 4166
 Slovenia: Phone number: 112
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)
 Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 2
 Skin irritation, Category 2
 Eye irritation, Category 2A
 Germ cell mutagenicity, Category 1B
 Carcinogenicity, Category 1A
 Reproductive toxicity, Category 2
 Specific target organ toxicity - single exposure, Category 3, Central nervous system
 Specific target organ toxicity - repeated exposure, Category 1, Blood
 Specific target organ toxicity - repeated exposure, Category 2, Inhalation, Auditory organs, color vision
 Aspiration hazard, Category 1

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H336: May cause drowsiness or dizziness.
 H340: May cause genetic defects.

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

H350: May cause cancer.
 H361: Suspected of damaging fertility or the unborn child.
 H372: Causes damage to organs (Blood) through prolonged or repeated exposure.
 H373: May cause damage to organs (Auditory organs, color vision) through prolonged or repeated exposure if inhaled.

Precautionary Statements**: Prevention:**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe mist or vapors.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
 P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Carcinogenicity:**IARC**

Group 1: Carcinogenic to humans

Benzene 71-43-2

Group 2B: Possibly carcinogenic to humans

Naphtha (petroleum), light catalytic reformed 64741-63-5

NTP

Known to be human carcinogen

Benzene 71-43-2

SECTION 3: Composition/information on ingredients

Synonyms : None Established

Molecular formula : UVCB

Component	CAS-No.	Weight %
Naphtha (petroleum), light catalytic reformed	64741-63-5	90 - 100
Benzene	71-43-2	50 - 70
Toluene	108-88-3	20 - 30
Xylenes	1330-20-7	1 - 10

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Notes to physician

Risks : May be harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation and serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

Flash point : -11°C (12°F)
Method: Tag closed cup

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Use : Feedstock

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Components	Basis	Value	Control parameters	Note
Naphtha (petroleum), light catalytic reformed	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	
Benzene	ACGIH	TWA	0.02 ppm,	A1, Skin,
	OSHA Z-1-A	TWA	1 ppm,	
	OSHA Z-1-A	CEIL	5 ppm,	
	OSHA Z-2	Peak	50 ppm,	
	OSHA 29 CFR 1910.1028(c)	TWA	1 ppm,	
	OSHA 29 CFR 1910.1028(c)	STEL	5 ppm,	
	OSHA CARC	PEL	1 ppm,	
	OSHA CARC	STEL	5 ppm,	
Toluene	ACGIH	TWA	20 ppm,	OTO, A4,
	OSHA Z-2	TWA	200 ppm,	
	OSHA Z-2	CEIL	300 ppm,	
	OSHA Z-2	Peak	500 ppm,	
	OSHA Z-1-A	TWA	100 ppm, 375 mg/m3	
	OSHA Z-1-A	STEL	150 ppm, 560 mg/m3	
Xylenes	OSHA Z-1	TWA	100 ppm, 435 mg/m3	
	OSHA Z-1-A	STEL	150 ppm, 655 mg/m3	
	OSHA Z-1-A	TWA	100 ppm, 435 mg/m3	
	ACGIH	TWA	20 ppm,	OTO, A4,
	ACGIH	STEL	150 ppm,	A4,

A1 Confirmed human carcinogen
A4 Not classifiable as a human carcinogen
OTO Ototoxicant
Skin Danger of cutaneous absorption

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Benzene	71-43-2	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	1995-03-01
Toluene	108-88-3	Immediately Dangerous to Life or Health Concentration Value 500 parts per million	1995-03-01
Xylenes	1330-20-7	Immediately Dangerous to Life or Health Concentration Value 900 parts per million	2017-09-01

Biological exposure indices**US**

Substance name	CAS-No.	Control parameters	Sampling time	Update
Benzene	71-43-2	S-Phenylmercapturic acid: 25 µg/g creatinine Background (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		t,t-Muconic acid: 500 µg/g creatinine Background (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	2010-03-01
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	2010-03-01
		o-Cresol: 0.3 mg/g creatinine Background (Urine) With hydrolyses ()	End of shift (As soon as possible after exposure ceases)	2010-03-01
Xylenes	1330-20-7	Methylhippuric acids: 0.3 g/g creatinine 2024 Adoption (Urine) Commercial or technical grade xylenes consist of mixtures of isomers and significant amounts of ethyl benzene as indicated under 'Properties.' Because ethyl benzene is known to reduce the metabolism of xylenes to methylhippuric acids, the BEI applies to technical or commercial grades of xylenes only. () The determinants refer to the total of all isomers of methylhippuric acids. () Adopted values or notations enclosed are those for which changes are proposed in the NIC ()	End of shift (As soon as possible after exposure ceases)	2024-01-01

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Physical state : liquid
- Color : Clear, colorless
- Odor : Sweet, distinct

Safety data

- Flash point : -11°C (12°F)
Method: Tag closed cup
- Molecular formula : UVCB
- Molecular weight : Not applicable
- pH : Not applicable
- Melting point/ range : -5.5°C (22.1°F)
- Boiling point/boiling range : 80°C (176°F)
- Vapor pressure : 75.00 MMHG
at 20°C (68°F)

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Relative density	: 0.87 at 15.6 °C (60.1 °F)
Density	: 0.87 G/ML
Water solubility	: Insoluble in water; miscible with most organic solvents.
Viscosity, kinematic	: < 1.138 cSt at 37.8°C (100.0°F)
Relative vapor density	: 2.77 (Air = 1.0)
Evaporation rate	: 2.8

SECTION 10: Stability and reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Further information: No decomposition if stored and applied as directed. Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Benzene / Toluene Mixture - Kingwood**

Acute oral toxicity : LD50 Oral: 4,052 mg/kg
Species: Rat
Method: Acute toxicity estimate

Benzene / Toluene Mixture - Kingwood

Acute inhalation toxicity : LC50: > 40 mg/l
Exposure time: 4 h
Species: Rat
Test atmosphere: vapor
Method: Acute toxicity estimate

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Benzene / Toluene Mixture - Kingwood

Acute dermal toxicity : LD50 Dermal: > 5,000 mg/kg
Species: Rabbit
Method: Acute toxicity estimate

Skin irritation

Naphtha (petroleum), light catalytic reformed : Skin irritation
Benzene : Skin irritation
Vapors may cause irritation to the eyes, respiratory system and the skin.
Toluene : Skin irritation
Xylenes : Skin irritation

Benzene / Toluene Mixture - Kingwood

Eye irritation : May irritate eyes.

Benzene / Toluene Mixture - Kingwood

Sensitization : Not classified. Estimated based on individual component values.

Repeated dose toxicity

Naphtha (petroleum), light catalytic reformed : Species: Rat
Application Route: Inhalation
Dose: 0, 2.00, 5.85, 20.3 mg/l
Exposure time: 21 day
Number of exposures: 6 h/d, 5 d/wk
NOEL: 20.3 mg/l

Species: Rabbit
Application Route: Dermal
Dose: 0, 200, 1000, 2000 mg/l
Exposure time: 28 day
Number of exposures: 3 times/wk
Lowest observable effect level: 1000 mg/l

Benzene : Species: Rat, female
Sex: female
Application Route: oral gavage
Dose: 0, 25, 50, 100 mg/kg
Exposure time: 103 wk
Number of exposures: 5 d/wk
NOEL: < 25 mg/kg
Lowest observable effect level: 25 mg/kg

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

	<p>Species: Rat, male Sex: male Application Route: oral gavage Dose: 0, 50, 100, 200 mg/kg Exposure time: 103 wk Number of exposures: 5 d/wk NOEL: < 50 mg/kg Lowest observable effect level: 50 mg/kg</p> <p>Species: Mouse Application Route: oral gavage Dose: 0, 25, 50, 100 mg/kg Exposure time: 103 wk NOEL: < 25 mg/kg</p>
Toluene	<p>Species: Rat Application Route: Inhalation Dose: 0, 100, 625, 1250, 3000 ppm Exposure time: 15 wk Number of exposures: 6.5 h/d, 5 d/wk NOEL: 625 ppm</p> <p>Species: Mouse Application Route: Inhalation Dose: 0, 100, 625, 1250, 3000 ppm Exposure time: 14 wk Number of exposures: 6.5 h/d, 5 d/wk NOEL: 100 ppm</p>
Xylenes	<p>Species: Rat Application Route: oral gavage Dose: 0, 62.5, 125, 250, 500, 1000 mg/kg Exposure time: 13 wk Number of exposures: daily, 5 d/wk NOEL: 1,000 mg/kg</p> <p>Species: Rat Application Route: Inhalation Dose: 0, 180, 460, 810 ppm Exposure time: 13 wk Number of exposures: 6 h/d, 5 d/wk NOEL: > 810 ppm</p> <p>Species: Rat Application Route: Inhalation Dose: 0, 450, 900, 1800 ppm Exposure time: 13 wk Number of exposures: 6 h/d, 6 d/wk Lowest observable effect level: 900 ppm</p>

Genotoxicity in vitroNaphtha (petroleum), light
catalytic reformed: Test Type: Ames test
Result: negativeTest Type: Cytogenetic assay
Result: negative

Benzene

Test Type: Ames test

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Result: negative

Test Type: Cytogenetic assay

Result: positive

Test Type: Mouse lymphoma assay

Result: positive

Test Type: Sister Chromatid Exchange Assay

Result: negative

Toluene

Test Type: Ames test

Result: negative

Test Type: Sister Chromatid Exchange Assay

Result: negative

Test Type: Mouse lymphoma assay

Result: negative

Test Type: Cytogenetic assay

Result: negative

Xylenes

Test Type: Ames test

Result: negative

Test Type: Mouse lymphoma assay

Result: negative

Genotoxicity in vivoNaphtha (petroleum), light
catalytic reformed

: Test Type: Cytogenetic assay

Result: negative

Benzene

Test Type: Mouse micronucleus assay

Result: positive

Toluene

Test Type: Cytogenetic assay

Result: negative

Test Type: Mouse micronucleus assay

Result: negative

Xylenes

Test Type: Mouse micronucleus assay

Result: negative

Carcinogenicity

Benzene

: Species: Rat

Sex: female

Dose: 0, 25, 50, 250 mg/kg

Exposure time: 103 wks

Number of exposures: daily, 5 days/week

Test substance: yes

Remarks: zymbal gland carcinomas, squamous cell
papillomas

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Species: Rat
Sex: male
Dose: 0, 50, 100, 200 mg/kg
Exposure time: 103 wks
Number of exposures: daily, 5 days/week
Test substance: yes
Remarks: zymbal gland carcinomas, squamous cell papillomas

Species: Mouse
Sex: male and female
Dose: 25, 50, 100 mg/kg
Exposure time: 103 wks
Number of exposures: daily, 5 days/week
Test substance: yes
Remarks: Clear evidence of multiple organ carcinogenicity.

Toluene

Species: Rat
Dose: 0, 600, 1200 ppm
Exposure time: 2 yrs
Number of exposures: 6.5 h/d, 5 d/wk
Remarks: No evidence of carcinogenicity

Species: Mouse
Dose: 0, 600, 1200 ppm
Exposure time: 2 yrs
Number of exposures: 6.5 h/d, 5 d/wk
Remarks: No evidence of carcinogenicity

Xylenes

Species: Rat
Dose: 0, 250, 500 mg/kg
Exposure time: 103 wks
Number of exposures: 5 d/wk
Remarks: No evidence of carcinogenicity

Species: Mouse
Dose: 0, 500, 1000 mg/kg
Exposure time: 103 wks
Number of exposures: 5 d/wk
Remarks: No evidence of carcinogenicity

Reproductive toxicity**Toluene**

: Species: Rat
Application Route: Inhalation
Dose: 0, 100, 500, 2000 ppm
Test period: 95 d
NOAEL Parent: 2000 ppm

Developmental Toxicity**Toluene**

: Species: Rat
Application Route: Inhalation
Dose: 0, 100, 500, 2000 ppm
Test period: 95 d
NOAEL Teratogenicity: 400-750 ppm

Xylenes

Species: Rat
Application Route: Inhalation

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Dose: 0, 805, 1610 ppm
Number of exposures: 6 h/d
Test period: GD 7-16
NOAEL Maternal: 1610 ppm

Species: Mouse
Application Route: oral gavage
Dose: 0, 780, 1960, 2619 mg/kg
Number of exposures: 3 times/d
Test period: GD 6-15
NOAEL Teratogenicity: 780 mg/kg
NOAEL Maternal: 780 mg/kg

Benzene / Toluene Mixture - Kingwood

Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

Naphtha (petroleum), light catalytic reformed : Carcinogenicity: Possible human carcinogen
Mutagenicity: In vivo tests showed mutagenic effects
Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Benzene : Carcinogenicity: Human carcinogen.
Mutagenicity: In vivo tests showed mutagenic effects
Teratogenicity: Did not show teratogenic effects in animal experiments.
Reproductive toxicity: Animal testing did not show any effects on fertility.

Toluene : Carcinogenicity: Not classifiable as a human carcinogen.
Mutagenicity: Animal testing did not show any mutagenic effects.
Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.
Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

Xylenes : Carcinogenicity: Not classifiable as a human carcinogen.
Mutagenicity: Did not show mutagenic effects in animal experiments.
Teratogenicity: Damage to fetus not classifiable

Benzene / Toluene Mixture - Kingwood

Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity effects****Toxicity to fish**

Naphtha (petroleum), light catalytic reformed : LL50: 8.2 mg/l
Exposure time: 96 h

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Benzene	Species: Pimephales promelas (fathead minnow) semi-static test LC50: 5.3 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) flow-through test Test substance: yes Method: OECD Test Guideline 203
Toluene	LC50: 18 - 36 mg/l Exposure time: 96 h Species: Pimephales promelas (fathead minnow)
Xylenes	LC50: 8.2 mg/l Exposure time: 96 h Species: Salmo gairdneri (Rainbow trout)

Toxicity to daphnia and other aquatic invertebrates

Benzene	: EC50: 10 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Test substance: yes Method: OECD Test Guideline 202
Toluene	EC50: 3.78 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)

Toxicity to algae

Benzene	: ErC50: 100 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (green algae) Test substance: yes Method: OECD Test Guideline 201
Toluene	EC50: 134 mg/l Exposure time: 72 h Species: Chlamydomonas angulosa (Green algae)

Biodegradability

Naphtha (petroleum), light catalytic reformed	: aerobic 96.17 % Method: ISO/DIS 14593 Expected to be inherently biodegradable.
Benzene	: According to the results of tests of biodegradability this product is considered as being readily biodegradable.
Toluene	: This material is expected to be readily biodegradable.
Xylenes	: This material is expected to be readily biodegradable.
Elimination information (persistence and degradability)	

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Bioaccumulation

Naphtha (petroleum), light : The product may be accumulated in organisms.

catalytic reformed

Benzene : Bioconcentration factor (BCF): 13

Toluene : This material is not expected to bioaccumulate.

Xylenes : This material is not expected to bioaccumulate.

Mobility : No data available

Results of PBT assessment

Benzene : Not persistent, bioaccumulative, and toxic (PBT)., Not very persistent and very bioaccumulative (vPvB).

Toluene : Non-classified vPvB substance, Non-classified PBT substance

Additional ecological : An environmental hazard cannot be excluded in the event of information unprofessional handling or disposal.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic : Toxic to aquatic life. hazard

Long-term (chronic) aquatic : Harmful to aquatic life with long lasting effects. hazard

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (-11 °C c.c.), MARINE POLLUTANT, (NAPHTHA (PETROLEUM), LIGHT CATALYTIC REFORMED)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (NAPHTHA (PETROLEUM), LIGHT CATALYTIC REFORMED)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

33, UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (NAPHTHA (PETROLEUM), LIGHT CATALYTIC REFORMED)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (NAPHTHA (PETROLEUM), LIGHT CATALYTIC REFORMED)

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****National legislation**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Skin corrosion or irritation
Serious eye damage or eye irritation

CERCLA Reportable : 16 lbs

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Quantity

Benzene

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : The following components are subject to reporting levels established by SARA Title III, Section 313:
: Benzene - 71-43-2
: Toluene - 108-88-3
: Xylenes - 1330-20-7

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):
: Benzene - 71-43-2
: Toluene - 108-88-3
: Xylenes - 1330-20-7

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):
: Benzene - 71-43-2
: Toluene - 108-88-3
: Xylenes - 1330-20-7

US State Regulations**Massachusetts Right To Know**

: Benzene - 71-43-2
: Toluene - 108-88-3

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Xylenes - 1330-20-7

Pennsylvania Right To Know

: Naphtha (petroleum), light catalytic reformed - 64741-63-5
 Benzene - 71-43-2
 Toluene - 108-88-3
 Xylenes - 1330-20-7

California Prop. 65 Components

: WARNING: This product can expose you to chemicals including [listed below], which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov/food.

Benzene

71-43-2


WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Benzene
Toluene71-43-2
108-88-3**Notification status**

Europe REACH	:	Not in compliance with the inventory
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	All substances listed as active on the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AIIC	:	All components are listed on the inventory, regulatory obligations/restrictions apply
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECI	:	On the inventory, or in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information**NFPA Classification**

: Health Hazard: 2
 Fire Hazard: 3
 Reactivity Hazard: 0
 Health Hazard: 2
 Fire Hazard: 3
 Reactivity Hazard: 0



Revision Date : 2025-11-19
Date of last issue : 2020-11-04

Benzene / Toluene Mixture - Kingwood

Version 1.5

Revision Date 2025-11-19

Further information

Legacy SDS Number : CPC00230

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate