

**Orfom® MCX Flotation Oil**

Version 2.2

Revision Date 2025-12-03

according to GB/T 16483 and GB/T 17519

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Orfom® MCX Flotation Oil
Material : 1121555, 1118476, 1118475, 1117264, 1110866, 1016872
Use : Mineral Collector
Uses advised against : This material should not be used for purposes other than the identified uses in section 1 without expert advice.

Company : Chevron Phillips Chemical Company LP
9500 Lakeside Blvd.
The Woodlands, TX 77381

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Organization that prepared : Product Safety and Toxicology Group
the SDS
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

GHS Classification and Labeling: Follow GB 13690, GB 15258 and GB 30000.2 to GB 30000.29 (GHS 2013)

Emergency Overview**Danger**

Form: liquid **Physical state:** liquid **Color:** Colorless **Odor:** Mild

Hazards : Combustible liquid. May be fatal if swallowed and enters airways.

Classification


: Flammable liquids, Category 4
Aspiration hazard, Category 1

Labeling

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

Symbol(s) : 

Signal Word : Danger

Hazard Statements : H227: Combustible liquid.
H304: May be fatal if swallowed and enters airways.

Precautionary Statements : **Prevention:**
P210: Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P280: Wear protective gloves/ eye protection/ face protection.
Response:
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331: Do NOT induce vomiting.
P370+P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.
Disposal:
P501: Dispose of contents/ container to an approved waste disposal plant.

SECTION 3: Composition/information on ingredients

Synonyms : Flotation Oil

Molecular formula : UVCB

Chemical name	CAS-No. / EINECS-No.	Concentration [wt%]
C13-C16 Isoalkanes	68551-20-2	0 - 100
C12-C14 Isoalkanes	68551-19-9	0 - 100

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Never give anything by mouth to

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

an unconscious person. If symptoms persist, call a physician.
Take victim immediately to hospital.

Notes to physician

Symptoms : No data available.
Risks : No data available.
Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

Flash point : 79°C (174°F)
Method: ASTM D 93

Autoignition temperature : No data available

Suitable extinguishing media : Carbon dioxide (CO₂).

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions : Use personal protective equipment. Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. For

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Uses advised against : This material should not be used for purposes other than the identified uses in section 1 without expert advice.

Use : Mineral Collector

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1,200 mg/m3	RCP,

RCP Reciprocal Calculation Procedure

CN

Components	Basis	Value	Control parameters	Note
------------	-------	-------	--------------------	------

Not listed

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant protective clothing. Footwear protecting against chemicals.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : liquid
- Physical state : liquid
- Color : Colorless
- Odor : Mild

Safety data

- Flash point : 79°C (174°F)
Method: ASTM D 93
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : No
- Autoignition temperature : No data available
- Molecular formula : UVCB
- Molecular weight : Not applicable
- pH : 7
- Pour point : No data available
- Boiling point/boiling range : 214.4-316°C (417.9-601°F)
- Vapor pressure : 0.36 MMHG
at 37.8°C (100.0°F)
- Relative density : 0.79
at 15.6 °C (60.1 °F)
- Density : 794.5 g/l
- Water solubility : negligible

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

Partition coefficient: n-octanol/water : No data available
Viscosity, kinematic : 3.3 cSt
at 38°C (100°F)

Relative vapor density : 1
(Air = 1.0)

Evaporation rate : < 1

SECTION 10: Stability and reactivity

Reactivity : Stable under recommended storage conditions.

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Hazardous reactions : Hazardous reactions: Hazardous polymerization does not occur.

Hazardous reactions: Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous decomposition products : Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Orfom® MCX Flotation Oil
Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method
Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil
Acute inhalation toxicity : Acute toxicity estimate: > 5.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method
Information given is based on data obtained from similar

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

substances.

Orfom® MCX Flotation Oil**Acute dermal toxicity**

: Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method
Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil**Skin irritation**

: Repeated exposure may cause skin dryness or cracking.
May irritate skin. largely based on animal evidence.
Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil**Eye irritation**

: No eye irritation
largely based on animal evidence. Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil**Sensitization**

: Did not cause sensitization on laboratory animals.
Information given is based on data obtained from similar substances.

Repeated dose toxicity**C13-C16 Isoalkanes**

: Species: Rat, male and female
Sex: male and female
Application Route: oral gavage
Exposure time: 13 wk
Number of exposures: 7 d/wk
NOEL: > 5,000 mg/kg
Method: OECD Test Guideline 408
No significant adverse effects were reported
Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

Species: Rat, male and female
Sex: male and female
Application Route: Inhalation
Exposure time: 13 wk
Number of exposures: 6 h/d
NOEL: 30 mg/l
Method: OECD Test Guideline 413
No significant adverse effects were reported
Information given is based on data obtained from similar substances.

Species: Rat, male and female
Sex: male and female
Application Route: Dermal
Exposure time: 13 wk
Number of exposures: 5 d/wk
NOEL: > 495 mg/kg
Method: OECD Test Guideline 411
No significant adverse effects were reported
Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes

Species: Rat, male and female
Sex: male and female
Application Route: oral gavage
Dose: 100, 500, 1000 mg/kg/d
Exposure time: 13 wk
Number of exposures: daily
NOEL: > 1000 mg/kg/d
Method: OECD Test Guideline 408
No adverse effects expected
Information given is based on data obtained from similar substances.

Species: Rat, male and female
Sex: male and female
Application Route: Inhalation
Dose: 2600, 5200, 10400 mg/m³
Exposure time: 90 d
Number of exposures: 6 h/d; 5d/wk
NOEL: > 10400 mg/m³
Method: OECD Test Guideline 413
No adverse effects expected
Information given is based on data obtained from similar substances.

Genotoxicity in vitro**C13-C16 Isoalkanes**

: Test Type: Reverse mutation assay
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
Remarks: Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

	<p>Test Type: Cytogenetic assay Test system: Chinese hamster cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: negative Remarks: Information given is based on data obtained from similar substances.</p> <p>Test Type: Mouse lymphoma assay Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative Remarks: Information given is based on data obtained from similar substances.</p>
C12-C14 Isoalkanes	<p>Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative</p> <p>Test Type: Mouse lymphoma assay Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative</p> <p>Test Type: Sister Chromatid Exchange Assay Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 479 Result: negative</p>

Genotoxicity in vivo

C12-C14 Isoalkanes	: Test Type: dominant lethal test Species: Rat Route of Application: Intraperitoneal injection Dose: 300, 900 ppm Method: OECD Test Guideline 478 Remarks: Information given is based on data obtained from similar substances.
--------------------	--

Reproductive toxicity

C13-C16 Isoalkanes	: Species: Rat Sex: male and female Application Route: oral gavage Dose: 50, 100, 750 mg/kg/d Exposure time: 70 d Number of exposures: Daily Method: OECD Test Guideline 416 NOAEL Parent: ≥ 750 mg/kg NOAEL F1: ≥ 750 mg/kg No adverse effects expected Information given is based on data obtained from similar substances.
--------------------	---

Developmental Toxicity

C12-C14 Isoalkanes	: Species: Rat
--------------------	----------------

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

Application Route: Inhalation
 Dose: 0, 400, 1200 ppm
 Exposure time: 6h
 Test period: GD 6-15
 NOAEL Teratogenicity: 1200 ppm
 NOAEL Maternal: 1200 ppm
 Information given is based on data obtained from similar substances.

Species: Rat
 Application Route: Inhalation
 Dose: 300, 900 ppm
 Exposure time: 6h
 Test period: GD 6-15
 NOAEL Teratogenicity: \geq 900 ppm
 NOAEL Maternal: \geq 900 ppm
 Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil
Aspiration toxicity

: May be fatal if swallowed and enters airways.

CMR effects

C13-C16 Isoalkanes : Carcinogenicity: Not available
 Mutagenicity: In vitro tests did not show mutagenic effects
 Reproductive toxicity: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

C12-C14 Isoalkanes : Carcinogenicity: Not available
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: Animal testing did not show any effects on fertility.

Orfom® MCX Flotation Oil
Further information

: Solvents may degrease the skin.

SECTION 12: Ecological information

Ecotoxicity effects
Toxicity to fish

C13-C16 Isoalkanes : LL50: > 1,028 mg/l
 Exposure time: 96 h
 Species: *Scophthalmus maximus* (Flatfish, Flounder)
 Method: OECD Test Guideline 203
 Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes : LL50: > 1,000 mg/l
 Exposure time: 96 h
 Species: *Oncorhynchus mykiss* (rainbow trout)
 semi-static test Method: OECD Test Guideline 203

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates

C13-C16 Isoalkanes : LL50: > 3,193 mg/l
Exposure time: 48 h
Species: *Acartia tonsa* (Marine Copepod)
static test Method: ISO 14669 and PARCOM method

C12-C14 Isoalkanes EL50: > 1,000 mg/l
Exposure time: 48 h
Species: *Daphnia magna* (Water flea)
static test Method: OECD Test Guideline 202
Information given is based on data obtained from similar substances.

Toxicity to algae

C13-C16 Isoalkanes : EL50: > 3,200 mg/l
Exposure time: 72 h
Species: *Skeletonema costatum* (Marine Algae)
Growth inhibition Method: ISO 10253

C12-C14 Isoalkanes EL50: > 1,000 mg/l
Exposure time: 72 h
Species: *Pseudokirchneriella subcapitata* (green algae)
Growth inhibition Method: OECD Test Guideline 201
Information given is based on data obtained from similar substances.

Toxicity to bacteria

C13-C16 Isoalkanes : > 100 mg/l
Exposure time: 3 h
Respiration inhibition
Method: OECD Test Guideline 209
Information given is based on data obtained from similar substances.

Toxicity to fish (Chronic toxicity)

C12-C14 Isoalkanes : No data available:

Biodegradability

C13-C16 Isoalkanes : aerobic
Result: Inherently biodegradable.
18 %
Testing period: 28 d
Method: OECD Test Guideline 306
Information given is based on data obtained from similar substances.

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

C12-C14 Isoalkanes : aerobic
 Result: Readily biodegradable.
 89.8 %
 Testing period: 28 d
 Method: OECD Test Guideline 301F
 Information given is based on data obtained from similar substances.

Elimination information (persistence and degradability)

Bioaccumulation : The product may be accumulated in organisms.

Mobility : immobile

Results of PBT assessment

C13-C16 Isoalkanes : Non-classified PBT substance, Non-classified vPvB substance

C12-C14 Isoalkanes : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : This material is not expected to be harmful to aquatic organisms.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : This material is not expected to be harmful to aquatic organisms.

Long-term (chronic) aquatic hazard : This material is not expected to be harmful to aquatic organisms.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names,

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3295, HYDROCARBONS, LIQUID, N.O.S., COMBUSTIBLE LIQUID, III

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information**Notification status**

Europe REACH	:	This product is in full compliance according to REACH regulation 1907/2006/EC.
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AIIC	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Japan ISHL	:	On the inventory, or in compliance with the inventory
Korea KECI	:	Not in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

China IECSC : On the inventory, or in compliance with the inventory
 Taiwan TCSI : On the inventory, or in compliance with the inventory
 Other TECI : Not in compliance with the inventory

Other regulations : Law on the Prevention and Control of Occupational Diseases

SECTION 16: Other information**Further information**

Legacy SDS Number : 250860

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIRC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and

Orfom® MCX Flotation Oil

Version 2.2

Revision Date 2025-12-03

			Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate