



2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

MSDS number:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product Name : 2-Methyl-2-Butene
Material : 1083996, 1021754, 1021753, 1021755, 1034801, 1030212

Recommended use of the product : Chemical intermediate

Address : Chevron Phillips Chemical Company LP
Specialty Chemicals
9500 Lakeside Blvd.
The Woodlands, TX 77381

Address : CHEVRON PHILLIPS CHEMICALS ASIA PTE. LTD.
C/O DONG WOO CORPORATION
#B-2601, JEONGJAIL-RO,
BUNDANG-GU, SEONGNAMI-SI,
GYEONGGI-DO, 13557
SOUTH KOREA
Telephone no.: +612-9186-1132

Emergency telephone:

Health:

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
Mexico CHEMTREC 01-800-681-9531 (24 hours)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Argentina: +(54)-1159839431
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)
Belgium: 070 245 245 (24 hours/day, 7 days/week)
Bulgaria: +359 2 9154 233
Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
Cyprus: 1401

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
 Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212
 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Finland: 0800 147 111 09 471 977 (24 hours/day)
 France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
 Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
 Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
 Iceland: 543 2222 (24 hours/day, 7 days/week)
 Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;
 Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)
 Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Lithuania: +370 (85) 2362052
 Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
 Malta: +356 2395 2000
 The Netherlands: NVIC: +31 (0)88 755 8000
 Norway: 22 59 13 00 (24 hours/day, 7 days/week)
 Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Portugal: CIAV phone number: +351 800 250 250
 Romania: +40213183606
 Slovakia: +421 2 5477 4166
 Slovenia: Phone number: 112
 Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)
 Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS : Product Safety and Toxicology Group

E-mail address : SDS@CPChem.com

Website : www.CPChem.com

Appointees : 회사명: 리이치24시코리아㈜.

주소: 서울특별시 강남구 강남대로 94길 34, 4층

전화: +82-02-6245-1610

SECTION 2: Hazards identification**Hazard classification**

Number:100000013905

2/16

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

**Standards for classification and labeling of chemical substances and material safety data sheet
(ministry of employment and labor public notice No. 2020-130)****Classification**

- : Flammable liquids, Category 2
- Acute toxicity, Category 4, Oral
- Skin corrosion/irritation, Category 2
- Germ cell mutagenicity, Category 2
- Carcinogenicity, Category 2
- Specific target organ toxicity - single exposure, Category 3, Central nervous system
- Aspiration hazard, Category 1
- Long-term (chronic) aquatic hazard, Category 2

Warning label elements including precautionary statements

Symbol(s)	:					
Signal Word	:	Danger				
Hazard Statements	:	H225: Highly flammable liquid and vapor. H302: Harmful if swallowed. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H336: May cause drowsiness or dizziness. H341: Suspected of causing genetic defects. H351: Suspected of causing cancer. H411: Toxic to aquatic life with long lasting effects.				
Precautionary Statements	:	Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233: Keep container tightly closed. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242: Use only non-sparking tools. P243: Take precautionary measures against static discharge. P261: Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264: Wash the contact area thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P273: Avoid release to the environment. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection. Response:				

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P308 + P313: IF exposed or concerned: Get medical advice/ attention.

P321: Specific treatment (see supplemental first aid instructions on this label).

P331: Do NOT induce vomiting.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391: Collect spillage.

Storage:

P403 + P233: Store in a well-ventilated place. Keep container tightly closed.

P403 + P235: Store in a well-ventilated place. Keep cool.

Disposal:

P501: Dispose of contents and container according to wastes control act.

Other hazards which do :
not result in classification

SECTION 3: Composition/information on ingredients

Synonyms : 2-MB-2
beta-Isoamylene
Isoamylene

Molecular formula : C5H10

Common name	Synonyms	CAS-No.	Concentration	KECI Number
2-methyl-2-butene	2-methylbut-2-ene	513-35-9	88 % - 95%	KE-23587
2-methyl-1-butene	2-methylbut-1-ene	563-46-2	5 % - 12%	KE-23586

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

- Flash point : -45°C (-49°F)
Method: Setaflash Closed Cup
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

surfaces and sources of ignition.

Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Secure storage

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Specific Use : Chemical intermediate

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

SECTION 8: Exposure controls/personal protection**Chemical exposure standards, biological exposure standards, etc.**

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:.. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:.. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties**

Appearance

Physical state

: liquid

Color

: Colorless

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

Odor	: Mild
pH	: Not applicable
Pour point	: No data available
Boiling point/boiling range	: 38.6°C (101.5°F)
Flash point	: -45°C (-49°F) Method: Setaflash Closed Cup
Evaporation rate	: 1
Lower explosion limit	: 1.4 %(V)
Vapor pressure	: 14.30 PSI at 37.8°C (100.0°F)
Solubility	: negligible
Relative density	: 0.67 at 15.6 °C (60.1 °F)
Vapor density	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Viscosity, kinematic	: 0.29 mm ² /s at 20°C (68°F)
Molecular weight	: 70.15 g/mol

SECTION 10: Stability and reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

Further information: No decomposition if stored and applied as directed.

Hazardous reactions: Vapors may form explosive mixture with air.

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition products	: Carbon oxides
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Information on exposure routes****Acute oral toxicity**

2-methyl-2-butene : LD50: 1,000 - 1,700 mg/kg
Species: Rat

Acute inhalation toxicity

2-methyl-2-butene : LC50: > 175 mg/l
Exposure time: 4 h
Species: Rat
Test atmosphere: vapor

Acute dermal toxicity

2-methyl-2-butene : LD50: > 2,000 mg/kg
Species: Rat

Skin corrosion or irritation

2-methyl-2-butene : Skin irritation
May cause skin irritation in susceptible persons.

Secure storage

2-methyl-2-butene : No eye irritation
Vapors may cause irritation to the eyes, respiratory system and the skin.

Sensitization

2-methyl-2-butene : Did not cause sensitization on laboratory animals.

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

2-Methyl-2-Butene
Skin sensitization**Repeated dose toxicity**

2-methyl-2-butene : Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 580, 2000, 7000 ppm
Exposure time: 4 wk
Number of exposures: 6 h/d, 7 d/wk
NOEL: 580 ppm
Method: OECD Guideline 422

Germ cell mutagenicity (in vitro)

2-methyl-2-butene : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Method: OECD Test Guideline 480
Result: negative

Germ cell mutagenicity (in vivo)

2-methyl-2-butene : Test Type: Mouse micronucleus assay
Species: Rat
Cell type: Bone marrow
Route of Application: Inhalation
Exposure time: 6 h/d 2d
Method: OECD Test Guideline 474
Result: positive

Developmental Toxicity

2-methyl-2-butene : Species: Rat
Application Route: Inhalation
Dose: 500, 2000, 8000 ppm
Exposure time: 6 h/d
Test period: Days 5 -21
Method: OECD Guideline 414
NOAEL Teratogenicity: 8000 ppm
NOAEL Maternal: 8000 ppm
Information given is based on data obtained from similar substances.
Animal testing did not show any effects on fetal development.

Specific Target Organ
Toxicity (Single Exposure)

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

**Specific Target Organ
Toxicity (Repeated
Exposure)****2-Methyl-2-Butene
Aspiration toxicity**

: May be fatal if swallowed and enters airways.

CMR effects

2-methyl-2-butene

: Carcinogenicity: Limited evidence of carcinogenicity in animal studies
Mutagenicity: In vitro tests showed mutagenic effects
Teratogenicity: Animal testing did not show any effects on fetal development.
Reproductive toxicity: Animal testing did not show any effects on fertility.

Reproductive toxicity

2-methyl-2-butene

: Species: Rat
Sex: male and female
Application Route: Inhalation
Dose: 580, 2000, 7000 ppm
Number of exposures: 6 h/d, 7 d/wk
Test period: 4 wks
Method: OECD Guideline 422
NOAEL Parent: 7000 ppm
NOAEL F1: 7000 ppm
no abnormalities observed

**2-Methyl-2-Butene
Further information**

: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Solvents may degrease the skin.

SECTION 12: Ecological information**Ecological Toxicity****Toxicity to fish**

2-methyl-2-butene

: LC50: 4.99 mg/l
Exposure time: 96 h
Species: *Oncorhynchus mykiss* (rainbow trout)
semi-static test Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

Number:100000013905

11/16

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

2-methyl-2-butene : EC50: 3.84 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
static test Method: OECD Test Guideline 202

Toxicity to algae

2-methyl-2-butene : ErC50: 13.2 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (green algae)
static test Method: OECD Test Guideline 201

Persistence and degradability

2-methyl-2-butene : aerobic
7 %
Testing period: 28 d
Method: OECD Test Guideline 301D
This material is not expected to be readily biodegradable.

Results of PBT assessment
2-methyl-2-butene : Non-classified PBT substance, Non-classified vPvB substance

Other adverse effects : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard
2-methyl-2-butene : Toxic to aquatic life.

Long-term (chronic) aquatic hazard
2-methyl-2-butene : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Disposal method : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

waste management company.

Disposal precaution : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

UN Number	:	
UN Product Shipping Name	:	
Hazard Class	:	
Packing Group	:	
Marine Pollutant	:	
Special Safety Measures on Mode of Transport	:	

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1993, FLAMMABLE LIQUIDS, N.O.S., (2-METHYL-2-BUTENE, 2-METHYL-1-BUTENE), 3, II

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1993, FLAMMABLE LIQUID, N.O.S., (2-METHYL-2-BUTENE, 2-METHYL-1-BUTENE), 3, II, (-45°C), MARINE POLLUTANT, (2-METHYL-2-BUTENE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1993, FLAMMABLE LIQUID, N.O.S., (2-METHYL-2-BUTENE, 2-METHYL-1-BUTENE), 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1993, FLAMMABLE LIQUID, N.O.S., (2-METHYL-2-BUTENE, 2-METHYL-1-BUTENE), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (2-METHYL-2-BUTENE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

GOODS (EUROPE))

UN1993, FLAMMABLE LIQUID, N.O.S., (2-METHYL-2-BUTENE, 2-METHYL-1-BUTENE), 3, II,
ENVIRONMENTALLY HAZARDOUS, (2-METHYL-2-BUTENE)

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF
DANGEROUS GOODS BY INLAND WATERWAYS)**

UN1993, FLAMMABLE LIQUID, N.O.S., (2-METHYL-2-BUTENE, 2-METHYL-1-BUTENE), 3, II,
ENVIRONMENTALLY HAZARDOUS, (2-METHYL-2-BUTENE)

Maritime transport in bulk according to IMO instruments**SECTION 15: Regulatory information****National legislation****Regulation under the Occupational Safety and Health Act**

A Material Safety Datasheet (MSDS) for this product is not required according to article 41 of the ISHA.

Regulation	Chemical name	Threshold limits
Harmful Substances Prohibited from Manufacturing	:	Not applicable
Harmful Substances Required Permission for Manufacture	:	Not applicable

Act on the Registration and Evaluation, etc. of Chemical Substances, Chemicals Control Act

Regulation	Chemical name	Threshold limits
Toxic Chemicals	:	Not applicable
Prohibited Chemicals	:	Not applicable
Restricted Chemicals	:	Not applicable
Toxic Release Inventory	:	Not applicable

Dangerous Substances Safety Management Act

Dangerous Substances : Flammable liquids, Special flammables
Safety Management Act

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19


Regulations by the Waste Management Act :**Regulations by other domestic and foreign laws**

Europe REACH	:	Not in compliance with the inventory
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA)	:	On or in compliance with the active portion of the TSCA inventory
TSCA	:	
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AIIC	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Korea KECL	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations.
Philippines PICCS	:	On the inventory, or in compliance with the inventory
Taiwan TCSI	:	On the inventory, or in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

Source of data	:	
Date of initial writing	:	
Revision number	:	
Last revision date	:	

NFPA Classification : Health Hazard: 2
 Fire Hazard: 4
 Reactivity Hazard: 0

**Other information**

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

2-Methyl-2-Butene

Version 2.3

Revision Date 2026-02-19

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate