



## Liquid HE® 150 Polymer

Version 2.7

Revision Date 2026-04-02

according to GB/T 16483 and GB/T 17519

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### Product information

Product Name : Liquid HE® 150 Polymer  
 Material : 1122098, 1112193, 1103427, 1105173  
 Use : Oilfield Fluids Additive

Uses advised against : This material should not be used for purposes other than the identified uses in section 1 without expert advice.

Company : Chevron Phillips Chemical Company LP  
 Drilling Specialties Company LLC  
 9500 Lakeside Blvd.  
 The Woodlands, TX 77381

Local : See Company Address

#### Emergency telephone:

##### Health:

866.442.9628 (North America)

1.832.813.4984 (International)

##### Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)

Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090

Mexico CHEMTREC 01-800-681-9531 (24 hours)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Argentina: +(54)-1159839431

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)

Belgium: 070 245 245 (24 hours/day, 7 days/week)

Bulgaria: +359 2 9154 233

Croatia: +3851 2348 342 (24 hours/day, 7 days/week)

Cyprus: 1401

Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402

Denmark: Danish Poison Center (Gifflinjen): +45 8212 1212

Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Finland: 0800 147 111 09 471 977 (24 hours/day)

France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)

Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Greece: (0030) 2107793777 (24 hours/day, 7 days/week)

Hungary: +36-80-201-199 (24 hours/day, 7 days/week)

Iceland: 543 2222 (24 hours/day, 7 days/week)

Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS : Product Safety and Toxicology Group  
 E-mail address : SDS@CPChem.com  
 Website : www.CPChem.com

**SECTION 2: Hazards identification**

**Classification of the substance or mixture**  
**GB 30000 Specification for classification and labeling of chemicals**

**Emergency Overview****Warning**

**Physical state:** liquid    **Color:** White    **Odor:** Slight hydrocarbon

**Hazards** : Combustible liquid.

**Classification**

: Flammable liquids, Category 4

**Labeling**

**Signal Word** : Warning

**Hazard Statements** : H227: Combustible liquid.

**Precautionary Statements** : **Prevention:**  
 P210: Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

P280: Wear protective gloves/ eye protection/ face protection.

**Response:**

P370+P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235: Store in a well-ventilated place. Keep cool.

**Disposal:**

P501: Dispose of contents/ container to an approved waste disposal plant.

**SECTION 3: Composition/information on ingredients**

Synonyms : Liquid Acid Gelling Agent

Molecular formula : Mixture

Chemical name	CAS-No. / EINECS-No.	Concentration [wt%]
C12-C14 Isoalkanes	68551-19-9	0 - 60
Distillates (petroleum), hydrotreated light	64742-47-8	0 - 60

**SECTION 4: First aid measures**

General advice : No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

**Notes to physician**

Treatment : Treat symptomatically.

**SECTION 5: Firefighting measures**Flash point : 93°C (199°F)  
Method: closed cup

Autoignition temperature : 232°C (450°F)

Suitable extinguishing : Carbon dioxide (CO2).

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

media

Unsuitable extinguishing media : High volume water jet.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

**SECTION 6: Accidental release measures**

Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

**SECTION 7: Handling and storage****Handling**

Advice on safe handling : Avoid formation of aerosol. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

**Storage**

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Uses advised against : This material should not be used for purposes other than the identified uses in section 1 without expert advice.

Use : Oilfield Fluids Additive

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

**SECTION 8: Exposure controls/personal protection****Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1,200 mg/m3	RCP,

RCP Reciprocal Calculation Procedure

**CN**

Components	Basis	Value	Control parameters	Note
Not listed				

Not listed

**Engineering measures**

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

- Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors, Dusts and Mists. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant protective clothing. Footwear protecting against chemicals.
- Hygiene measures : Wash hands before breaks and at the end of workday.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Physical state : liquid  
Color : White  
Odor : Slight hydrocarbon

**Safety data**

Flash point : 93°C (199°F)  
Method: closed cup

Lower explosion limit : No data available

Upper explosion limit : No data available

Oxidizing properties : No

Autoignition temperature : 232°C (450°F)

Molecular formula : Mixture

Molecular weight : Not applicable

pH : 7

Freezing point : No data available

Boiling point/boiling range : 224-275°C (435-527°F)

Vapor pressure : 0.01 PSI  
at 25°C (77°F)

Relative density : 0.96  
at 15.6 °C (60.1 °F)

Density : 958.6 g/l

Water solubility : dispersible

Partition coefficient: n-  
octanol/water : No data available

Viscosity, kinematic : 79007 cSt

Relative vapor density : 3  
(Air = 1.0)

Evaporation rate : < 1

**SECTION 10: Stability and reactivity**

**Reactivity** : Stable at normal ambient temperature and pressure.

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

<b>Chemical stability</b>	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
<b>Possibility of hazardous reactions</b>	
<b>Hazardous reactions</b>	: Further information: No decomposition if stored and applied as directed.  Hazardous reactions: Vapors may form explosive mixture with air.
<b>Conditions to avoid</b>	: Heat, flames and sparks.
<b>Materials to avoid</b>	: No data available.
<b>Other data</b>	: No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****Acute oral toxicity**

C12-C14 Isoalkanes : LD50: > 5,000 mg/kg  
Species: Rat  
Sex: male and female  
Method: OECD Test Guideline 401  
Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : LD50: > 15,000 mg/kg  
Species: Rat  
Sex: male and female  
Method: OECD Test Guideline 423  
Information given is based on data obtained from similar substances.

**Acute inhalation toxicity**

C12-C14 Isoalkanes : LC50: > 4.9 mg/l  
Exposure time: 4 h  
Species: Rat  
Sex: male and female  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.  
Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : LC50: > 4.9 mg/l  
Exposure time: 4 h  
Species: Rat  
Sex: male and female  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Information given is based on data obtained from similar substances.

**Acute dermal toxicity**

C12-C14 Isoalkanes : LD50: > 2,000 - 2,500 mg/kg  
 Species: Rabbit  
 Sex: male and female  
 Method: OECD Test Guideline 402  
 Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : LD50: > 5,000 mg/kg  
 Species: Rat  
 Sex: male and female  
 Method: OECD Test Guideline 402  
 Information given is based on data obtained from similar substances.

**Skin irritation**

C12-C14 Isoalkanes : May irritate skin. Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : No skin irritation  
 Information given is based on data obtained from similar substances.

**Eye irritation**

C12-C14 Isoalkanes : No eye irritation  
 Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : No eye irritation  
 Information given is based on data obtained from similar substances.

**Sensitization**

C12-C14 Isoalkanes : Did not cause sensitization on laboratory animals.  
 Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : Does not cause skin sensitization.  
 Information given is based on data obtained from similar substances.

**Repeated dose toxicity**

C12-C14 Isoalkanes : Species: Rat, male and female  
 Sex: male and female  
 Application Route: oral gavage  
 Dose: 100, 500, 1000 mg/kg/d  
 Exposure time: 13 wk  
 Number of exposures: daily  
 NOEL: > 1000 mg/kg/d  
 Method: OECD Test Guideline 408  
 No adverse effects expected  
 Information given is based on data obtained from similar substances.

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Species: Rat, male and female  
 Sex: male and female  
 Application Route: Inhalation  
 Dose: 2600, 5200, 10400 mg/m<sup>3</sup>  
 Exposure time: 90 d  
 Number of exposures: 6 h/d; 5d/wk  
 NOEL: > 10400 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 413  
 No adverse effects expected  
 Information given is based on data obtained from similar substances.

Distillates (petroleum),  
 hydrotreated light

Species: Rat, male and female  
 Sex: male and female  
 Application Route: oral gavage  
 Dose: 25, 150, 1000 mg/kg/d  
 NOEL: > 1,000 mg/kg  
 Method: OECD Test Guideline 422  
 Information given is based on data obtained from similar substances.

Species: Rat, male and female  
 Sex: male and female  
 Application Route: Inhalation  
 Dose: 2600, 5200, 10400 mg/m<sup>3</sup>  
 Exposure time: 13 wk  
 Number of exposures: 6 h/d, 5 d/wk  
 NOEL: > 10400 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 413  
 Information given is based on data obtained from similar substances.

**Genotoxicity in vitro**

C12-C14 Isoalkanes

: Test Type: Ames test  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative

Test Type: Mouse lymphoma assay  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 476  
 Result: negative

Test Type: Sister Chromatid Exchange Assay  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 479  
 Result: negative

Distillates (petroleum),  
 hydrotreated light

Test Type: Ames test  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Test Type: Chromosome aberration test in vitro  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 473  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

Test Type: In vitro mammalian cell gene mutation test  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 476  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

**Genotoxicity in vivo**

C12-C14 Isoalkanes : Test Type: dominant lethal test  
 Species: Rat  
 Route of Application: Intraperitoneal injection  
 Dose: 300, 900 ppm  
 Method: OECD Test Guideline 478  
 Remarks: Information given is based on data obtained from similar substances.

Distillates (petroleum), hydrotreated light : Test Type: Micronucleus test  
 Species: Mouse  
 Method: OECD Test Guideline 474  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

Test Type: Dominant lethal assay  
 Method: OECD Test Guideline 478  
 Result: negative  
 Remarks: Information given is based on data obtained from similar substances.

**Reproductive toxicity**

Distillates (petroleum), hydrotreated light : No adverse effects expected  
 Information given is based on data obtained from similar substances.

**Developmental Toxicity**

C12-C14 Isoalkanes : Species: Rat  
 Application Route: Inhalation  
 Dose: 0, 400, 1200 ppm  
 Exposure time: 6h  
 Test period: GD 6-15  
 NOAEL Teratogenicity: 1200 ppm  
 NOAEL Maternal: 1200 ppm  
 Information given is based on data obtained from similar substances.

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Species: Rat  
 Application Route: Inhalation  
 Dose: 300, 900 ppm  
 Exposure time: 6h  
 Test period: GD 6-15  
 NOAEL Teratogenicity:  $\geq$  900 ppm  
 NOAEL Maternal:  $\geq$  900 ppm  
 Information given is based on data obtained from similar substances.

Distillates (petroleum),  
 hydrotreated light

No adverse effects expected  
 Information given is based on data obtained from similar substances.

**Liquid HE® 150 Polymer  
 Aspiration toxicity**

: No aspiration toxicity classification.

**CMR effects**

C12-C14 Isoalkanes

: Carcinogenicity: Not available  
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects  
 Teratogenicity: Animal testing did not show any effects on fetal development.  
 Reproductive toxicity: Animal testing did not show any effects on fertility.

**Liquid HE® 150 Polymer  
 Further information**

: Solvents may degrease the skin.  
 No data available.

**SECTION 12: Ecological information****Toxicity to fish**

C12-C14 Isoalkanes

: LL50: > 1,000 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 semi-static test Method: OECD Test Guideline 203  
 Information given is based on data obtained from similar substances.

Distillates (petroleum),  
 hydrotreated light

LL50: > 88,444 mg/l  
 Exposure time: 96 h  
 Species: Oncorhynchus mykiss (rainbow trout)  
 static test Information given is based on data obtained from similar substances.

**Toxicity to daphnia and other aquatic invertebrates**

C12-C14 Isoalkanes

: EL50: > 1,000 mg/l  
 Exposure time: 48 h  
 Species: Daphnia magna (Water flea)  
 static test Method: OECD Test Guideline 202  
 Information given is based on data obtained from similar substances.

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Distillates (petroleum),  
hydrotreated light

EL50: > 1,000 mg/l  
Exposure time: 48 h  
Species: Daphnia magna (Water flea)  
static test Method: OECD Test Guideline 202  
Information given is based on data obtained from similar  
substances.

**Toxicity to algae**

C12-C14 Isoalkanes

: EL50: > 1,000 mg/l  
Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (green algae)  
Growth inhibition Method: OECD Test Guideline 201  
Information given is based on data obtained from similar  
substances.

Distillates (petroleum),  
hydrotreated light

EL50: > 1,000 mg/l  
Exposure time: 72 h  
Species: Pseudokirchneriella subcapitata (algae)  
Growth inhibition Method: OECD Test Guideline 201  
Information given is based on data obtained from similar  
substances.

**Toxicity to fish (Chronic toxicity)**

C12-C14 Isoalkanes

: No data available:

Distillates (petroleum),  
hydrotreated light

NOELR: > 1,000 mg/l  
Exposure time: 28 d  
Method: QSAR modeled data

**Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)**

Distillates (petroleum),  
hydrotreated light

: NOELR: 1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
semi-static test  
Method: OECD Test Guideline 211  
Information given is based on data obtained from similar  
substances.

**Biodegradability**

C12-C14 Isoalkanes

: aerobic  
Result: Readily biodegradable.  
89.8 %  
Testing period: 28 d  
Method: OECD Test Guideline 301F  
Information given is based on data obtained from similar  
substances.

Distillates (petroleum),  
hydrotreated light

: aerobic  
Result: Readily biodegradable.  
68 %

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Testing period: 28 d  
Information given is based on data obtained from similar substances.

**Bioaccumulation**

C12-C14 Isoalkanes : The product may be accumulated in organisms.

Distillates (petroleum),  
hydrotreated light : This material is not expected to bioaccumulate.

**Mobility**

C12-C14 Isoalkanes : immobile

Distillates (petroleum),  
hydrotreated light : No data available

**Results of PBT assessment**

C12-C14 Isoalkanes : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological  
information : No data available

**Ecotoxicology Assessment****Short-term (acute) aquatic hazard**

C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

Distillates (petroleum),  
hydrotreated light : This material is not expected to be harmful to aquatic organisms.

**Long-term (chronic) aquatic hazard**

C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

Distillates (petroleum),  
hydrotreated light : This material is not expected to be harmful to aquatic organisms.

**SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product.

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Testing (ASTM D4206) has shown product does not sustain combustion.

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**Maritime transport in bulk according to IMO instruments**

**SECTION 15: Regulatory information****Notification status**

SDS Number:100000014589

14/16

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

Europe EU REACH	:	This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).
Switzerland CH INV	:	Not in compliance with the inventory
United States of America (USA) TSCA	:	All substances listed as active on the TSCA inventory
Canada DSL	:	All components of this product are on the Canadian DSL
Australia AU AIC	:	On the inventory, or in compliance with the inventory
New Zealand NZIoC	:	Not in compliance with the inventory
Japan ENCS	:	On the inventory, or in compliance with the inventory
Japan ISHL	:	On the inventory, or in compliance with the inventory
Korea KECI	:	Not in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory
China IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TW TCSI	:	On the inventory, or in compliance with the inventory
<b>Other regulations</b>	:	Law on the Prevention and Control of Occupational Diseases

**SECTION 16: Other information**

Print Date : 2026-04-07

**Further information**

Legacy SDS Number : CPC00496

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit

**Liquid HE® 150 Polymer**

Version 2.7

Revision Date 2026-04-02

EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate