

**Liquid Flowzan® Biopolymer**

Version 1.19

Revision Date 2026-05-06

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Liquid Flowzan® Biopolymer
Material : 1106106, 1016833, 1105963
Company : Chevron Phillips Chemical Company LP
Drilling Specialties Company LLC
9500 Lakeside Blvd.
The Woodlands, TX 77381

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
Mexico CHEMTREC 01-800-681-9531 (24 hours)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Argentina: +(54)-1159839431
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)
Belgium: 070 245 245 (24 hours/day, 7 days/week)
Bulgaria: +359 2 9154 233
Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
Cyprus: 1401
Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
Denmark: Danish Poison Center (Gifflinjen): +45 8212 1212
Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Finland: 0800 147 111 09 471 977 (24 hours/day)
France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
Iceland: 543 2222 (24 hours/day, 7 days/week)
Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Classification

: Flammable liquids, Category 4

Labeling

Signal Word : Warning

Hazard Statements : H227: Combustible liquid.

Precautionary Statements : **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
Response:
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
 P403 Store in a well-ventilated place.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3: Composition/information on ingredients

Synonyms : Drilling Mud Additive

Molecular formula : Mixture

Component	CAS-No.	Weight %
Distillates (petroleum), hydrotreated light	64742-47-8	40 - 60
C12-C14 Isoalkanes	68551-19-9	40 - 60

SECTION 4: First aid measures

General advice : No hazards which require special first aid measures.

If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

Notes to physician

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

Flash point : 93°C (199°F)
Method: closed cup

Autoignition temperature : >200°C (>392°F)

Suitable extinguishing media : Carbon dioxide (CO₂).

Unsuitable extinguishing media : High volume water jet.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Further information : For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.

Fire and explosion protection : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

SECTION 6: Accidental release measures

Environmental precautions : Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Avoid formation of aerosol. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep in a well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Chevron Phillips Chemical Company LP**

Components	Basis	Value	Control parameters	Note
C12-C14 Isoalkanes	Manufacturer	TWA	1,200 mg/m ³	RCP,

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Personal protective equipment

- Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Organic Vapors, Dusts and Mists. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant protective clothing. Footwear protecting against chemicals.
- Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Physical state : liquid
 Color : Light brown
 Odor : negligible

Safety data

- Flash point : 93°C (199°F)
 Method: closed cup
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : No
- Autoignition temperature : >200°C (>392°F)
- Molecular formula : Mixture

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Molecular weight	: Not applicable
pH	: No data available
Pour point	: No data available
Boiling point/boiling range	: 224-275°C (435-527°F)
Vapor pressure	: No data available
Relative density	: 0.97
Water solubility	: soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity, dynamic	: 72,000 cP
Relative vapor density	: No data available
Evaporation rate	: No data available

SECTION 10: Stability and reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Further information: No decomposition if stored and applied as directed. Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Acute oral toxicity	
Distillates (petroleum), hydrotreated light	: LD50: > 15,000 mg/kg Species: Rat Sex: male and female

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Distillates (petroleum), hydrotreated light : Does not cause skin sensitization. Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes Did not cause sensitization on laboratory animals. Information given is based on data obtained from similar substances.

Repeated dose toxicity

Distillates (petroleum), hydrotreated light : Species: Rat, male and female
Sex: male and female
Application Route: oral gavage
Dose: 25, 150, 1000 mg/kg/d
NOEL: > 1,000 mg/kg
Method: OECD Test Guideline 422
Information given is based on data obtained from similar substances.

Species: Rat, male and female
Sex: male and female
Application Route: Inhalation
Dose: 2600, 5200, 10400 mg/m³
Exposure time: 13 wk
Number of exposures: 6 h/d, 5 d/wk
NOEL: > 10400 mg/m³
Method: OECD Test Guideline 413
Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes Species: Rat, male and female
Sex: male and female
Application Route: oral gavage
Dose: 100, 500, 1000 mg/kg/d
Exposure time: 13 wk
Number of exposures: daily
NOEL: > 1000 mg/kg/d
Method: OECD Test Guideline 408
No adverse effects expected
Information given is based on data obtained from similar substances.

Species: Rat, male and female
Sex: male and female
Application Route: Inhalation
Dose: 2600, 5200, 10400 mg/m³
Exposure time: 90 d
Number of exposures: 6 h/d; 5d/wk
NOEL: > 10400 mg/m³
Method: OECD Test Guideline 413
No adverse effects expected
Information given is based on data obtained from similar substances.

Genotoxicity in vitro

Distillates (petroleum), hydrotreated light : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
Remarks: Information given is based on data obtained from

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

similar substances.

Test Type: Chromosome aberration test in vitro
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 473
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

Test Type: In vitro mammalian cell gene mutation test
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes

Test Type: Ames test
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Mouse lymphoma assay
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: negative

Test Type: Sister Chromatid Exchange Assay
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 479
 Result: negative

Genotoxicity in vivo

Distillates (petroleum),
 hydrotreated light

: Test Type: Micronucleus test
 Species: Mouse
 Method: OECD Test Guideline 474
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

Test Type: Dominant lethal assay
 Method: OECD Test Guideline 478
 Result: negative
 Remarks: Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes

Test Type: dominant lethal test
 Species: Rat
 Route of Application: Intraperitoneal injection
 Dose: 300, 900 ppm
 Method: OECD Test Guideline 478
 Remarks: Information given is based on data obtained from similar substances.

Reproductive toxicity

Distillates (petroleum),
 hydrotreated light

: No adverse effects expected
 Information given is based on data obtained from similar substances.

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Developmental Toxicity

Distillates (petroleum), hydrotreated light : No adverse effects expected
Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes Species: Rat
Application Route: Inhalation
Dose: 0, 400, 1200 ppm
Exposure time: 6h
Test period: GD 6-15
NOAEL Teratogenicity: 1200 ppm
NOAEL Maternal: 1200 ppm
Information given is based on data obtained from similar substances.

Species: Rat
Application Route: Inhalation
Dose: 300, 900 ppm
Exposure time: 6h
Test period: GD 6-15
NOAEL Teratogenicity: \geq 900 ppm
NOAEL Maternal: \geq 900 ppm
Information given is based on data obtained from similar substances.

Liquid Flowzan® Biopolymer

Aspiration toxicity : No aspiration toxicity classification.

CMR effects

C12-C14 Isoalkanes : Carcinogenicity: Not available
Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects., In vivo tests did not show mutagenic effects
Teratogenicity: Animal testing did not show any effects on fetal development.
Reproductive toxicity: Animal testing did not show any effects on fertility.

Liquid Flowzan® Biopolymer

Further information : No data available.

SECTION 12: Ecological information**Toxicity to fish**

Distillates (petroleum), hydrotreated light : LL50: > 88,444 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
static test Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes LL50: > 1,000 mg/l
Exposure time: 96 h
Species: Oncorhynchus mykiss (rainbow trout)
semi-static test Method: OECD Test Guideline 203

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates

Distillates (petroleum), hydrotreated light : EL50: > 1,000 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
static test Method: OECD Test Guideline 202
Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes EL50: > 1,000 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
static test Method: OECD Test Guideline 202
Information given is based on data obtained from similar substances.

Toxicity to algae

Distillates (petroleum), hydrotreated light : EL50: > 1,000 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (algae)
Growth inhibition Method: OECD Test Guideline 201
Information given is based on data obtained from similar substances.

C12-C14 Isoalkanes EL50: > 1,000 mg/l
Exposure time: 72 h
Species: Pseudokirchneriella subcapitata (green algae)
Growth inhibition Method: OECD Test Guideline 201
Information given is based on data obtained from similar substances.

Toxicity to fish (Chronic toxicity)

Distillates (petroleum), hydrotreated light : NOELR: > 1,000 mg/l
Exposure time: 28 d
Method: QSAR modeled data

C12-C14 Isoalkanes No data available:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Distillates (petroleum), hydrotreated light : NOELR: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
semi-static test
Method: OECD Test Guideline 211
Information given is based on data obtained from similar substances.

Biodegradability : Taking into consideration the properties of several ingredients,

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

the product is estimated not to be readily biodegradable according to OECD classification.

Elimination information (persistence and degradability)

Bioaccumulation

- Distillates (petroleum), hydrotreated light C12-C14 Isoalkanes : This material is not expected to bioaccumulate.
 C12-C14 Isoalkanes : The product may be accumulated in organisms.

Mobility

- Distillates (petroleum), hydrotreated light C12-C14 Isoalkanes : No data available
 C12-C14 Isoalkanes : immobile

Results of PBT assessment

- C12-C14 Isoalkanes : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : This material is not expected to be harmful to aquatic organisms.

No data available

Ecotoxicology Assessment

Short-term (acute) aquatic hazard

- Distillates (petroleum), hydrotreated light : This material is not expected to be harmful to aquatic organisms.
 C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

Long-term (chronic) aquatic hazard

- Distillates (petroleum), hydrotreated light : This material is not expected to be harmful to aquatic organisms.
 C12-C14 Isoalkanes : This material is not expected to be harmful to aquatic organisms.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

- Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container.

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Testing (ASTM D4206) has shown product does not sustain combustion.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Maritime transport in bulk according to IMO instruments

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

SECTION 15: Regulatory information**National legislation****SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : This material does not contain any components with a section 302 EHS TPQ.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations

Massachusetts Right To Know : No components are subject to the Massachusetts Right to Know Act.

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

Pennsylvania Right To Know

: C12-C14 Isoalkanes - 68551-19-9
Distillates (petroleum), hydrotreated light - 64742-47-8**Notification status**

Europe EU REACH : This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).

Switzerland CH INV : Not in compliance with the inventory

United States of America (USA) TSCA : All substances listed as active on the TSCA inventory

Canada DSL : All components of this product are on the Canadian DSL

Australia AU AIC : On the inventory, or in compliance with the inventory

New Zealand NZIoC : On the inventory, or in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory

Japan ISHL : On the inventory, or in compliance with the inventory

Korea KECI : Not in compliance with the inventory


Philippines PICCS : Not in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory

Taiwan TW TCSI : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 0
Fire Hazard: 2
Reactivity Hazard: 0



Revision Date : 2026-05-06

Date of last issue : 2025-06-02

Print Date : 2026-05-14

Further information

Legacy SDS Number : 630920

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

Liquid Flowzan® Biopolymer

Version 1.19

Revision Date 2026-05-06

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate