



Soltex® Additive

Version 2.21

Revision Date 2026-05-26

according to GB/T 16483 and GB/T 17519

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : Soltex® Additive
 Material : 1126278, 1016807
 Use : Drilling Mud Additive
 Uses advised against : This material should not be used for purposes other than the identified uses in section 1 without expert advice.

Company : Chevron Phillips Chemical Company LP
 Drilling Specialties Company LLC
 9500 Lakeside Blvd.
 The Woodlands, TX 77381

Local : See Company Address

Emergency telephone:

Health:

866.442.9628 (North America)
 1.832.813.4984 (International)

Transport:

CHEMTREC 800.424.9300 or 703.527.3887(int'l)
 Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
 Mexico CHEMTREC 01-800-681-9531 (24 hours)
 South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
 Argentina: +(54)-1159839431
 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)
 Belgium: 070 245 245 (24 hours/day, 7 days/week)
 Bulgaria: +359 2 9154 233
 Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
 Cyprus: 1401
 Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
 Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212
 Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Finland: 0800 147 111 09 471 977 (24 hours/day)
 France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
 Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
 Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
 Iceland: 543 2222 (24 hours/day, 7 days/week)
 Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726; POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;

Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)

Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Lithuania: +370 (85) 2362052

Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)

Malta: +356 2395 2000

The Netherlands: NVIC: +31 (0)88 755 8000

Norway: 22 59 13 00 (24 hours/day, 7 days/week)

Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

Portugal: CIAV phone number: +351 800 250 250

Romania: +40213183606

Slovakia: +421 2 5477 4166

Slovenia: Phone number: 112

Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)

Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

GHS Classification and Labeling: Follow GB 13690, GB 15258 and GB 30000.2 to GB 30000.29 (GHS 2011)

Emergency Overview**Danger**

Form: Powder **Physical state:** solid **Color:** Black **Odor:** no odor

Hazards : May cause cancer by inhalation.

Classification

: Carcinogenicity, Category 1A, Inhalation

Labeling

Symbol(s) :



Signal Word :

: Danger

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Hazard Statements : H350: May cause cancer by inhalation.

Precautionary Statements : **Prevention:**
 P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P308 + P313: IF exposed or concerned: Get medical advice/ attention.
Storage:
 P405: Store locked up.
Disposal:
 P501: Dispose of contents/ container to an approved waste disposal plant.

SECTION 3: Composition/information on ingredients

Synonyms : Drilling Mud Additive

Molecular formula : Mixture

Chemical name	CAS-No. / EINECS-No.	Concentration [wt%]
Asphalt, Sulfonated, Sodium Salt	68201-32-1	40 - 70
Sodium Sulfate	7757-82-6	10 - 25
Crystalline Silica	14808-60-7	0.1 - 2.5

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance.

If inhaled : If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

Notes to physician

Treatment : Treat symptomatically.

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

SECTION 5: Firefighting measures

Flash point	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	:	High volume water jet.
Specific hazards during fire fighting	:	Risks of ignition followed by flame propagation or secondary explosions can be caused by the accumulation of dust, e.g. on floors and ledges.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire and explosion protection	:	Avoid dust formation. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Provide appropriate exhaust ventilation at places where dust is formed.
Hazardous decomposition products	:	Carbon oxides. Sulfur oxides.

SECTION 6: Accidental release measures

Personal precautions	:	Use personal protective equipment. Avoid dust formation. Avoid breathing dust.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.
Additional advice	:	Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

SECTION 7: Handling and storage**Handling**

Advice on safe handling	:	Avoid formation of respirable particles. Do not breathe
-------------------------	---	---

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient.

Advice on protection against fire and explosion : Avoid dust formation. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Provide appropriate exhaust ventilation at places where dust is formed.

Storage

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Uses advised against : This material should not be used for purposes other than the identified uses in section 1 without expert advice.

Use : Drilling Mud Additive

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****CN**

Components	Basis	Value	Control parameters	Note
Crystalline Silica	CN OEL	PC-TWA	0.7 mg/m3	G1, Respirable
	CN OEL	PC-TWA	1 mg/m3	G1, Total
	CN OEL	PC-TWA	0.2 mg/m3	G1, Respirable
	CN OEL	PC-TWA	0.5 mg/m3	G1, Total
	CN OEL	PC-TWA	0.3 mg/m3	G1, Respirable
	CN OEL	PC-TWA	0.7 mg/m3	G1, Total
	CN OEL	PC-TWA	0.5 mg/m3	G1, Total dust
	CN OEL	PC-TWA	0.2 mg/m3	G1, (respirable dust)
	CN OEL	PC-TWA	0.7 mg/m3	G1, Total dust
	CN OEL	PC-TWA	0.3 mg/m3	G1, (respirable dust)
	CN OEL	PC-TWA	1 mg/m3	G1, Total dust
	CN OEL	PC-TWA	0.7 mg/m3	G1, (respirable dust)

G1 G1 - Carcinogenic to humans

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as: Air-Purifying Respirator for Dusts and Mists / P100. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Safety glasses.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Protective suit. Safety shoes.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : Powder
- Physical state : solid
- Color : Black
- Odor : no odor
- Odor Threshold : Not applicable

Safety data

- Flash point : Not applicable
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Oxidizing properties : No
- Autoignition temperature : Not applicable
- Molecular formula : Mixture
- Molecular weight : No data available

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

pH	: 7 - 10
Pour point	: Not applicable
Boiling point/boiling range	: Not applicable
Vapor pressure	: Not applicable
Relative density	: Not applicable
Density	: 1.54 g/cm ³
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: Not applicable
Relative vapor density	: Not applicable
Evaporation rate	: Not applicable

SECTION 10: Stability and reactivity

Reactivity	: Stable at normal ambient temperature and pressure.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur. Further information: No decomposition if stored and applied as directed.
Conditions to avoid	: Generation of Dusts.
Materials to avoid	: No data available.
Hazardous decomposition products	: Carbon oxides Sulfur oxides
Other data	: No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Acute oral toxicity**

SDS Number:100000013416

7/14

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Asphalt, Sulfonated, Sodium Salt : LD50: > 5,000 mg/kg
 Sodium Sulfate LD50 Oral: >2000 milligram per kilogram
 Species: Rat
 Sex: female
 Method: OECD Test Guideline 423
 Test substance: yes

Acute inhalation toxicity

Asphalt, Sulfonated, Sodium Salt : LC50: > 5.3 mg/l
 Exposure time: 4 h
 Species: Rat
 Sex: male and female
 Test atmosphere: dust/mist
 Method: OECD Test Guideline 403
 Rats exposed to a 5.3 mg/L dust aerosol for 4-hr resulted in effects generally expected with high concentrations of dust aerosols made of relatively dense particles. Higher lung weight and atelectasis persisted after the 14-day recovery period. There were no reports of lethality or any significant clinical observations. There was however an acute inflammatory response with evidence of recovery after 14-days. The presence of particulate matter with indication of partial clearance from the lung after the 14-day recovery period was noted. These effects would not be expected during normal operating conditions when using this substance.

Sodium Sulfate LC50: >2400milligram per cubic meter
 Exposure time: 4 h
 Test atmosphere: dust/mist

Acute dermal toxicity

Asphalt, Sulfonated, Sodium Salt : No data available

Sodium Sulfate : > 4,000 mg/kg
 Species: Rabbit

Skin irritation

Asphalt, Sulfonated, Sodium Salt : No skin irritation
 largely based on animal evidence.
 Sodium Sulfate No skin irritation

Eye irritation

Asphalt, Sulfonated, Sodium Salt : No eye irritation
 largely based on animal evidence.
 Sodium Sulfate

Sensitization

Asphalt, Sulfonated, Sodium Salt : Did not cause sensitization on laboratory animals.
 largely based on animal evidence.
 Sodium Sulfate Did not cause sensitization on laboratory animals.

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Repeated dose toxicity

Asphalt, Sulfonated, Sodium Salt : Species: Rat, Male and female
Sex: Male and female
Application Route: oral gavage
Dose: 0, 250, 500, 1000 mg/kg
Exposure time: 43 - 54 D
Number of exposures: daily
NOEL: 1,000 mg/kg
Method: OECD Guideline 422

Genotoxicity in vitro

Asphalt, Sulfonated, Sodium Salt : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Reproductive toxicity

Asphalt, Sulfonated, Sodium Salt : Species: Rat
Sex: male and female
Application Route: oral gavage
Dose: 0, 250, 500, 1000 mg/kg
Exposure time: 43-54 D
Number of exposures: daily
Method: OECD Guideline 422
NOAEL Parent: 1,000 mg/kg
NOAEL F1: 1,000 mg/kg

Developmental Toxicity

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Asphalt, Sulfonated, Sodium Salt : Species: Rat
 Application Route: oral gavage
 Dose: 0, 250, 500, 1000 mg/kg
 Number of exposures: daily
 Test period: 54 D
 NOAEL Teratogenicity: 1,000 mg/kg
 NOAEL Maternal: 1,000 mg/kg

Species: Rat
 Application Route: oral gavage
 Dose: 0, 100, 300, 1000 mg/kg
 Number of exposures: daily
 Test period: GD 6 - 20
 Method: OECD Guideline 414
 NOAEL Teratogenicity: 1,000 mg/kg
 NOAEL Maternal: 1,000 mg/kg

CMR effects

Asphalt, Sulfonated, Sodium Salt : Carcinogenicity: Not available
 Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: Animal testing did not show any effects on fertility.

Crystalline Silica : Carcinogenicity: Human carcinogen.

Soltex® Additive

Further information : Chronic Health Hazard.

SECTION 12: Ecological information**Ecotoxicity effects****Toxicity to fish**

Asphalt, Sulfonated, Sodium Salt : LC50: > 240 mg/l
 Exposure time: 96 h
 Species: Scophthalmus maximus (Flatfish, Flounder)
 semi-static test Method: OECD Test Guideline 203

Sodium Sulfate : 13,500 - 14,000 mg/l
 Exposure time: 96 h
 Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates

Asphalt, Sulfonated, Sodium Salt : LC50: 380 mg/l
 Exposure time: 48 h
 Species: Acartia tonsa (Marine Copepod)
 static test Method: ISO TC147/SC5/WG2

Sodium Sulfate : 4,547 mg/l
 Exposure time: 96 h
 Species: Daphnia magna (Water flea)

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Toxicity to algae

Asphalt, Sulfonated, Sodium Salt : EC50: 240 mg/l
 Exposure time: 72 h
 Species: Skeletonema costatum (Marine Algae)
 static test Method: ISO 10253

Biodegradability : This material is not expected to be readily biodegradable.

Elimination information (persistence and degradability)

Bioaccumulation : No data available

Mobility : No data available

Results of PBT assessment
 Asphalt, Sulfonated, Sodium Salt : Non-classified PBT substance, Non-classified vPvB substance
 Additional ecological information : This material is not expected to be harmful to aquatic organisms.

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : This material is not expected to be harmful to aquatic organisms.

Long-term (chronic) aquatic hazard : This material is not expected to be harmful to aquatic organisms.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information**China. Banned or Severely Restricted Toxic Chemicals Regulation for Environmental Management of the First Import of Chemicals and the Import & Export of Toxic Chemicals, Article 3)**

Crystalline Silica : declarable

Notification status

Europe EU REACH : This product is in full compliance according to REACH regulation 1907/2006/EC.

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) TSCA : All substances listed as active on the TSCA inventory

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

Canada DSL	:	All components of this product are on the Canadian DSL
Australia AU AIIC	:	All substances are listed on AIIC. Obligations to provide information to AICIS apply.
New Zealand NZIoC	:	On the inventory, or in compliance with the inventory
Japan ENCS	:	Not in compliance with the inventory
Philippines PICCS	:	Not in compliance with the inventory
Korea KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations.
China IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TW TCSI	:	Not in compliance with the inventory
Other regulations	:	Law on Prevention and Control of Environment Pollution by Solid Waste, Regulation on the Safety Management of Hazardous Chemicals, Provisions on the Safe Use of Chemicals at Workplace, GB 30000 Specification for classification and labeling of chemicals, Law on the Prevention and Control of Occupational Diseases

SECTION 16: Other information

Print Date : 2026-05-29

Further information

Legacy SDS Number : 59370

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration

Soltex® Additive

Version 2.21

Revision Date 2026-05-26

EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate