Toluene Standardization Fuel 96.9

Version 1.8 Revision Date 2026-10-26

According to Regulation (EC) No. 1907/2006, Regulation (EC) No. 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1

Product information

Product Name : Toluene Standardization Fuel 96.9
Material : 1024367, 1024366, 1024365, 1024364

EC-No.Registration number

Chemical name	CAS-No. EC-No. Index No.	Legal Entity Registration number
Toluene	108-88-3 203-625-9 601-021-00-3	Chevron Phillips Chemicals International NV 01-2119471310-51-0116
Toluene	108-88-3 203-625-9 601-021-00-3	Chevron Phillips Chemical Company LP 01-2119471310-51-0156
2,2,4-Trimethylpentane (Isooctane)	540-84-1 208-759-1 601-009-00-8	Chevron Phillips Chemicals International NV 01-2119457965-22-0002
2,2,4-Trimethylpentane (Isooctane)	540-84-1 208-759-1 601-009-00-8	Chevron Phillips Chemical Company LP 01-2119457965-22-0013

Unique Formula Identifier : UT10-S01A-G001-QDPF

1.2

Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified Uses Supported : Fuel

1.3

Details of the supplier of the safety data sheet

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
9500 Lakeside Blvd.
The Woodlands, TX 77381

1.4

Emergency telephone:

Health:
866.442.9628 (North America)

1.832.813.4984 (International)
Transport:
CHEMTREC 800.424.9300 or 703.527.3887(int'l)
Asia: CHEMWATCH (+612 9186 1132) China: 0532 8388 9090
Mexico CHEMTREC 01-800-681-9531 (24 hours)
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600
Argentina: +(54)-1159839431
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Austria: VIZ +43 1 406 43 43 (24 hours/day, 7 days/week)
Belgium: 070 245 245 (24 hours/day, 7 days/week)
Bulgaria: +359 2 9154 233
Croatia: +3851 2348 342 (24 hours/day, 7 days/week)
Cyprus: 1401
Czech Republic: Toxicological Information Center +420 224 919 293, +420 224 915 402
Denmark: Danish Poison Center (Giftlinjen): +45 8212 1212
Estonia: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Finland: 0800 147 111 09 471 977 (24 hours/day)
France: ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week)
Germany: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Greece: (0030) 2107793777 (24 hours/day, 7 days/week)
Hungary: +36-80-201-199 (24 hours/day, 7 days/week)
Iceland: 543 2222 (24 hours/day, 7 days/week)
Ireland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Italy: POISON CENTER MILAN – Azienda Ospedaliera Niguarda Ca` Grande Tel. +39 02 66101029; POISON CENTER ROME – Policlinico “Agostino Gemelli”, Servizio di tossicologia clinica Tel. +39 06 3054343; POISON CENTER ROME – Ospedale Pediatrico Bambino Gesù Tel. +39 06 68593726;POISON CENTER ROME – Policlinico “Umberto I” Tel. +39 06 4997 8000; POISON CENTER FOGGIA – Azienda Ospedaliera Universitaria Riuniti Tel. +39 0881 732326; POISON CENTER NAPLES – Azienda Ospedaliera “Antonio Cardarelli” Tel. +39 081 7472870; POISON CENTER FLORENCE – Azienda Ospedaliera universitaria Careggi Tel. +39 055 7947819; POISON CENTER PAVIA – IRCCS Fondazione Salvatore Maugeri Tel. +39 0382 24444; POISON CENTER BERGAMO – Azienda Ospedaliera “Papa Giovanni XXIII” Tel. 800 883 300; POISON CENTER VERONA – Azienda Ospedaliera Universitaria integrata Tel. 800 011 858;
Latvia: State Fire and Rescue Service, phone number: 112; Toxicology and Sepsis Clinic Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1038, phone number +371 67042473. (24 hours.)
Liechtenstein: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Lithuania: +370 (85) 2362052
Luxembourg: (+352) 8002 5500 (24 hours/day, 7 days/week)
Malta: +356 2395 2000
The Netherlands: NVIC: +31 (0)88 755 8000
Norway: 22 59 13 00 (24 hours/day, 7 days/week)
Poland: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Portugal: CIAV phone number: +351 800 250 250
Romania: +40213183606
Slovakia: +421 2 5477 4166
Slovenia: Phone number: 112
Spain: National Emergency Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24 hours/day, 7 days/week)
Sweden: 112 – ask for Poisons Information

Organization that prepared the SDS	:	Product Safety and Toxicology Group
E-mail address	:	SDS@CPChem.com
Website	:	www.CPChem.com

SECTION 2: Hazards identification

2.1

Classification of the substance or mixture
REGULATION (EC) No 1272/2008

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements :	H225	Highly flammable liquid and vapor.
	H304	May be fatal if swallowed and enters airways.
	H315	Causes skin irritation.
	H336	May cause drowsiness or dizziness.
	H361d	Suspected of damaging the unborn child.
	H373	May cause damage to organs through prolonged or repeated exposure.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary Statements :	**Prevention:**	
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe mist or vapors.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
	Response:	
	P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
	P331	Do NOT induce vomiting.
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:
- 108-88-3 Toluene

2.3

Other hazards

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Synonyms : Reference Fuel

Molecular formula : Mixture

Hazardous ingredients

Chemical name	CAS-No. EC-No. Index No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]	Specific Conc. Limits, M-factors and ATEs
Toluene	108-88-3 203-625-9 601-021-00-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361d STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	73 - 75	
n-Heptane	142-82-5 205-563-8 601-008-00-2	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	20 - 22	
2,2,4-Trimethylpentane (Isooctane)	540-84-1 208-759-1 601-009-00-8	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315	4 - 6	

		STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.

If inhaled : Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed
Notes to physician

Risks : May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

Flash point : 4°C (39°F)
Method: closed cup
estimated

Autoignition temperature : 528,9°C (984,0°F)

5.1

Extinguishing media

Suitable extinguishing media	:	Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.
Unsuitable extinguishing media	:	High volume water jet.

5.2

Special hazards arising from the substance or mixture

Specific hazards during fire fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.

5.3

Advice for firefighters

Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	:	Hydrocarbons. Carbon oxides.

SECTION 6: Accidental release measures

6.1

Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.2

Environmental precautions

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3

Methods and materials for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4

Reference to other sections

SECTION 7: Handling and storage

7.1

Precautions for safe handling
Handling

Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

7.2

Conditions for safe storage, including any incompatibilities

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection

8.1

Control parameters
Ingredients with workplace control parameters

SK

Zložky	Podstata	Hodnota	Kontrolné parametre	Poznámka
Toluene	SK OEL	NPEL priemerný	50 ppm, 192 mg/m3	K,
	SK OEL	NPEL krátkodobý	100 ppm, 384 mg/m3	K,
n-heptane	SK OEL	NPEL priemerný	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	SK OEL	NPEL krátkodobý	300 ppm, 1.400 mg/m3	
	SK OEL	NPEL priemerný	200 ppm, 900 mg/m3	

K Znamená, ze faktor môže byt' l'ahko absorbovaný kožou. Niektoré faktory, ktoré l'ahko prenikajú kožou, môžu spôsobovat' až smrtel'né otravy, éasto bez varovných príznakov (napr. anilín, nitrobenzén, nitroglykol, fenoly a pod.). Pri látkach s významným prienikom cez kožu, éi už v podobe kvapalín alebo pár, je osobitne dôležité zabránit' kožnému kontaktu.

SI

Sestavine	Osnova	Vrednost	Parametri nadzora	Pripomba
Toluene	SI OEL	MV	50 ppm, 192 mg/m3	RD-2, K,
	SI OEL	KTV	100 ppm, 384 mg/m3	RD-2, K,
n-heptane	SI OEL	MV	500 ppm, 2.085 mg/m3	
	SI OEL	KTV	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	SI OEL	MV	500 ppm, 2.400 mg/m3	
	SI OEL	KTV	1.000 ppm, 4.800 mg/m3	

K Lastnost lažjega prehajanja snovi v organizem skozi kožo
RD-2 Strupeno za razmnoževanje - lahko škoduje nerojenemu otroku - kategorija 2

SE

Beståndsdelar	Grundval	Värde	Kontrollparametrar	Anmärkning
Toluene	AFS 2023:14	NGV	50 ppm, 192 mg/m3	H,
	AFS 2023:14	KGV	100 ppm, 384 mg/m3	H,
n-heptane	AFS 2023:14	NGV	200 ppm, 800 mg/m3	
	AFS 2023:14	KGV	300 ppm, 1.200 mg/m3	V,
2,2,4-Trimethylpentane (Isooctane)	AFS 2023:14	NGV	200 ppm, 900 mg/m3	
	AFS 2023:14	KGV	300 ppm, 1.400 mg/m3	V,

H Ämnet tas lätt upp genom huden
V Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas

RU

Компоненты	Основа	Величина	Параметры контроля	Заметка
Toluene	RU OEL	ПДК	50 mg/m3	3,
	RU OEL	ПДК разовая	150 mg/m3	3,
	RU OEL	ПДК	50 mg/m3	3, пары и/или газы
	RU OEL	ПДК разовая	150 mg/m3	3, пары и/или газы
	RU OEL	ПДК	50 mg/m3	3, пары и/или газы
	RU OEL	ПДК разовая	150 mg/m3	3, пары и/или газы
	РФ ПДК	ПДК	50 mg/m3	3, пары и/или газы
	РФ ПДК	ПДК разовая	150 mg/m3	3, пары и/или газы
n-heptane	RU OEL	ПДК	300 mg/m3	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m3	4, пары и/или газы
	RU OEL	ПДК	300 mg/m3	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m3	4, пары и/или газы
2,2,4-Trimethylpentane (Isooctane)	RU OEL	ПДК	300 mg/m3	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m3	4, пары и/или газы
	RU OEL	ПДК	300 mg/m3	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m3	4, пары и/или газы
Benzene	RU OEL	ПДК	5 mg/m3	+, 2, К, пары и/или газы
	RU OEL	ПДК разовая	15 mg/m3	+, 2, К, пары и/или газы
	RU OEL	ПДК	5 mg/m3	2, К, пары и/или газы
	RU OEL	ПДК разовая	15 mg/m3	2, К, пары и/или газы
	РФ ПДК	ПДК	5 mg/m3	2, CANCER, +, пары и/или газы
	РФ ПДК	ПДК разовая	15 mg/m3	2, CANCER, +, пары и/или газы
Octane Isomers	RU OEL	ПДК	300 mg/m3	4, пары и/или газы
	RU OEL	ПДК разовая	900 mg/m3	4, пары и/или газы

\+ соединения, при работе с которыми требуется специальная защита кожи и глаз; символ проставлен вслед за наименованием вещества
2 2 класс - высокоопасные
3 3 класс - опасные
4 4 класс - умеренно опасные
CANCER Канцероген
К канцерогены

RS

Компоненты	Основа	Величина	Параметры контроля	Заметка
Toluene	RS OEL	GVI	50 ppm, 192 mg/m3	K, EU**,
	RS OEL	KGVI	100 ppm, 384 mg/m3	K, EU**,
n-heptane	RS OEL	GVI	500 ppm, 2.085 mg/m3	EU*,

EU* Substance mentioned in indicative exposure limit values in Directive 2000/39 / EC (first list)
EU** Substance mentioned in indicative exposure limit values in Directive 2006/15 / EC (second list)
K This chemical substance can adversely affect the skin.

RO

Componente	Sursă	Valoare	Parametri de control	Notă
Toluene	RO OEL	TWA	50 ppm, 192 mg/m3	R2, P,
	RO OEL	STEL	100 ppm, 384 mg/m3	R2, P,
n-heptane	RO OEL	TWA	500 ppm, 2.085 mg/m3	

P Contribuţie substanţială la încărcarea totală din organism prin posibilă expunere cutanată.
R2 susceptibil de a dăuna fertilităţii

PT

Componentes	Base	Valor	Parâmetros de controle	Nota
Toluene	PT OEL	VLE-MP	20 ppm,	P, A4,
	PT DL 305/2007	oito horas	50 ppm, 192 mg/m3	Cutânea,
	PT DL 305/2007	curta duração	100 ppm, 384 mg/m3	Cutânea,
n-heptane	PT DL 305/2007	oito horas	500 ppm, 2.085 mg/m3	
	PT OEL	VLE-MP	400 ppm,	
	PT OEL	VLE_CD	500 ppm,	

A4 Agente não classificável como carcinogénico no Homem.

Cutânea Uma notação cutânea atribuída ao valor limite de exposição profissional assinala a possibilidade de absorção significativa através de pele.
P Perigo de absorção cutânea

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
Toluene	PL NDS	NDS	100 mg/m3	
	PL NDS	NDSch	200 mg/m3	
n-heptane	PL NDS	NDS	1.200 mg/m3	
	PL NDS	NDSch	2.000 mg/m3	

NO

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Toluene	FOR-2011-12-06-1358	GV	25 ppm, 94 mg/m3	H,
n-heptane	FOR-2011-12-06-1358	GV	200 ppm, 800 mg/m3	

H Kjemikalier som kan tas opp gjennom huden.

NL

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Toluene	NL WG	TGG-8 uur	39 ppm, 150 mg/m3	
	NL WG	TGG-15 min	100 ppm, 384 mg/m3	
n-heptane	NL WG	TGG-8 uur	288 ppm, 1.200 mg/m3	
	NL WG	TGG-15 min	384 ppm, 1.600 mg/m3	

MT

Components	Basis	Value	Control parameters	Note
Toluene	MT OEL	TWA	50 ppm, 192 mg/m3	Skin,
	MT OEL	STEL	100 ppm, 384 mg/m3	Skin,
n-Heptane	MT OEL	TWA	500 ppm, 2.085 mg/m3	

Skin A skin notation assigned to the OEL identifies the possibility of significant uptake through the skin.

MK

Съставки	Основа	Стойност	Параметри на контрол	Бележка
Toluene	MK OEL	MV	50 ppm, 192 mg/m3	K,
n-heptane	MK OEL	MV	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	MK OEL	MV	500 ppm, 2.400 mg/m3	

K The properties of easier transport of substances into organism through (via) the skin

LV

Sastāvdaļas	Bāze	Vērtība	Kontroles parametri	Piezīme
Toluene	LV OEL	AER 8 st	14 ppm, 50 mg/m3	Āda,
	LV OEL	AER īslaicīgā	40 ppm, 150 mg/m3	Āda,
n-heptane	LV OEL	AER 8 st	85 ppm, 350 mg/m3	
	LV OEL	AER īslaicīgā	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	LV OEL	AER 8 st	100 mg/m3	
	LV OEL	AER īslaicīgā	300 mg/m3	

Āda Āda

LU

Composants	Base	Valeur	Paramètres de contrôle	Note
Toluene	LU OEL	TWA	50 ppm, 192 mg/m3	Peau,
	LU OEL	STEL	100 ppm, 384 mg/m3	Peau,
n-heptane	LU OEL	TWA	500 ppm, 2.085 mg/m3	

Peau Une pénétration cutanée s'ajoutant à l'inhalation réglementée est possible

LT

Komponentai	Šaltinis	Vertė	Kontrolės parametrai	Pastaba
Toluene	LT OEL	IPRD	50 ppm, 192 mg/m3	O,
	LT OEL	TPRD	100 ppm, 384 mg/m3	O,
n-heptane	LT OEL	IPRD	500 ppm, 2.085 mg/m3	
	LT OEL	TPRD	750 ppm, 3.128 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	LT OEL	IPRD	200 ppm, 900 mg/m3	
	LT OEL	TPRD	300 ppm, 1.400 mg/m3	

O patekimas per nepažeistą odą

IT

Componenti	Base	Valore	Parametri di controllo	Nota
Toluene	IT VLEP	TWA	50 ppm, 192 mg/m3	Cute,
n-heptane	IT VLEP	TWA	500 ppm, 2.085 mg/m3	

Cute La notazione che riporta il termine 'cute' per un valore limite di esposizione professionale, indica la possibilità di un assorbimento significativo attraverso la cute.

IS

Komponenter	Grunnlag	Verdi	Kontrollparametrer	Nota
Toluene	IS OEL	TWA	25 ppm, 94 mg/m3	H,
	IS OEL	STEL	50 ppm, 188 mg/m3	H,
n-heptane	IS OEL	TWA	200 ppm, 820 mg/m3	

H Skin notation

IE

Components	Basis	Value	Control parameters	Note
Toluene	IE OEL	OELV - 8 hrs (TWA)	50 ppm, 192 mg/m3	Skin,
	IE OEL	OELV - 15 min (STEL)	100 ppm, 384 mg/m3	Skin,
n-Heptane	IE OEL	OELV - 8 hrs (TWA)	500 ppm, 2.085 mg/m3	

Skin Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body

HU

Komponensek	Bázis	Érték	Ellenőrzési paraméterek	Megjegyzés
Toluene	HU OEL	AK-érték	50 ppm, 192 mg/m3	R+T, b, EU2, i,
	HU OEL	CK-érték	380 mg/m3	R+T, b, EU2, i,
n-heptane	HU OEL	AK-érték	2.000 mg/m3	R, EU1,
2,2,4-Trimethylpentane (Isooctane)	HU OEL	AK-érték	500 ppm, 2.350 mg/m3	R, i,
	HU OEL	CK-érték	4.700 mg/m3	R, i,
	HU OEL	CK-érték	1.000 ppm, 4.700 mg/m3	R, i,

b Bőrön át is felszívódik.
EU1 2000/39/EK irányelvben közölt érték
EU2 2006/15/EK irányelvben közölt érték
i Ingerlő anyag (izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat)
R Azok az anyagok, amelyek egészségkárosító hatása RÖVID expozíció hatására jelentkezik. Korrigált ÁK = ÁK x 8/a napi óraszám
R+T Azok az anyagok, amelyek RÖVID és TARTÓS expozíciója is egészségkárosodást okoz. Korrigált ÁK = ÁK x 8/a napi óraszám; Korrigált ÁK = ÁK x 40/a heti óraszám. A két faktor közül a szigorúbb (kisebb) értéket kell alkalmazni

HR

Sastojci	Temelj	Vrijednost	Nadzorni parametri	Bilješka
Toluene	HR OEL	GVI	50 ppm, 192 mg/m3	koža,
	HR OEL	KGVI	100 ppm, 384 mg/m3	koža,
n-heptane	HR OEL	GVI	500 ppm, 2.085 mg/m3	koža,
	HR OEL		500 ppm, 2.000 mg/m3	

koža Razvrstana kao tvar koja nadražuje kožu (H315) ili je takva napomena navedena u direktivama

GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Toluene	GR OEL	TWA	50 ppm, 192 mg/m3	Δ,
	GR OEL	STEL	100 ppm, 384 mg/m3	Δ,
n-heptane	GR OEL	TWA	500 ppm, 2.000 mg/m3	
	GR OEL	STEL	500 ppm, 2.000 mg/m3	

Δ Η ένδειξη 'δέρμα' (Δ), η οποία επισημαίνει ορισμένους χημικούς παράγοντες του πίνακα της παρ. 1 του άρθρου 3, υπονοεί την πιθανή συμβολή στην συνολική έκθεση του εργαζόμενου και της ποσότητας αυτών των χημικών παραγόντων που απορροφάται διαμέσου του δέρματος κατά την άμεση επαφή μαζί τους.

GB

Components	Basis	Value	Control parameters	Note
Toluene	GB EH40	TWA	50 ppm, 191 mg/m3	Sk,
	GB EH40	STEL	100 ppm, 384 mg/m3	Sk,
n-Heptane	GB EH40	TWA	500 ppm, 2.085 mg/m3	

Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

FR

Composants	Base	Valeur	Paramètres de contrôle	Note
Toluene	FR VLE	VME	20 ppm, 76,8 mg/m3	R2, Peau, VLR contraignantes,
	FR VLE	VLCT (VLE)	100 ppm, 384 mg/m3	R2, Peau, VLR contraignantes,
n-heptane	FR VLE	VME	400 ppm, 1.668 mg/m3	VLR contraignantes,
	FR VLE	VLCT (VLE)	500 ppm, 2.085 mg/m3	VLR contraignantes,
2,2,4-Trimethylpentane (Isooctane)	FR VLE	VME	1.000 mg/m3	Valeurs limites admises (circulaires), Vapeur
	FR VLE	VLCT (VLE)	1.500 mg/m3	Valeurs limites admises (circulaires), Vapeur

Peau Risque de pénétration percutanée
R2 Toxique pour la reproduction de catégorie 2 - Substances preoccupantes en raison d'effets toxiques pour la reproduction possibles
Valeurs limites admises (circulaires) Valeurs limites admises (circulaires)
VLR contraignantes Valeurs limites réglementaires contraignantes

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Huomautus
Toluene	FI OEL	HTP-arvot 8h	25 ppm, 81 mg/m3	melu, iho,
	FI OEL	HTP-arvot 15 min	100 ppm, 380 mg/m3	melu, iho,
n-heptane	FI OEL	HTP-arvot 8h	300 ppm, 1.200 mg/m3	
	FI OEL	HTP-arvot 15 min	500 ppm, 2.100 mg/m3	
	FI OEL	HTP-arvot 8h	300 ppm, 1.200 mg/m3	
	FI OEL	HTP-arvot 15 min	500 ppm, 2.100 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	FI OEL	HTP-arvot 8h	300 ppm, 1.400 mg/m3	
	FI OEL	HTP-arvot 15 min	380 ppm, 1.800 mg/m3	

iho Ihon läpi imeytyvien aineiden elimistöön joutuvia määriä ja elimistöön joutuneesta aineesta aiheutuvaa vaaraa ei voida näin ollen arvioida pelkästään ilmapitoisuuksien avulla.Tämän vuoksi näiden aineiden HTP-arvojen yhteyteen on huomautussarakkeeseen otettu ihon läpi imeytymisen osoittamiseksi merkintä 'iho'. Monet aineet, varsinkin voimakkaat hapot tai emäkset, voivat aiheuttaa iholle jouduttuaan ihon ärsyyntymistä tai syöpymistä.
melu Melu: aineille, joiden tiedetään voimistavan melun haitallisia kuulovaikutuksia.

ES

Componentes	Base	Valor	Parámetros de control	Nota
Toluene	ES VLA	VLA-ED	50 ppm, 192 mg/m3	vía dérmica,
	ES VLA	VLA-EC	100 ppm, 384 mg/m3	vía dérmica,
n-heptane	ES VLA	VLA-ED	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	ES VLA	VLA-ED	300 ppm, 1.420 mg/m3	

vía dérmica Vía dérmica

EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Toluene	EE OEL	Piirnorm	50 ppm, 192 mg/m3	A,
	EE OEL	Lühiajalise kokkupuute piirnorm	100 ppm, 384 mg/m3	A,
n-heptane	EE OEL	Piirnorm	500 ppm, 2.085 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	EE OEL	Piirnorm	200 ppm, 900 mg/m3	
	EE OEL	Lühiajalise kokkupuute piirnorm	300 ppm, 1.400 mg/m3	

A Naha kaudu kergesti absorbeeruvad ained

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
Toluene	DK OEL	GV	25 ppm, 94 mg/m3	H,
	DK OEL	S	100 ppm, 384 mg/m3	H,
n-heptane	DK OEL	GV	200 ppm, 820 mg/m3	
	DK OEL	S	400 ppm, 1.640 mg/m3	

H Betyder, at stoffet kan optages gennem huden.

DE

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	DE TRGS 900	AGW	50 ppm, 190 mg/m3	H, Y,
	DE DFG MAK	MAK	50 ppm, 190 mg/m3	H, C,
n-heptane	DE DFG MAK	MAK	500 ppm, 2.100 mg/m3	D,
	DE TRGS 900	AGW	500 ppm, 2.100 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	DE DFG MAK	MAK	100 ppm, 470 mg/m3	D,

C Eine fruchtschädigende Wirkung ist bei Einhaltung des MAK- und BATWertes nicht anzunehmen
D Für die Beurteilung der fruchtschädigenden Wirkung ggf. inklusive der entwicklungsneurotoxischen Wirkung liegen entweder keine Daten vor oder die vorliegenden Daten reichen für eine Einstufung in eine der Gruppen A, B oder C nicht aus
H Hautresorptiv
Y Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden

CZ

Složky	Základ	Hodnota	Kontrolní parametry	Poznámka
Toluene	CZ OEL	PEL	50 ppm, 192 mg/m3	I, D,
	CZ OEL	NPK-P	100 ppm, 384 mg/m3	I, D,
n-heptane	CZ OEL	PEL	240 ppm, 1.000 mg/m3	I,
	CZ OEL	NPK-P	480 ppm, 2.000 mg/m3	I,

D Při expozici se významně uplatňuje pronikání faktoru kůží
I dráždí sliznice (oči, dýchací cesty), respektive kůži

CY

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Toluene	CY OEL	TWA	50 ppm, 192 mg/m3	
	CY OEL	STEL	100 ppm, 384 mg/m3	
n-heptane	CY OEL	TWA	500 ppm, 2.085 mg/m3	

CH

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung

Toluene	CH SUVA	MAK-Wert	50 ppm, 190 mg/m3	OL, R2, H, NIOSH, DFG, INRS, HSE, SSc,
	CH SUVA	KZGW	200 ppm, 760 mg/m3	OL, R2, H, NIOSH, DFG, INRS, HSE, SSc,
n-heptane	CH SUVA	KZGW	400 ppm, 1.600 mg/m3	NIOSH,
	CH SUVA	MAK-Wert	400 ppm, 1.600 mg/m3	NIOSH,
2,2,4-Trimethylpentane (Isooctane)	CH SUVA	MAK-Wert	300 ppm, 1.400 mg/m3	NIOSH,
	CH SUVA	KZGW	600 ppm, 2.800 mg/m3	NIOSH,
	CH SUVA	MAK-Wert	100 ppm, 470 mg/m3	
	CH SUVA	KZGW	200 ppm, 940 mg/m3	

DFG Deutsche Forschungsgemeinschaft
H Vergiftung durch Hautresorption möglich; Bei Stoffen, welche die Haut leicht zu durchdringen vermögen, kann durch die zusätzliche Hautresorption die innere Belastung wesentlich höher werden als bei alleiniger Aufnahme durch die Atemwege.
HSE Gesundheits- und Sicherheitsbeauftragter (Labor für Arbeitsmedizin und Hygiene)
INRS Nationales Institut für Forschung und Sicherheit zur Prävention von Arbeitsunfällen und Berufskrankheiten
NIOSH Nationales Institut für Arbeitssicherheit und Gesundheit
OL lärmverstärkende Ototoxizität
R2 Möglicherweise reproduktionstoxischer Stoff
SSc Eine Schädigung der Leibesfrucht braucht bei Einhaltung des MAK-Wertes nicht befürchtet zu werden.

BG

Съставки	Основа	Стойност	Параметри на контрол	Бележка
Toluene	BG OEL	TWA	50 ppm, 192 mg/m3	
	BG OEL	STEL	100 ppm, 384 mg/m3	
n-heptane	BG OEL	TWA	1.600 mg/m3	

BE

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Toluene	BE OEL	TGG 8 hr	20 ppm, 77 mg/m3	D,
	BE OEL	TGG 15 min	100 ppm, 384 mg/m3	D,
n-heptane	BE OEL	TGG 8 hr	400 ppm, 1.664 mg/m3	
	BE OEL	TGG 15 min	500 ppm, 2.085 mg/m3	

D Opname van het agens via de huid, de slijmvliezen of de ogen vormt een belangrijk deel van de totale blootstelling. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.

AT

Inhaltsstoffe	Grundlage	Wert	Zu überwachende Parameter	Bemerkung
Toluene	AT OEL	MAK-TMW	50 ppm, 190 mg/m3	H,
	AT OEL	MAK-KZW	100 ppm, 380 mg/m3	H,
n-heptane	AT OEL	MAK-TMW	500 ppm, 2.000 mg/m3	
	AT OEL	MAK-KZW	2.000 ppm, 8.000 mg/m3	
2,2,4-Trimethylpentane (Isooctane)	AT OEL	MAK-TMW	300 ppm, 1.400 mg/m3	
	AT OEL	MAK-KZW	1.200 ppm, 5.600 mg/m3	

H Besondere Gefahr der Hautresorption

Biological exposure indices

SK

Názov látky	Č. CAS	Kontrolné parametre	Doba odberu vzorky	Aktualizácia
Toluene	108-88-3	toluén: 600 µg/l (Krv)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		toluén: 6.517 µmol.l-1 (Krv)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 2.401 mg/l (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 13399 µmol.l-1 (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 1600 mg/g kreatinínu (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18
		kyselina hippurová: 1010 µmol/mmol kreatinínu (moč)	Koniec vystavenia alebo pracovnej zmeny	2016-01-18

		o-krezol: 14.3 µmol.l-1 (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18
		o-krezol: 1.03 mg/g kreatinínu (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18
		o-krezol: 1.08 µmol/mmol kreatinínu (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18
		o-krezol: 1,5 mg/l (moč)	Pri dlhodobej expozícii; po viacerých predchádzajúcich pracovných zmenáchKoniec vystavenia alebo pracovnej zmeny	2016-01-18

SI

Ime snovi	Št. CAS	Parametri nadzora	Čas vzorčenja	Sprememba
Toluene	108-88-3	toluen: 600 µmol/l (Kri)	Ob koncu delovne izmene	2021-05-11
		toluen: 75 µg/l (Urin)	Ob koncu delovne izmene	2021-05-11
		o-krezol: 1,5 mg/l po hidrolizi (Urin)	pri dolgotrajni izpostavljenosti: ob koncu delovne izmene po več zaporednih delavnikihOb koncu delovne izmene	2021-05-11

RO

Numele substanţei	Nr. CAS	Parametri de control	Timp de prelevare a probei	Adus la zi
Toluene	108-88-3	o-cresol: 3 mg/l (Urină)	Sfârşit schimb	2018-08-17
		acid hipuric: 2 g/l (Urină)	Sfârşit schimb	2018-08-17

PT

Nome da substância	Número de registro CAS	Parâmetros de controle	Tempo de amostragem	Atualização
Toluene	108-88-3	Tolueno: 0,02 mg/l (Sangue)	Antes do último turno da semana de trabalho	2014-11-14
		Tolueno: 0,03 mg/l (Urina)	Fim do turno	2014-11-14
		o-Cresol: 0.3 mg/g creatinina Com hidrólise (Urina) Valor basal ()	Fim do turno	2014-11-14

LV

Vielas nosaukums	CAS Nr.	Kontroles parametri	Parauga ņemšanas laiks	Precizējums
Toluene	108-88-3	toluols: 75 µg/l (Urīns)	maiņas beigās nosaka	2024-04-03

		toluols: 600 µg/l (Asinis)	uzreiz, beidzoties iedarbībai	2024-04-03
		o-krezol: 1,5 mg/l pēc hidrolīzes (Urīns)	Ekspozīcijas beigas vai maiņas beigas	2024-04-03

IT

Denominazione della sostanza	N. CAS	Parametri di controllo	Tempo di campionamento	Aggiornamento

HU

Az anyag megnevezése	CAS szám	Ellenőrzési paraméterek	Mintavétel időpontja	Aktualizálás
Toluene	108-88-3	o-krezol: 1 mg/g kreatinin (húgyhólyag)	A műszak végén	2020-02-06
		o-krezol: 1 µmol/mmol kreatinin (kerekített értékek) (húgyhólyag)	A műszak végén	2020-02-06

HR

Naziv tvari	CAS-br.	Nadzorni parametri	Vrijeme uzorkovanja	Ažurirati
Toluene	108-88-3	toluen: 10.85 µmol/l (Krv)	na kraju radne smjene	2018-10-12
		toluen: 1 mg/l (Krv)	na kraju radne smjene	2018-10-12
		toluen: 0.83 µmol/l (krajnje izdahnuti zrak)	za vrijeme izloženosti	2018-10-12
		toluen: 20 dijelova na milijun (krajnje izdahnuti zrak)	za vrijeme izloženosti	2018-10-12
		hipurna kiselina: 1.58 mol/mol kreatinina Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin) hrana bogata voćem i povrćem te konzervirana Na-benzoatom povisuje nalaz ()	na kraju radne smjene	2018-10-12
		hipurna kiselina: 2.5 g/g kreatinin Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin) hrana bogata voćem i povrćem te konzervirana Na-benzoatom povisuje nalaz ()	na kraju radne smjene	2018-10-12
		o-krezol: 1.05 mmol/mol kreatinina Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin)	na kraju radne smjene	2018-10-12
		o-krezol: 1 mg/g kreatinina Računato na prosječnu vrijednost kreatinina od 1,2 g/L urina. Za sve rezultate koji se izražavaju na kreatinin, koncentracije kreatinina < 0,5 g/L i > 3,0 g/L ne mogu se uzeti u obzir. (Urin)	na kraju radne smjene	2018-10-12

FI

Aineen nimi	CAS-Nro.	Valvontaa koskevat muuttujat	Näytteenottoaika	Päivämäärä
Toluene	108-88-3	tolueeni: 500 nmol/l (Veri)	Työpäivän jälkeinen aamu	2016-12-22

ES

Nombre de la sustancia	No. CAS	Parámetros de control	Hora de muestreo	Puesto al día

Toluene	108-88-3	o-cresol: 0.6 mg/g creatinina Cuando el final de la exposición no coincida con el final de la jornada laboral, la muestra se tomará lo antes posible después de que cese la exposición real (Orina) Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB. ()	Final de la jornada laboral	2018-02-19
		tolueno: 0,05 mg/l Antes del comienzo de la quinta jornada consecutiva de exposición. (Sangre)	principio de la última jornada de la semana laboral	2018-02-19
		tolueno: 0,08 mg/l Cuando el final de la exposición no coincida con el final de la jornada laboral, la muestra se tomará lo antes posible después de que cese la exposición real (Orina)	Final de la jornada laboral	2018-02-19

DE

Stoffname	CAS-Nr.	Zu überwachende Parameter	Probennahmezeitpunkt	Stand
Toluene	108-88-3	Toluol: 600 µg/l (Blut)	Schichtende	2024-08-16
		o-Kresol: 1,5 mg/l Nach Hydrolyse (Urin)	bei Langzeitexposition: nach mehreren vorangegangenen Schichten	2024-08-16
		Toluol: 75 µg/l (Urin)	Expositionsende, bzw. Schichtende	2024-08-16
		Toluol: 75 µg/l vgl. Abschn. XIII.1 (Urin)	Expositionsende, bzw. Schichtende	2024-07-01
		Toluol: 600 µg/l vgl. Abschn. XIII.1 (Blut)	Schichtende	2024-07-01
		o-Kresol: 1,5 mg/l nach Hydrolyse (Urin) vgl. Abschn. XIII.1 ()	Expositionsende, bzw. Schichtende	2024-07-01
n-heptane	142-82-5	Heptan-2,5-dion: 250 µg/l vgl. Abschn. XIII.1 (Urin)	Expositionsende, bzw. Schichtende	2023-07-01
		Heptan-2,5-dion: 250 µg/l (Urin)	Expositionsende, bzw. Schichtende	2022-02-25

CZ

Název látky	Č. CAS	Kontrolní parametry	Doba odběru vzorku	Aktualizace
Toluene	108-88-3	Hippurová kyselina: 1600 mg/g kreatininu Je-li hodnota při nálezu kyseliny hippurové vyšší než 1600 mg/g, avšak nepřesahuje 2500 mg/g kreatininu, použije se ke zpřesnění expozice toluenu biologický expoziční test podle ukazatele o-Kresol. Je-li hodnota při nálezu kyseliny hippurové vyšší než 2500 mg/g, považuje se za hodnotu prokazující, že jde o pracovní expozici toluenu, jehož hodnota PEL je překračována a biologický expoziční test podle ukazatele o-Kresol se již neprovádí (moč)	Konec směny	2013-04-22

		Hippurová kyselina: 1000 µmol/mmol kreatininu Je-li hodnota při nálezu kyseliny hippurové vyšší než 1600 mg/g, avšak nepřesahuje 2500 mg/g kreatininu, použije se ke zpřesnění expozice toluenu biologický expoziční test podle ukazatele o-Kresol. Je-li hodnota při nálezu kyseliny hippurové vyšší než 2500 mg/g, považuje se za hodnotu prokazující, že jde o pracovní expozici toluenu, jehož hodnota PEL je překračována a biologický expoziční test podle ukazatele o-Kresol se již neprovádí (moč)	Konec směny	2013-04-22
		o-Kresol: 1.5 mg/g kreatininu Po hýdrolyse (moč)	Konec směny	2013-04-22
		o-Kresol: 1.6 µmol/mmol kreatininu Po hýdrolyse (moč)	Konec směny	2013-04-22

CH

Stoffname	CAS-Nr.	Zu überwachende Parameter	Probennahmezeitpunkt	Stand
Toluene	108-88-3	o-Kresol: 0,5 mg/l Quantitative Interpretation schwierig; Bei den mit Q gekennzeichneten biologischen Parametern ist die exakte quantitative Interpretation schwierig. Als Screening-Test kann der biologische Parameter verwendet werden, ebenfalls als Zusatzuntersuchung nach der Bestimmung nicht spezifischer Parameter (N). (Urin)	Expositionsende, bzw. Schichtendebei Langzeitexposition: nach mehreren vorangegangenen Schichten	2022-05-10
		Hippursäure: 2 g/g Kreatinin Nicht spezifischer Parameter; Die mit N gekennzeichneten biologischen Parameter sind nicht für den aufgeführten Arbeitsstoff spezifisch, sondern können auch nach Expositionen gegenüber bestimmten anderen Arbeitsstoffen im biologischen Material gemessen werden. In der Praxis hat sich die Bestimmung dieser Stoffe jedoch bewährt. Bei speziellen Problemen empfiehlt sich zusätzlich die Bestimmung eines spezifischen Parameters. (Urin) Umwelteinflüsse; Die mit X gekennzeichneten biologischen Parameter werden auch in unterschiedlicher Quantität bei beruflich Nichtexponierten gemessen, da sie zusätzlich auf Umwelteinflüsse zurückgeführt werden können. Die Festsetzung des BAT-Wertes berücksichtigt bei diesen Parametern auch die Einflüsse von Umweltfaktoren. ()	Expositionsende, bzw. Schichtendebei Langzeitexposition: nach mehreren vorangegangenen Schichten	2022-05-10
		Toluol: 6.48 µmol/l (Blut)	Expositionsende, bzw. Schichtende	2022-05-10
		Toluol: 75 µg/l (Urin)	Expositionsende, bzw. Schichtende	2022-05-10

		o-Kresol: 4.62 µmol/l Quantitative Interpretation schwierig; Bei den mit Q gekennzeichneten biologischen Parametern ist die exakte quantitative Interpretation schwierig. Als Screening-Test kann der biologische Parameter verwendet werden, ebenfalls als Zusatzuntersuchung nach der Bestimmung nicht spezifischer Parameter (N). (Urin)	Expositionsende, bzw. Schichtendebei Langzeitexposition: nach mehreren vorangegangenen Schichten	2022-05-10
		Toluol: 600 µg/l (Blut)	Expositionsende, bzw. Schichtende	2022-05-10
		Hippursäure: 1.26 mmol/mmol Kreatinin Nicht spezifischer Parameter; Die mit N gekennzeichneten biologischen Parameter sind nicht für den aufgeführten Arbeitsstoff spezifisch, sondern können auch nach Expositionen gegenüber bestimmten anderen Arbeitsstoffen im biologischen Material gemessen werden. In der Praxis hat sich die Bestimmung dieser Stoffe jedoch bewährt. Bei speziellen Problemen empfiehlt sich zusätzlich die Bestimmung eines spezifischen Parameters. (Urin) Umwelteinflüsse; Die mit X gekennzeichneten biologischen Parameter werden auch in unterschiedlicher Quantität bei beruflich Nichtexponierten gemessen, da sie zusätzlich auf Umwelteinflüsse zurückgeführt werden können. Die Festsetzung des BAT-Wertes berücksichtigt bei diesen Parametern auch die Einflüsse von Umweltfaktoren. ()	Expositionsende, bzw. Schichtendebei Langzeitexposition: nach mehreren vorangegangenen Schichten	2022-05-10
n-heptane	142-82-5	Heptan-2,5-dion: 200 µg/l (Urin)	Expositionsende, bzw. Schichtende	2023-01-02

BG

Наименование на веществото	CAS номер	Параметри на контрол	Време на взимане на пробата	Последна актуализация
Toluene	108-88-3	хипурова киселина: 1.6 mmol/mmol креатинин (Урина)	В края на експозицията или в края на работната смяна	2007-08-17

AT

Stoffname	CAS-Nr.	Zu überwachende Parameter	Probennahmezeitpunkt	Stand
Toluene	108-88-3	o-Cresol: 0,8 mg/l Bei wiederholt erhöhten o-Cresolwerten ist zusätzlich Toluol im Blut am Ende eines Arbeitstages zu bestimmen (der Zeitpunkt der Untersuchung ist anzugeben). (Urin)	Nach Ablauf einer Arbeitswoche/am Ende des Arbeitstages/am Schichtende	2014-02-18
		Toluol: 250 µg/l (Blut)	Am Ende eines Arbeitstages	2014-02-18

8.2

Exposure controls
Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits.

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection	:	If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
Hand protection	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	:	Eye wash bottle with pure water. Tightly fitting safety goggles.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

9.1

Information on basic physical and chemical properties

Appearance

Form	:	Non-viscous, liquid
Physical state	:	liquid
Color	:	Clear
Odor	:	Strong gasoline

Safety data

Flash point	:	4°C (39°F) Method: closed cup estimated

Lower explosion limit	:	1,1 %(V)
Upper explosion limit	:	7,1 %(V)
Oxidizing properties	:	No
Autoignition temperature	:	528,9°C (984,0°F)
Molecular formula	:	Mixture
Molecular weight	:	Not applicable
pH	:	Not applicable
Freezing point	:	-94,44°C (-137,99°F)
Pour point		No data available
Boiling point/boiling range	:	99°C (210°F)
Vapor pressure	:	30,00 MMHG estimated
Relative density	:	0,823 at 15,6 °C (60,1 °F)
Density	:	0,823 g/cm3
Water solubility	:	negligible
Partition coefficient: n-octanol/water	:	No data available
Viscosity, kinematic	:	No data available
Relative vapor density	:	3,2 (Air = 1.0)
Evaporation rate	:	4,5
Percent volatile	:	0,02 %

9.2

Other information

Conductivity	:	No data available

SECTION 10: Stability and reactivity

10.1

Reactivity	:	Stable under recommended storage conditions.

10.2

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3

Possibility of hazardous reactions

Hazardous reactions : Hazardous reactions: Hazardous polymerization does not occur., Vapors may form explosive mixture with air.

10.4

Conditions to avoid : Heat, flames and sparks.

10.5

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

10.6

Hazardous decomposition products : Hydrocarbons
Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1

Information on toxicological effects

Toluene Standardization Fuel 96.9
Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg
Method: Calculation method

Toluene Standardization Fuel 96.9
Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Toluene Standardization Fuel 96.9
Acute dermal toxicity : Acute toxicity estimate: > 5.000 mg/kg
Method: Calculation method

Toluene Standardization Fuel 96.9
Skin irritation : Skin irritation
largely based on animal evidence.
May cause skin irritation in susceptible persons.

Toluene Standardization Fuel 96.9
Eye irritation : Vapors may cause irritation to the eyes, respiratory system and the skin.
Vapors may cause irritation to the eyes, respiratory system and the skin.

Toluene Standardization Fuel 96.9

Sensitization : Does not cause skin sensitization.
largely based on animal evidence.

Repeated dose toxicity

Toluene : Species: Rat
Application Route: Inhalation
Dose: 0, 100, 625, 1250, 3000 ppm
Exposure time: 15 wk
Number of exposures: 6.5 h/d, 5 d/wk
NOEL: 625 ppm

Species: Mouse
Application Route: Inhalation
Dose: 0, 100, 625, 1250, 3000 ppm
Exposure time: 14 wk
Number of exposures: 6.5 h/d, 5 d/wk
NOEL: 100 ppm

n-Heptane Species: Rat, male
Sex: male
Application Route: Inhalation
Dose: 12.47 mg/l
Exposure time: 16 wk
Number of exposures: 12 h/d, 7 d/wk
NOEL: 12,47 mg/l
No adverse effect has been observed in chronic toxicity tests.

Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 12.35 mg/l
Exposure time: 26 wk
Number of exposures: 6 h/d, 5 d/wk
Method: OECD Test Guideline 413
No adverse effect has been observed in chronic toxicity tests.

2,2,4-Trimethylpentane (Isooctane) Species: Rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 0, 668, 2220, 6646 ppm
Exposure time: 13 weeks
Number of exposures: 6 hr/day 5 d/wk
NOEL: 8,117 mg/l 2220 ppm
Method: OECD Guideline 413
Information given is based on data obtained from similar substances.

Genotoxicity in vitro

Toluene : Test Type: Ames test
Result: negative

	Test Type: Sister Chromatid Exchange Assay Result: negative Test Type: Mouse lymphoma assay Result: negative Test Type: Cytogenetic assay Result: negative
n-Heptane	Test Type: Ames test Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: negative Test Type: Mammalian cell gene mutation assay Method: OECD Guideline 476 Result: negative Test Type: Chromosome aberration test in vitro Method: OECD Guideline 473 Result: negative Test Type: Mitotic recombination Result: negative
2,2,4-Trimethylpentane (Isooctane)	Test Type: Ames test Method: Mutagenicity (Escherichia coli - reverse mutation assay) Result: negative Test Type: Mouse lymphoma assay Method: OECD Guideline 476 Result: negative Test Type: Sister Chromatid Exchange Assay Result: negative Test Type: Unscheduled DNA synthesis assay Result: negative

Genotoxicity in vivo

Toluene	:	Test Type: Cytogenetic assay Result: negative Test Type: Mouse micronucleus assay Result: negative
2,2,4-Trimethylpentane (Isooctane)		Test Type: Unscheduled DNA synthesis assay Species: Mouse Dose: 500 mg/kg Result: negative Test Type: Unscheduled DNA synthesis assay Species: Rat Dose: 500 mg/kg Result: negative

Carcinogenicity

Toluene	:	Species: Rat Dose: 0, 600, 1200 ppm Exposure time: 2 yrs Number of exposures: 6.5 h/d, 5 d/wk Remarks: No evidence of carcinogenicity Species: Mouse Dose: 0, 600, 1200 ppm Exposure time: 2 yrs Number of exposures: 6.5 h/d, 5 d/wk Remarks: No evidence of carcinogenicity

Reproductive toxicity

Toluene	:	Species: Rat Application Route: Inhalation Dose: 0, 100, 500, 2000 ppm Test period: 95 d NOAEL Parent: 2000 ppm
n-Heptane		Species: Rat Sex: male and female Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 hr/d, 5 d/wk Test period: 13 wk Method: OECD Test Guideline 416 NOAEL Parent: 3000ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm Information given is based on data obtained from similar substances.
2,2,4-Trimethylpentane (Isooctane)		Species: Rat Sex: male and female Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Number of exposures: 6 h/d 5 d/wk Method: OECD Test Guideline 416 NOAEL Parent: 3000 ppm NOAEL F1: 3000 ppm NOAEL F2: 3000 ppm Information given is based on data obtained from similar substances.

Developmental Toxicity

Toluene	:	Species: Rat Application Route: Inhalation Dose: 0, 100, 500, 2000 ppm Test period: 95 d NOAEL Teratogenicity: 400-750 ppm
n-Heptane		Species: Rat Application Route: Inhalation Dose: 0, 900, 3000, 9000 ppm Exposure time: GD6-15

Number of exposures: 6 hrs/d
NOAEL Teratogenicity: 9000 ppm
NOAEL Maternal: 3000 ppm

2,2,4-Trimethylpentane (Isooctane)

Species: Rat
Application Route: Inhalation
Dose: 0, 400, 1200 ppm
Number of exposures: 6h/d
Test period: GD6-15
NOAEL Teratogenicity: 1200 ppm
NOAEL Maternal: 1200 ppm
Information given is based on data obtained from similar substances.

Species: Rat
Application Route: Inhalation
Dose: 0, 900, 3000, 9000 ppm
Number of exposures: 6h/d
Test period: GD6-15
Method: OECD Guideline 414
NOAEL Teratogenicity: 9000 ppm
NOAEL Maternal: 3000 ppm
Information given is based on data obtained from similar substances.

Toluene Standardization Fuel 96.9
Aspiration toxicity : May be fatal if swallowed and enters airways.

CMR effects

Toluene : Carcinogenicity: Not classifiable as a human carcinogen.
Mutagenicity: Animal testing did not show any mutagenic effects.
Teratogenicity: Some evidence of adverse effects on development, based on animal experiments.
Reproductive toxicity: Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

n-Heptane

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Teratogenicity: Animal testing did not show any effects on fetal development.
Reproductive toxicity: No toxicity to reproduction

2,2,4-Trimethylpentane (Isooctane)

Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
Teratogenicity: Animal testing did not show any effects on fetal development.
Reproductive toxicity: Animal testing did not show any effects on fertility.

11.2
Information on other hazards

Toluene Standardization Fuel 96.9
Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents

may degrease the skin.

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1

Toxicity

Toxicity to fish

Toluene	:	LC50: 18 - 36 mg/l Exposure time: 96 h Species: Pimephales promelas (fathead minnow)
n-Heptane		LL50: 5,738 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) Method: QSAR modeled data
2,2,4-Trimethylpentane (Isooctane)		LC50: 0,11 mg/l Exposure time: 96 h Species: Oncorhynchus mykiss (rainbow trout) semi-static test Method: OECD Test Guideline 203 Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates

Toluene	:	EC50: 3,78 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)
n-Heptane		EC50: 1,5 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Toxic to aquatic organisms. LC50: 0,1 mg/l Exposure time: 96 h Species: Mysidopsis bahia (mysid shrimp) semi-static test Very toxic to aquatic organisms.
2,2,4-Trimethylpentane (Isooctane)		EC50: 0,4 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) static test Information given is based on data obtained from similar substances.

Toxicity to algae

Toluene	:	EC50: 134 mg/l Exposure time: 72 h

	Species: Chlamydomonas angulosa (Green algae)
n-Heptane	EL50: 4,338 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (microalgae) Method: QSAR
2,2,4-Trimethylpentane (Isooctane)	EL50: 2,943 mg/l Exposure time: 72 h Method: QSAR modeled data

Toxicity to fish (Chronic toxicity)

n-Heptane	:	NOELR: 1,284 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: QSAR modeled data

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

2,2,4-Trimethylpentane (Isooctane)	:	NOEL: 0,17 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 Information given is based on data obtained from similar substances.

12.2
Persistence and degradability

Biodegradability

Toluene	:	This material is expected to be readily biodegradable.
n-Heptane	:	Result: Readily biodegradable. 70 % Testing period: 10 d
2,2,4-Trimethylpentane (Isooctane)	:	Result: Not readily biodegradable. Method: OECD Test Guideline 301 Expected to be inherently biodegradable. Information given is based on data obtained from similar substances.

12.3
Bioaccumulative potential

Bioaccumulation

Toluene	:	This material is not expected to bioaccumulate.
n-Heptane	:	Bioconcentration factor (BCF): 552 Method: QSAR modeled data This material is not expected to bioaccumulate.
2,2,4-Trimethylpentane (Isooctane)	:	Bioconcentration factor (BCF): 231 Method: QSAR modeled data

This material is not expected to bioaccumulate.

12.4
Mobility in soil

Mobility

Toluene	:	Not expected to adsorb on soil.
n-Heptane	:	Medium: Air Method: Calculation, Mackay Level I Fugacity Model Content: 100 % After release, disperses into the air.
2,2,4-Trimethylpentane (Isooctane)	:	Medium: Air Method: Calculation, Mackay Level I Fugacity Model After release, disperses into the air.

12.5
Results of PBT and vPvB assessment

Results of PBT assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6
Endocrine disrupting properties

Endocrine disrupting properties	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7
Other adverse effects

Additional ecological information	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

12.8
Additional Information

Ecotoxicology Assessment

Short-term (acute) aquatic hazard

Toluene	:	Toxic to aquatic life.
n-Heptane	:	Very toxic to aquatic life.
2,2,4-Trimethylpentane (Isooctane)	:	Very toxic to aquatic life.

Long-term (chronic) aquatic hazard

Toluene	:	Harmful to aquatic life with long lasting effects.
n-Heptane	:	Very toxic to aquatic life with long lasting effects.

2,2,4-Trimethylpentane (Isooctane)	:	Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1

Waste treatment methods

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 - 14.7

Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, MARINE POLLUTANT, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (4 °C c.c.), MARINE POLLUTANT, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))
33,UN1268,PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)
UN1268, PETROLEUM PRODUCTS, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS, (HEPTANE, 2,2,4-TRIMETHYLPENTANE (ISOOCTANE))

Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1

Safety, health and environmental regulations/legislation specific for the substance or mixture
National legislation

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

15.2

Major Accident Hazard Legislation	:	96/82/EC Update: 2003 Highly flammable 7b Quantity 1: 5.000 t Quantity 2: 50.000 t
	:	96/82/EC Update: 2003 Dangerous for the environment 9b Quantity 1: 200 t Quantity 2: 500 t
	:	ZEU_SEVES3 Update: FLAMMABLE LIQUIDS P5c Quantity 1: 5.000 t Quantity 2: 50.000 t

Notification status

Europe EU REACH	:	This mixture contains only ingredients which have been registered according to Regulation (EU) No. 1907/2006 (REACH).
Switzerland CH INV	:	On the inventory, or in compliance with the inventory
United States of America (USA) US TSCA	:	On or in compliance with the active portion of the TSCA inventory
Canada CA. DSL	:	All components of this product are on the Canadian DSL

Australia AU AIIC	:	On the inventory, or in compliance with the inventory
New Zealand NZ NZIoC	:	Not in compliance with the inventory
Japan JP ENCS	:	On the inventory, or in compliance with the inventory
Japan JP ISHL	:	On the inventory, or in compliance with the inventory
Korea KR KECI	:	A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations.
Philippines PH PICCS	:	On the inventory, or in compliance with the inventory
China CN IECSC	:	On the inventory, or in compliance with the inventory
Taiwan TW TCSI	:	On the inventory, or in compliance with the inventory

SECTION 16: Other information

Revision Date : 2026-10-26
Date of last issue : 2023-08-03

Print Date : 2026-11-05

Further information

Legacy SDS Number : 26820

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AIIC	Australian Inventory of Industrial Chemicals	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.